

JK White Cement Works, Gotan

A Unit of JK Cement Ltd.

CIN: L17229UP1994PLC017199

n P.O. Gotan - 342 902, Dist - Nagaur (Rajasthan), India

# www.jkcement.com

#### **REG/AD & MAIL**

GTN: WH: ENV: EC:/

Date: 23.05.2025

The Director,

Ministry of Environment, Forest & Climate Change (Integrated Regional Office), A-209 & 218, "ARANYA BHAWAN", Jhalana Institutional Area, Jaipur-302004 Tel No: 0141-2713786, 2713778 Email: iro.jaipur-mefcc@gov.in

Subject:

Half Yearly Compliance Report of Environmental Clearance conditions of M/s JK White Cement

Works, (Unit of JK Cement Ltd.) situated at P.O. Gotan, Tehsil - Merta, Distt. Nagaur, Rajasthan

for the Period from 1st Oct, 2024 to 31st Marc, 2025.

Ref.:

EC Letter No. F1 (4)/SEIAA/SEAC-Raj/Sectt/Project/Cat. 7(d) B1 (367)/2018-19 dated: 29.03.2019

Sir.

As above subjected matter, submitting herewith the point - wise compliance report

Name of the Project

: Expansion of White Cement from 618000 TPA to 880000 MTPA

Clearance Letter No.

: EC Letter No. F1 (4)/SEIAA/SEAC-Raj/Sectt/Project/Cat. 7(d) B1 (367)/2018-19

dated: 29.03.2019

#### A. SPECIFIC CONDITIONS:

Sr.	Conditions	Compliance Status
1	The production capacity of the industry will not exceed more than 8, 80,000 TPA cement.	The annual production is within specified quantity (880000 TPA).  FY 2024-25 total cement production took place 682472 MT
2	The Water Requirement for the project shall not exceed 1050 KLD. The water will be obtained from ground water supply. No ground water extraction shall be permitted without prior permission of the CGWA	The water consumption is within the prescribed limit or less than NOC. Permission for the same has been obtained from CGWA. In 3 <sup>rd</sup> renewal water withdrawal limit has been reduced up to 882 m3/Day or 317520 m3/Annum.  FY 2024-25 total water withdrawal 284698 m3 & 790.82 m3/Day
3	The PP shall achieve the stack emission standards and ambient air standards as notified under E.P. Rules, 1986.	We are achieving the stack and ambient standards as per EPA Act, 1986. Stack and ambient monitoring from approved laboratory and self-monitoring. Refer annexure attached: 1
4	The Height of stack for disbursement of the process emissions shall net be more than 30 mtrs from ground level.	All process stacks height maintained >30 meters from ground level.

#### Corporate Office

- Prism Tower, Ninaniya Estate, Gwal Pahari, Gurugram, Haryana - 122102, India
- +0124-6919000
- admin.prismt@jkcement.com
- www.jkcement.com





Manufacturing Units at:

Nimbahera, Mangrol, Gotan (Rajasthan) | Muddapur (Karnataka) | Jharli (Haryana) Katni, Panna, Ujjain (M.P.) | Prayagraj, Aligarh, Hamirpur (U.P.) | Balasinor (Gujarat) | Fujairah

TROY

CERTIFIED





5	The PP shall operate the unit with prior Consent to Establish and Consent to Operate under the provisions of Water (Prevention & Control of Pollution) Act 74 and Air (Prevention & Control of Pollution) Act 181.	We have obtained the expansion project CTE & CTO from RSPCB Jaipur. Present CTE and CTO details as below: Letter Reference: Expansion CTE letter-no. F(Tech)/Nagaur(Merta)/ 4(1)/2008-2009/2297-2299 dated 04/10/2019, Order No2019-2020/CPM/5531. CTO Letter Reference: F(CPM)/Nagaur(Merta)/5(1)/2022-2023/5454-5456 dated 10/11/2023, and Order No: 2023-2024/CPM/9099 and valid up to 31/01/2029
6	The particulate matter and gaseous emissions (SOx, NOx, CO, CO2 etc) from various processes/ units/storages shall conform to the standards prescribed by the RPCB/CPCB or under the Environment (Protection) Rules' 86 from time to time.	We are achieving the particulate matter and gaseous emission as per prescribed standards by the RPCB/CPCB. For continuous emission monitoring system is installed at site which are connected to RSPCB and CPCB servers. Copy of monitoring results from approved laboratory and selfmonitoring. Refer annexure attached: 1
7	That the grant of this E.C. is issued from the environmental angle only, and does not absolve the project proponent from the other statutory obligations prescribed under any other Jaw or any other instrument in force. The sole and complete responsibility, to comply with the conditions laid down in all other laws for the timebeing in force, rests with the industry/unit/project proponent. Any appeal against this environmental clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under section 16 of the National Green Tribunal Act, 2010	We are communicating agreement,
8	At no time, the emissions shall go beyond the prescribed standards. In the event of failure of any pollution control system adopted by the unit, the unit shall immediately put off operation and shall not restart until the control measures are rectified to achieve the desired efficiency.	To meet the prescribed standards, pollution control equipment are interlocked the with the power supply to the production/process. All pollution control measures are fully efficient to meet the norms i.e. <30 mg/Nm3.
9	The PP shall install adequate dust collection and extraction system to control fugitive dust emissions at loading/unloading points and at all the transfer points. For source emission control, bag filters shall be provided on clinker hopper, cement silo, fly ash silo, elevator; packer: cement transport equipment etc which will also contribute to reduce fugitive emissions. The fugitive emissions during loading and unloading shall be suitably controlled. Fugitive dust emissions from ball mill and storage areas shall be collected in bag filters and recycled back to the process. Storage of raw material shall be in closed roof sheds. Water sprinkling arrangement shall be made in the raw material stock yard and cement bag loading areas.	We have installed adequate dust collection and extraction system to control fugitive dust emission at loading, unloading point and all the transfer point as per provided APCDs detail. We have also implemented road sweeping and a truck mounted big vacuum cleaner for collection and control of any spillage. All the collected materials is being used in process. This has been verified by Regional Officer/CPCB teams/MoEFCC during inspections.
10	Ambient air quality monitoring stations shall be set up in consultation with RPCB in the down wind direction as well as where maximum ground level concentration of PM and PM2.5, SOx, NOx, CO, CO2, are anticipated.	Presently, there are four number of manual ambient air quality monitoring stations maintained at site and four continuous ambient air quality monitoring station (CAAQMS) has been installed. All CAAQMS are connected with RSPCB and CPCB servers for online data monitoring.

11	Air emission sampling facilities shall be provided for the emissions monitoring as per the Central Pollution Control Board guidelines, in consultation with RPCB.	Yes, we have provided adequate sampling platform and all monitoring facilities are available at site along with sampling point as per CPCB/RSPCB guidelines.
12	Data on ambient air quality and emissions shall be submitted to RPCB once in six months carried out by MOEF/NABL/CPCB/Government approved lab.	Yes, we are regularly submitting the data and further, we will ensure the same.
13	The PP shall not install any additional DG set or enhance the capacity of present DG set for the purpose of power requirement.	We have not installed any additional DG sets at site without prior permission.
14	Fugitive dust emissions shall be controlled as per relevant guidelines issued by CPCB.	We agree to comply as above details condition point number 9.
15	Handling, manufacture, storage and transportation of hazardous chemicals shall be in accordance with the Manufacture, Storage and Import of Hazardous Chemicals Rules, 1989 (amended till date).	We have provided proper Handling/Storage facility of Hazardous Waste as per guidelines.
16	The PP shall take adequate measures for the control of noise so as to keep the noise levels below 85 Db in the work environment. Persons working near the machines should be provided with well-designed ear muffs/plugs and other personnel protective equipment.	Noise monitoring is being done around plant boundary & work zone area in regular intervals. Noise levels are well within norms. Proper enclosures have been provided at high noise area and PPEs have been provided to the workers.  Noise Monitoring results from approved laboratory & self-monitoring's are attached Refer annexure: 1
17	Suitable alarm system and standard procedure for transmitting the information on the occurrence of an accident to the proper focal point shall be established.	The alarm system has been established,
18	Efforts shall be made to increase green belt all around the premises. Native plant species shall be selected for this purpose in consultation with the local Forest Department. A green belt development plan be prepared and implemented so as to cover at least 33% area of the plot size.	More than 33% of the area covers plantation in the factory premises. We will also concerned with local forest department for increase in greenbelt. Till FY, around 18.69 Ha. & 39.64% plantation area covered. Total 43762 nos. of plants are survived with 69.42% survival rate. we are plan more dense of plantation upcoming monsoon 4500 tree plants Refer Annexure: 2 Plant Plantation layout & photographs
19	A qualified person in the field of environment or separate Environmental Management Cell shall be established to implement and carry out various functions is set up under the control of a Senior Executive who will report directly to the head of the project.	Environment Department has been setup for environmental management with qualified persons. Unit Head to look after about the total control of pollution, monitoring & maintenance of pollution control devices with the help of Site Managers along with Environment Dept. Officers, Engineer (Chemical) & trained team.
20	As envisaged under the Environmental Management Plan the PP shall earmark an amount of Rs. 8.00 Crores towards initial capital cost and Rs. 40 Lacs towards annual recurring cost of implementing the Environmental Protection Measures. The funds earmarked for the environmental protection measures shall be kept in separate account and shall not be diverted for other purposes and year wise expenditure shall be reported to RPCB under the rules prescribed for environmental audit.	We have implemented Environment management Plan according to submitted project report and expenditure detail provided to RSPCB in the annual audit report every year with recurring cost.
21	Implementation of the environmental safeguards like firefighting, water harvesting etc. along with socio economic measures like group insurance, free medical facilities, ESI/EPF facilities to the	We are communicating the agreement.

	employees as envisaged under the Environmental Management Plan; details are to be submitted to the Rajasthan Pollution Control	
	Board, at the time of applying for consent to establish/operate.	
22	As committed the PP shall earmark an additional amount of Rs.22500.00 (1.5% of proposed project cost of 15 lacs) for implementing various activities specified under the earlier EC granted by SEIAA as per CER action plan.	We are communicating the agreement.  We have implemented various activities specified in during PH.
23	The PP shall ensure that, the EC letter as well as the status of compliance of EC conditions and the monitoring data are placed on company's website and displayed at the project site.	We upload six monthly compliance in our company website. The plant site monitoring data displaying to gate display board on Digital mode & manual.
24	Besides the above conditions the PP shall make strict compliance of the conditions stipulated under earlier EC.	Agreed. We will comply.

#### **B. GENERAL CONDITION:**

Sr.	Conditions	Compliance
1	The environmental safeguards contained in Form 1-A shall be implemented in letter and spirit.	We are communicating the agreement.
2	Six monthly monitoring reports shall be submitted to Rajasthan and Rajasthan State Pollution Control Board.	We are submitting regular six-monthly monitoring reports to RSPCB. Presently, we are regularly / timely submitting the compliance report to concerned department of present EC.
3	Officials of the RPCB, who would be monitoring the implementation of environmental safeguards, shall be given full cooperation facilities and documents/data by the PP during their inspection. A complete set of all the documents submitted to SEIAA, Rajasthan shall be forwarded to Rajasthan State Pollution Control Board.	Agreed, we are cooperating for the same every visit or inspection by PCB's Official.
4	In case of any change(s) in the scope of the project, the PP requires a fresh appraisal by SEIAA/SEAC, Rajasthan.	Agreed, We will conduct fresh evaluation by SEIAA/SEAC, Rajasthan.
5	The SEIAA/SEAC, Rajasthan reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environmental clearance under the provisions of the Environment (Protection) Act-1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.	Agreed, we are communicating the agreement.
6	All the other statutory clearances such as the approvals for storage of diesel from the Chief Controller of Explosives, Fire department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (protection) Act, 1972 etc. shall be obtained, as may be applicable, by PP from the competent authority.	Agreed, we are communicating the agreement.
7	Environmental clearance is subject to final order of the Hon'able Supreme court of India in the matter of Goa Foundation Vs union of India in Writ Petition (Civil) No 460 of the year 2004 as may be applicable to this project.	Agreed, we are communicating the agreement.
8	The PP shall ensure advertising in at least two local newspapers widely circulated in the region, one of which shall be in vernacular language that, the project has been accorded environmental clearance and copies of the clearance letters are available with SEIAA, Rajasthan and the Rajasthan State Pollution Control Board and may also be seen on the website of the Board at www.rpcb.nic.in. The advertisement shall be made within 7(seven) days from the date of	Grant of Environment Clearance was advertised in Dainik Bhasker on dated 06.04.2019 Page. No. 19 and in Rajasthan Patrika dated 06.04.2019 Copy of newspapers has already been submitted to your good office in g evious compliances

	issue of environmental clearance and a copy shall also be forwarded to the SEIAA, Rajasthan and Regional Office, Jaipur(S) of the Board.	
9	These stipulations would also be enforced amongst the others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification' 06.	Agreed, we are communicating the agreement.
10	Under the provisions of Environment (Protection) Act. 1986, legal action shall be initiated against the proponent, if it was found that construction of the project has been started without obtaining environmental clearance.	Agreed, we are communicating the agreement.
11	Environment clearance is subject to the specific condition that the PP shall obtain prior clearance from forestry and wild life angle including clearance from the standing committee of the national Board for wild life, if applicable. It is further categorically stated that grant of EC does not imply that forestry and wild life clearance shall be granted to the project and that their proposals for forestry and wild life clearance will be considered by the respective authorities on their merits and decision taken. The investment made in the project, if any, based on environment clearance so granted, in anticipation of the clearance from forestry and wildlife angle shall be entirely at the cost and risk of project proponent and authority of ministry of MoEF shall not be responsible in this regard in any manner.	Agreed, we are communicating the agreement.

Work force Health Medical checkup report attached Refer Annexure: 3

We Hope you will find the document in order. Thanking you,

Yours faithfully,

For J K White Cement Works,

Dr. Ranjeet Kumar Bagariya Authorized Signatory

CC TO:

Reg/Ad: The Member Secretory, SEIAA, Rajasthan

10 Bhawani Singh Lane, Near Sahkar Marg (Room No.05) Jaipur-302001

**CPP** 

Reg/Ad: Member Secretary,

Rajasthan State Pollution Control Board,

4, institutional Area, Jhalana Doongari, Jaipur (Raj)-302004

Reg/Ad: Regional Officer (Regional Office),

Rajasthan State Pollution Control Board,

First Floor, Sehkari Bhoomi Vikas Bank Ltd., Nagaur- 341001

Encl: As above annexures



JK White Cement Works, Gotan A Unit of JK Cement Ltd.

CIN: L17229UP1994PLC017199

REGD. A/D

🎓 P.O. Gotan - 342 902, Dist - Nagaur (Rajasthan), India € +01591 230201-03 (PBX), 230976 (D), ♠+01591 230206

@ www.jkcement.com

JKWC/PLG/ENV/03/ 63.

The Member Secretary, Rajasthan State Pollution Control Board 4, Institutional Area, Jhalana Doongari, Jaipur (Rajasthan) - 302 004

Date: 07.04.2025

C-024 CPM

Compliance Report of Consent to Operate conditions under Air & Water Act of M/s JK White Cement Works, situated at P.O. Gotan, Distt. Nagaur, Rajasthan for the period from Sub: Jan-2025 to Mar-2025 (Quarter-4) of FY 2024-25.

F(CPM)/Nagaur(Merta)/5(1)/2022-2023/5454-5456 dated 10/11/2023, and Ref: Order No: 2023-2024/CPM/9099.

Dear Sir,

As above subjected matter, submitting herewith the point - wise compliance report of the conditions of consent to operate as per communicated board vides letter no. mentioned as reference. Following is the compliance status of CTO under Air & Water Act for the period from Jan-2025 to Mar-2025 (Qtr-4) of FY 2024-25 is attached.

We hope that you will find all information in order.

Thanking you,

Yours faithfully For J. K. WHITE CEMENT WORKS,

Dr. Ranjeet Komar Bagariya (Environment Head)

Authorised Signatory Copy to:

Regional Officer

Reg. A/d

Rajasthan State Pollution Control Board

First Floor, Sehkari Bhoomi Vikas Bank Ltd., Nagaur- 341001

Encl:

as above

Corporate Office

 Prism Tower, Ninaniya Estate, Gwal Pahari, Gurugram, Haryana - 122102, India

+0124-6919000

admin.prismt@jkcement.com

www.jkcement.com



Nimbahera, Mangrol, Gotan (Rajasthan) | Muddapur (Karnataka) | Jharli (Haryana)

accentent wa Imax

Katni, Panna, Ujjain (M.P.) | Prayagraj, Aligarh, Hamirpur (U.P.) | Balasinor (Gujarat) | Fujairah







6 Registered Office: ♠Kamla Tower, Kanpur-208001, U.P., India. 😂 +91-512-237147816.85 ♥ 91-512-2399854 ∜ www.jkcement.com

а

7

#### M/S JK WHITE CEMENT WORKS COMPLIANCE REPORT OF CONSENT TO OPERATE FOR THE PERIOD: JAN-2025 to MAR-2025 (QUARTER-4) FY 2024-25

60	U Condit	ioner					m ti Ci-sire
	ollance Condit	10115.					Compliance Status
+	Conditions	is Consent to Operate is valid for the period from 01/02/2024			d for the perio	We are communicating our agreement	
- 1	to 31/01/2029						Tor mo venery -
+	That this Consent is granted for manufacturing/producing following					CAOCOO TRA CINKOR	
- 1	products/by product or carrying out the following activities of					To the Coment	
	operation/processes or providing following services with capacities					and 8,80,000 TPA White Cement productions.	
	given below.					productions.	
	Particular Type Quantity with Unit						
	CLINKER		Produ	oct 6	NOT 00,000,00	PER ANNUM	
	WHITE CEME	NT	Produ	ict 8	80,000.00 TON	PER ANNUM	
	-				idiaa plant n	rocess & canacity	We are communicating our agreement
	That this cons	ent to	operat	e is for e	existing plant p	process & capacity	for obtaining fresh Consent to Establish &
	and separate	e conse	ent to e	establish,	operate is re-	quired to be taker	l l l l l l l l l l l l l l l l l l l
	for any addit	tion/ m	nodifico	ation/alte	eration in pro	cess or change in	modification / expansion if any.
	capacity or c	hange	in fuel.			l de et disposa	
	That the quar	ntity of	effluen	it genero	ation along wit	h mode of disposa	generated from the unit. Domestic
	for the treate		ent shal	l be as u	inder:	Oh of officient	wastewater generated from the office
	Type of	Max.		Recycle		Qty. of effluent	toilets, canteen & guesthouse etc. Is
	effluent	efflue		d Qty		ia mode oi	being treated through STP (500 KLD
		gene		effluent	disposal		capacity) and treated water used in
		n (KLE		(KLD)	10.00	To be treated	plantation and horticulture.
	Domestic	13.00		Nil		- To be treated	1
	\$ewage					to be used in	
					plantation	and horticulture	
_!					along with	a pollution contro	of The Adequate stack heights have been
	measures of	and f	he er	mission	on along with standards fo	n pollution contro or the prescribed	provided at site for stacks.  All stacks are provided with Bag
I	measures of parameters	and f	he er e unde	mission	on along with standards fo	ine prescribed	provided at site for stacks.  All stacks are provided with Bag Filter/Bag House/ESPs along with safe
I	measures of	and f shall be Po	he er e unde	nission r: Control	standaras ro	Standard	provided at site for stacks.  All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure fo
Ī	measures of sources of air Emission	and f shall be Po ns Me	he er e unde llution ( easures	nission r: Control	Prescribed Prescribed	ine prescribed	provided at site for stacks.  All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure fo monitoring. Applicable monthly stack
Ī	measures of parameters Sources of air Emission Cement Mi	and f sholl be Po Is Me	he er eunde llution ( easures dequate	mission r: Control	Prescribed Parameter	Standard	provided at site for stacks. All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure fo monitoring. Applicable monthly stac. monitoring reports are being submitted
Ī	measures of sources of air Emission	and f shall be Po ns Me ill Ac H He	he er eunde llution ( easures dequate	mission r: Control i e Stack ulse Jet	Prescribed Parameter Particulate	Standard 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure fo monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.
Ī	measures parameters Sources of air Emission Cement Mi -1&2 (52 TP Each)	and f shall be Po ns Me ill Ac H He	the er llution ( easures dequate eight, Pu	mission r: Control i e Stack ulse Jet	Prescribed Parameter Particulate	Standard	provided at site for stacks. All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard
Ī	measures carcameters Sources of air Emissior Cement Mi -1&2 (52 TP Each) Cement Mi	and f shall be Po ns Me ill Ac H He Ba	the er under liution (constitution (constitu	mission  Control  Stack  Ulse Jet	Prescribed Parameter Particulate Matter	Standard 30 mg/NM3	provided at site for stacks. All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stac monitoring reports are being submitted to your good office. We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installe
I	measures parameters Sources of air Emission Cement Mi -1&2 (52 TP Each)	and f sholl be Po ns Me ill Ac He Ba He Ba	he er e unde llution ( easures dequati sight, Pu g Filter dequati sight, Pu	mission r: Control is e Stack ulse Jet e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate	Standard 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stac monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installe
I	measures carcameters Sources of air Emissior Cement Mi -1&2 (52 TP Each) Cement Mi	and f sholl be Po ns Me ill Ac He Ba He Ba	the er e unde llution ( easures dequate eight, Pu g Filter dequate	mission r: Control is e Stack ulse Jet e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate	Standard 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stac monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO
1	measures carameters Sources of air Emissior Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH)	and f sholl be Po Me iill Ac H Ba H Ba et Ac En	the er under	control e Stack ulse Jet e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate Matter	Standard 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters a analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB
I	measures carameters Sources of air Emissior Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se	and f sholl be Po Me iill Ac He Ba He Ba En Ac	the er under	control e Stack ulse Jet e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate Matter	Standard 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers. Stack monitoring results are give
I	measures corameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se (250KVA)	and f sholl be Po Me iill Ac He Ba En Ac He	the er under	control e Stack ulse Jet e Stack ulse Jet e Stack	Prescribed Parameter Particulate Matter  Particulate Matter	Standard 30 mg/NM3 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure fo monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters a analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers. Stack monitoring results are give in Annexure-1 & third-party monitoring
I	measures carameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se (250KVA)	and f sholl be Po Me iill Ac He Ba He Ba En Ac He Ac	the er under	control e Stack ulse Jet e Stack ulse Jet e Stack	Prescribed Parameter Particulate Matter  Particulate Matter  Particulate Particulate Particulate Particulate Particulate	Standard 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers. Stack monitoring results are give
Ī	measures carameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se (250KVA)  Petcoke / Coal Mill - 3	and f shall be shall	he er under llution (easures dequate) eight, Pure lle llution (easures dequate) eight, Pure lle llution (easure dequate) eight dequate) eight dequate)	control e Stack ulse Jet e Stack ulse Jet e Stack	Prescribed Parameter Particulate Matter  Particulate Matter	Standard 30 mg/NM3 30 mg/NM3	provided at site for stacks. All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stace monitoring reports are being submitted to your good office. We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installe continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB Servers. Stack monitoring results are give in Annexure-1 & third-party monitorin reports are attached as annexure - 2.
	measures coarameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se (250KVA)  Petcoke / Coal Mill -3 (12 TPH)	and f sholl be Po ns Me iill Ac He Ba et Ac En Ac Ac Ac Ba Ba	the er under under litution (easures dequation) and filter dequation closure dequation closure dequation dequation dequation gritter dequation closure dequation dequation dequation dequation dequation dequation depth of the filter light of the light of	control e Stack ulse Jet e Stack ulse Jet e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate Matter  Particulate Matter	Standard 30 mg/NM3 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stace monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers. Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.
	measures coarameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se (250KVA)  Petcoke / Coal Mill - 3 (12 TPH) Petcoke /	and f sholl be Po ns Me iill Ac He Ba et Ac En Ac He Ba Ac	the er under	control e Stack ulse Jet e Stack ulse Jet e Stack ulse Jet e Stack e Stack	Prescribed Parameter Particulate Matter  Particulate Matter  Particulate Matter  Particulate Particulate Particulate Particulate Particulate Particulate	Standard 30 mg/NM3 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stace monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers, Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sets are used in emergency only The 250 KVA DG set is used in emergency
	measures coarameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se (250KVA)  Petcoke / Coal Mill - 3 (12 TPH) Petcoke / Coal Mill	and f sholl be Po Me iill Ac He Ba He Ba Ac He Ac Ac He Ba	the er under	control e Stack ulse Jet e Stack ulse Jet e Stack ulse Jet e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate Matter  Particulate Matter	Standard 30 mg/NM3 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stace monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers, Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sets are used in emergency only The 250 KVA DG set is used in emergency and Two nos, of D.G sets (3500 KVA x.2)
I	measures coarameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se (250KVA)  Petcoke / Coal Mill - 3 (12 TPH) Petcoke /	and f sholl be Po Me iill Ac He Ba He Ba Ac He Ac Ac He Ba	the er under	control e Stack ulse Jet e Stack ulse Jet e Stack ulse Jet e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate Matter  Particulate Matter  Particulate Particulate Particulate Particulate Particulate Particulate	Standard 30 mg/NM3 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stace monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installe continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB Servers, Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sets are used in emergency only The 250 KVA DG set is used in emergency only. Two nos, of D.G sets (3500 KVA x.) (7000 KVA) not in operation which have
1	measures corameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH)  One D.G se (250KVA)  Petcoke / Coal Mill -1 (12 TPH) Petcoke / Coal Mill -1&2 (5 TPH Each)	and f sholl be possible and f sholl be properly and f	he er under	e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter	Standard 30 mg/NM3 30 mg/NM3 30 mg/NM3	provided at site for stacks. All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stace monitoring reports are being submitted to your good office. We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers, Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sefs are used in emergency only The 250 KVA DG set is used in emergency only. Two nos. of D.G sets (3500 KVA x.2) (7000 KVA) not in operation which have dismantled. Stack monitoring report
1	measures carameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH)  One D.G se (250KVA)  Petcoke / Coal Mill -3 (12 TPH) Petcoke / Coal Mill -1&2 (5 TPH Each) Quencher	and f sholl be possible to the sholl be sholl be should	he er under llution (easures dequate ight, Properties dequate ight, Properties dequate ight dequate ight dequate ight, Properties dequate ight, Properties dequate ight dequate ight, Properties igh	e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter  Particulate Particulate Particulate Particulate Particulate Particulate	Standard 30 mg/NM3 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers. Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sets are used in emergency only The 250 KVA DG set is used in emergency only. Two nos. of D.G sets (3500 KVA x 2 (7000 KVA) not in operation which have
	measures coarameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH)  One D.G se (250KVA)  Petcoke / Coal Mill -3 (12 TPH) Petcoke / Coal Mill -1&2 (5 TPH Each) Quencher Stack (Kiln	and f sholl be possible to the sholl be sholl be should	he er under	e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter	Standard 30 mg/NM3 30 mg/NM3 30 mg/NM3	provided at site for stacks.  All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters a analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers, Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sets are used in emergency only The 250 KVA DG set is used in emergency only. Two nos, of D,G sets (3500 KVA x 2 (7000 KVA) not in operation which have dismantled. Stack monitoring report of
	measures carameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH)  One D.G se (250KVA)  Petcoke / Coal Mill -3 (12 TPH) Petcoke / Coal Mill -1&2 (5 TPH Each) Quencher	and f sholl be possible to the sholl be sholl be should	the er under litution (easures dequate ight, Progritter coustic closure dequate ight dequate ight dequate ight, Progritter dequate ight, Progritter dequate ight	e Stack ulse Jet	Prescribed Parameter Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter  Particulate Matter  Particulate Particulate Particulate Particulate Particulate Particulate	Standard 30 mg/NM3 30 mg/NM3 30 mg/NM3	provided at site for stacks. All stacks are provided with Bags Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stace monitoring reports are being submitted to your good office. We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers, Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sefs are used in emergency only The 250 KVA DG set is used in emergency only. Two nos. of D.G sets (3500 KVA x.2) (7000 KVA) not in operation which have dismantled. Stack monitoring report
	measures coarameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH)  One D.G se (250KVA)  Petcoke / Coal Mill -3 (12 TPH) Petcoke / Coal Mill -1&2 (5 TPH Each) Quencher Stack (Kiln	and f sholl be Po Me Ba Ba Ba Ba Ac He Ba	the er under	e Stack ulse Jet	Prescribed Parameter Particulate Matter	Standard 30 mg/NM3 30 mg/NM3 30 mg/NM3 30 mg/NM3	provided at site for stacks. All stacks are provided with Bage Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers. Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sets are used in emergency only The 250 KVA DG set is used in emergency only. Two nos. of D.G sets (3500 KVA x 2 (7000 KVA) not in operation which have dismantled. Stack monitoring report of
	measures coarameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se (250KVA)  Petcoke / Coal Mill -3 (12 TPH) Petcoke / Coal Mill -1&2 (5 TPH Each) Quencher Stack (Kiln Outlet)	and f sholl be Pons Me iill Acc He Ba En Acc He Ba Ba Acc He Ba	the er under	e Stack ulse Jet	Prescribed Parameter Particulate Matter	Standard 30 mg/NM3 30 mg/NM3 30 mg/NM3 30 mg/NM3	provided at site for stacks. All stacks are provided with Bage Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers. Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sets are used in emergency only The 250 KVA DG set is used in emergency only. Two nos. of D.G sets (3500 KVA x 2 (7000 KVA) not in operation which have dismantled. Stack monitoring report of
	measures coarameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH)  One D.G se (250KVA)  Petcoke / Coal Mill -1 (12 TPH) Petcoke / Coal Mill -1&2 (5 TPH Each) Quencher Stack (Kiln Outlet) (73 TPH)	and f sholl be Pons Me iill Acc He Ba En Acc He Ba Ba Acc He Ba	the er under	e Stack ulse Jet	Prescribed Parameter Particulate Matter	Standard 30 mg/NM3 30 mg/NM3 30 mg/NM3 30 mg/NM3 10 mg/NM3 10 mg/NM3	provided at site for stacks. All stacks are provided with Bage Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers. Stack monitoring results are give in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sets are used in emergency only The 250 KVA DG set is used in emergency only. Two nos. of D.G sets (3500 KVA x 2 (7000 KVA) not in operation which have dismantled. Stack monitoring report of
	measures corameters Sources of air Emission Cement Mi -1&2 (52 TP Each) Cement Mi -3 (65 TPH) One D.G se (250KVA)  Petcoke / Coal Mill -1 (12 TPH) Petcoke / Coal Mill -1&2 (5 TPH Each) Quencher Stack (Kiln Outlet) (73 TPH) Raw Mill Kill	and f sholl be Pons Me iill Acc He Ba En Acc He Ba Ba Acc He Ba	the er under	e Stack ulse Jet	Prescribed Parameter Particulate Matter	Standard 30 mg/NM3 30 mg/NM3 30 mg/NM3 30 mg/NM3	All stacks are provided with Bag Filter/Bag House/ESPs along with safe and adequate infrastructure for monitoring. Applicable monthly stack monitoring reports are being submitted to your good office.  We are achieving the standard prescribed by the board w. r. t. emission standards in stacks. We have installed continuous online opacity meters analysers for monitoring of PM, SO <sub>2</sub> NO emission & data Connected to PCB' Servers. Stack monitoring results are given in Annexure-1 & third-party monitoring reports are attached as annexure - 2.  The DG sets are used in emergency only The 250 KVA DG set is used in emergency only. Two nos, of D.G sets (3500 KVA x 2 (7000 KVA) not in operation which have dismantled. Stack monitoring report of

		Total Organ Carbo		1 mg/NM3 0.1 ngTEQ/Nm3	
		HF	Dioxins	30 mg/NM3	Ä.
		& Furd	ans		
		Partic	ulate	800 mg/NM3	
	11 1	Matte	er	0.05 mg/Nm3	
	1	NOx			
	H i	Cd+	Th	1	
		+their		0.05 mg/Nm3	
	11	comp	ounds		
		Hg an	nd its	0.05 mg/Nm3	
		comp	ounds		
		Sb + A	s + Pb		
		+Co+	Cr+		
		Cu +N	/n +		
		Ni + V	+		
		their			
		comp	ounds		
	Two nos. of	CO		150 mg/NM3	
	D.G sets	Partic		75 mg/NM3	
	(3500 KVA x	Matte	r		
	2) (7000	NOx		710 mg/NM3	
	KVA)	NMHC		100 mg/NM3	
	Parameters  pH Value  Biological oxidation Der	mand (3 days	The second second	en 6.5 to 9.0 exceed 10mg/1	recognized laboratory is attached herewith as <b>Annexure 2.</b> During this period, STP is under shutdown due to upgradation work and domestic waste water is being treated through School STP (500 KLD Capacity).
	at 27 degree Celsius)	nana (o aays	110.70	····	
	Chemical Oxygen Dema	nd	Not to	exceed 50mg/l	
	NH4 - Ammoniacal Nitros		10 mg/	71	
	N Total		5 mg/l		
	Total Suspended Solids		Not to	exceed 20 mg/l	
	Fecal Coliform (MPN per 100 ml)			exceed 100	
					W are a resulting our agreement
7	That this consent to oper 6,00,000 TPA & white ceme	ate is valid for ent 8,80,000 TPA	the pro	oduction of clinker	We are communicating our agreement for the condition of clinker up to 6,00,000 TPA & white cement 880000 TPA White Cement production.
3	That the total capital investment as on 19.09.2023 as per the C. A certificate submitted by the unit is Rs 371.66 crores which includes the cost of land, building, plant & machinery and miscellaneous assets.			We are agreed this condition	
)	That the industry shall comply with all the conditions imposed by the SEIAA, Jaipur while issue of environment clearance vide letter no. F(14)/SEIAA/SEAC-Raj/Sectt/Project/ Cat.3(b)B1/ (367)/11-12 dated 28/12/2012 and subsequently unrended vide letter dated			Noted, we are complying. Six monthly compliances are submitted to your office and MoEF&CC timely.	
0	29.03.2019. That no hazardous wa	iste/ non-haza	ırdous	waste, shall be	Agreed.
	used/co-processed in permission from CPCB & f and Other Waste (Ma and consent to establi	cement kilr RPCB as per the	witho	ut obtaining prior sions of Hazardous	

11	That no fuel other than Indian coal/imported coal/petcoke shall be used in kiln without prior consent from the State Board.	Yes, noted and complying with.
12	That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the kiln of cement plant only and quantity of petcoke use shall not exceed to 82500 tons per annum (7750 tons per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.	Agreed. We are submitting the petcoke detail on monthly basis to your office.
13	That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.	Agreed.
14	That the industry shall not store petcoke for more than its three months consumption.	We are ensuring compliance within the stipulated time.
15	That the industry may import the petcoke for its own use only and consignment shall be in the name of the industry. For import of petcoke the industry shall obtain registration from the State Board.	Agreed. We are complying the same.
16	That the trading of pet coke by the industry is not permitted.	Agreed. We are complying the same.
17	That the industry shall submit details of pet coke purchased from various sources during the month (imported, purchased from refineries or authorized dealers), quantity consumed during the month and opening and closing stock to the State Board on monthly basis.	Agreed. We are submitting the petcoke detail on monthly basis to your office.
18	That the industry shall maintain online continuous emission monitoring systems at all the main stacks (attached to kiln, coal mill, cement mill and clinker cooler etc.) to monitor the emission level of particulate matter (PM), SO2 and NOx etc. and connectivity of the same shall be ensured with RPCB/CPCB server during operation of the plant.	We have installed CEMS at all mentioned stacks & connected with RSPCB servers.
19	That for the control of fugitive emission guidelines/ code of practice as issued by CPCB will be followed.	Agreed. We are following the CPCB guidelines.
20	That all the recommendations made in the Charter of Corporate Responsibility for Environment Protection for Cement Plants shall be implemented.	Complying with the recommended conditions of Corporate Responsibility for Environment Protection, as applicable.
21	That the industry shall comply with revised emission standards as notified by the MoEF & CC, Gol New Delhi for cement plants vide gazette notification dated 25/08/2014(without co-processing of waste) subsequently amended on 9/05/2016 and notified vide notification dated 10/05/2016(with co-processing of waste),	Yes, we are complying with all revised emission guidelines as prescribed by the MOEF&CC, CPCB/RSPCB.
22	whichever is applicable.  That guidelines on co-processing in cement industries issued by the Central Pollution Control Board shall be compiled, if applicable.	Agreed. We are complying the same.
23	That the industry shall maintain stack of adequate height and adequate air pollution control measures at all the sources of air emissions so as to achieve the prescribed emission standards.	We have maintained all stacks with adequate height & PCM to meet the norms according to the guidelines.
24	That adequate infrastructure facility for stack emission monitoring shall be maintained at all the stacks viz, kiln, cooler, cement mill and coal mill etc.	Adequate infrastructure facility for stack emission monitoring has provided at all stacks viz, kiln, cooler, cement mill and coal mill etc.
25	That no additional source of air pollution shall be installed without prior consent from the State Board.	Agreed. We will not install additional source of air pollution without prior consent from the State Board.
26	That closed conveyor bells shall be used for the transfer of material to minimize the fugitive emissions.	All conveyors have been covered where the possibility of fugitive emission or transportation of powder form materials.
27	That the industry shall maintain dust collection and extraction system to control fugitive dust emissions at all the transfer points and loading/unloading areas.	We have maintained dust collection and extraction system to control fugitive dust emissions at all the transfer points and loading/unloading area at site.



28	That all the raw materials and products shall be stored in closed covered shed.	All the raw material (powder form) and products are stored in closed covered shed and silos.
29	That cemented roads shall be provided & maintained in good condition inside the premises to minimize the fugitive emissions due to vehicular movements.	All roads are cemented (Pucca) in plant premises and maintained in good condition to minimize the fugitive emissions due to vehicular movements.
30	That water sprinkling and cleaning of roads by vacuum cleaner shall be done regularly to control the fugitive emissions generated due to vehicular movement.	Water sprinkling system is installed for controlling fugitive emissions. Sweeping machine and vacuum cleaner has been deployed for regular cleaning to control the fugitive emissions generated due to vehicular movement.
31	That the recommendations of the policy briefs related to human health risk due to cement dust exposures shall be complied.	We are following recommendations of policy related to human health risk due to cement dust exposures. Our plant is ISO 9001, ISO 14001, ISO 45001, ISO 50001 & SA 8000 Certified. We are committed to demonstrate continual improvement in our Environmental, Occupational Health & Safety (EHS) performance.
32	That the power supply to the production/process shall be interlocked with the pollution control equipment that in the event of non-functioning of the pollution equipment/or increase in levels of pollutants, the production process stops automatically.	Pollution control measures interlocked with production equipment, which on increase in levels of pollutants, the production process stops automatically.
33	That separate energy meter & hour meter shall be provided and maintained at all the air pollution control measures & STP and daily record of running hours of pollution control measures and energy consumption shall be maintained in logbook.	We are maintaining all records as per condition.
34	The industry shall comply with the MoEF&CC, Government of India, Notification dated 14th September 1999, amended up to date relating to fly ash management and shall provide relevant details to the State Board, MoEF &CC, and Government of India.	Not applicable, there is no use of fly ash because the plant is engaged in white cement production.
35	That industry shall maintain continuous ambient air quality monitoring stations in all directions for monitoring of gaseous emissions and particulate matter in the ambient air and records of the same shall be submitted on quarterly basis to the State Board.	We have maintained four numbers of continuous ambient air quality monitoring stations and four number manual stations in all directions. The continuous ambient air quality monitoring station is connected to PCB's servers. Quarterly monitoring reports are submitted timely to your good office and the report is attached as Annexure-1.
36	That the total water consumption shall not exceed to 1077 KLD (Boiler/cooling-100.00 KLD, industrial use- 805 KLD, domestic use- 17 KLD and others- 155.00 KLD) and the freshwater requirement shall be met from ground water (877 KLD) and recycled water from STP (200 KLD).	
37	That the industry shall comply with all the conditions of CGWA NOC for abstraction of ground water up to 1050 m3/day issued vide NOC No. CGWA/NOC/IND/REN/2/2021/ 59674 with validity up to 29.11.2022. The industry shall get renewed the NOC for drawl of groundwater from CGWA and submit a copy of the same to this office within 03 months.	
38	That ground water in excess to 1050 KLD shall not be abstracted without prior permission from CGWA and the State Board.	Agreed. We are complying with the issued water NOC.
39	That the water meter shall be installed and maintained at all the borewells to measure the quantity of daily ground water withdrawal & record of the same shall be maintained on daily basis	Digital water flow meters along with telemetry system are installed at all bore wells and records are being maintained.

Z I K W

40	That the domestic wastewater generated from the cement plant shall not exceed to 13.00 KLD. The domestic wastewater shall be treated through existing sewage treatment plant (STP) of 500 KLD located in the colony as per standards mentioned at condition no.7 and the same shall be used for in kiln and other purposes within the premises.	Agreed. We are complying the same,
41	That no trade effluent and domestic waste water will be discharged inside or outside the factory premises in to a stream or well or sewer or on land.	Agreed. No trade effluent and domestic wastewater is being discharged inside or outside the factory premises in to a stream or well or sewer or on land.
42	That suitable flow measuring devices/ meters on the inlet and outlet of STP shall be maintained. Daily record of domestic wastewater generation and its treatment and utilization shall be maintained.	Flow measuring digital meter is installed on the inlet and outlet of STP and daily record is maintained. Treated water is used in plantation / horticulture activity.
43	That industry shall comply with the provisions of Hazardous & others Waste (Management, & Transboundary Movement) Rules, 2016 and record of daily hazardous waste generation and its disposal shall be maintained.	Complied with,
44	That the industry shall carryout effluent sampling/stack monitoring/ambient air quality monitoring and submit quarterly analysis report from the State Board laboratory/ laboratory recognized by Ministry of Environment & Forests (MoE&F), Government of India.	Monitoring of effluent sampling/stack monitoring/ambient air quality reports is being done on quarterly basis from recognized NABL approved laboratory are attached as <b>Annexure-2</b> .
45	That the industry has to mandatorily carry out at least 25% of the designated frequency of sampling/monitoring as paid monitoring by the State Board laboratory.	Yes, we are ensuring the 25% paid monitoring yearly by the state board laboratory.
44	That suitable measure for rain water harvesting for artificial recharge of ground water shall be taken.	We have taken suitable measures for rain water harvesting for artificial recharge of ground water at plant, colony and mines lease area.
47	That the plantation in atleast 33% of total area of the project in and around the cement plant shall be carried out & maintained.	We covered more than 33% of total area in green belt. Tree sapling of Neem, Desi Ashok, Pendular Ashok, Arjun, Phycus panda, Kaner, Karanj, Duranta etc. has been planted in the plant and colony area along with boundary side & nearby. Photographs of the plantation are attached as annexure – 3.
48	That the industry shall make all efforts to control dust emissions and keep suspended particulate matter (SPM) as well as noise levels within the prescribed norms. The industry shall utilize all the available spaces near the plant and both sides of transportation roads for development of greenbelt with species like siris/cirrus, mulberry and jamun for control of SO2 and Neem, Tamarind, Palas and Churel trees for general purpose of Cement Plant and Maulsari, Ber, Ashoka, Pipal and Tulip trees for the control of noise levels. Compliance in this regard shall be submitted within 6 months.	We are ensuring the plantation work as per condition. Different types of plant species have been planted and submits the compliance accordingly.
49	That no Single Use Plastic (SUP) item, which is banned vide Ministry of Environment, Forest and Climate Change (MOEF & CC), Government of India notification dated 12.08.2021 shall be used in the industry/unit premises.	Yes. We are complying the same.
50	That the industry shall also ensure the compliance of all the other conditions of revised consent order no. 2022-23/CPM/8676 dated 23,12.2022.	Yes. We are complying the same,
51	That the industry shall submit the quarterly compliance report of all the above conditions to the State Board.	Yes. We are complying the same.
52	That this consent is being issued in supersession of earlier consent issued vide letter no.3242-3245 dated 11.12.2019.	Yes. Noted and we are complying the same.



	II. Charles	We are communicating our agreement
53	That notwithstanding anything provided hereinabove, the State Board shall have power and reserves its right, as contained under section 27(2) of the Water Act and under section 21(6) of the Air Act to review anyone or all the conditions imposed here in above and to make such variation as it deemed fit for the purpose of Air Act & Water Act.	to comply with all other requirements of Air act & Water act.
54	That the grant of this Consent to Operate is issued from the environmental angle only, and does not absolve the project proponent from the other statutory obligations prescribed under any other law or any other instrument in force. The sole and complete responsibility to comply with the conditions laid down in all other laws for the time-being in force, rests with the industry/ unit/ project proponent.	We are communicating our agreement for this condition.
55	That the grant of this Consent to Operate shall not, in any way, adversely affect or jeopardize the legal proceeding, if any, instituted in the past or that could be instituted against you by the State Board for violation of the provisions of the Act or the Rules made thereunder.	We are communicating our agreement for this condition.
56	That the Project Proponent shall comply with provisions of the E-waste (Management) Rules, 2016 and ensure that e-waste generated by them is channelized through collection centre or dealer of authorized producer or dismantler or recycler or through designated take back service provider of the producer to	We maintain the generation record of E-waste and submit annual return in form 3 annually. E- waste is disposed off to registered recycler only and ensuring the compliance as per board condition.
57	authorized dismantler or recycler.  That the Project Proponent shall maintain record of e-waste generated by them in Form-2 and make such records available for scrutiny by the Board.	We maintain the generation record of E-waste in form no. 2 and complying with.
58	That the Project Proponent shall file annual returns in Form-3, to the Board on or before the 30th day of June following the financial year to which that return relates.	We submit the annual return of E-waste in form no. 3 annually by the 30th Jun of every year.
59	That the transportation of e-waste shall be carried out as per the manifest system whereby the transporter shall be required to carry a document (three copies) prepared by the sender, giving the details as per form-6.	During disposal of E-waste, we fill and maintain all copies of manifest in form -6 and provide the three copies to the transporter after details completion.
60	That the Project Proponent shall comply with provisions of the Batteries (Management and Handling) Rules, 2001 (as amended) and submit half yearly returns (as bulk consumer, importer, auctioneer, recycler as the case may be) to the State Board as provided under Rule 10 (2) (ii) of the Battery (Management and Handling) Rules, 2001 (as amended). In case the Project Proponent is not a bulk consumer even then the used batteries shall be	
61	returned to the authorized dealers or recyclers only.  That the record of batteries purchased and sold/ returned to registered dealers and/ or authorized recyclers shall be maintained and made available to the officers of the Board during inspections.	Ensuring the disposal of battery waste to the registered recycler or dealers only. We are also maintaining the battery waste generation record and complying.



# MONTHLY ENVIRONMENT MONITORING REPORT

MONTH: JAN-2025

			Stack	Stack	:			Volume of	M <sub>A</sub>	Raw Mill/	Raw Mill/
S. No	Stack Mark	Stack attached to	OlA (In	Height. From G.L. (mtrs.)	Operating	iemp. of Gases °c	(m/sec)	Stack (Nm3/ Min)	(Mg/ Nm3)	Kiln SO <sub>2</sub> (mg/Nm <sup>3)</sup>	Kiln No <sub>x</sub> (mg/Nm³)
-	4	Crusi er	800	31		42	12.7	361.30	13.79	ı	
2	a	Screen House	480	31		43	9.4	96.65	17.99		
67	U	RM Sec. Crusher	1050	38	,	46	9.3	453.39	16.71		
4	٥	Kiln Feed Section	900	39		14	9.5	343.40	17.32		
25	ш	Raw Aill and Kiln Stack (ESP-1)	2100	65	Ä	136	15.0	2266.20	18.54		
9	ш	New ESP (ESP-2)	1400	40	readings		plant und	plant under shutdown			
7	O	Quericher Stack (Kiln outlet)	1650	30	were	191	14.4	1268.81	20.48		
σC	I	Petro Coke Mill - 1	800	31	taken		plant und	plant under shutdown		13.68	451.30
0	-	Pero Coke Mill - II	800	31	under	99	6.6	261.14	8.25		
. 0	-	Pero Coxe Mill - III	086	40	normal	65	9.8	389.56	7.42		
=	~	Clinker Tunnel	800	93	operating	55	9.3	255.54	15.72	T	
12	-	Cement Mill -1 & II	920	8	conditions	89	9.0	155.99	6.79	T	
1 2	2	Cement Mill-III	650	30		29	9.4	164.38	11.58		
14	2	Parking Plant (50 kg)	450	32		46	8.8	78.66	17.21		
r r	c	Pombina Plant (Bag Cleaning Sys.)	800	32		47	8.5	239.52	16.36		
2 2	0	3ciler Stock (TPP)	1200	72			plani un	plani under shutdown		under	under shutdown

ORT
2
낊
(5)
ž
5
의
=
õ
A
2
>
-
9
7
C
Ω¢
⋖
-
íi.
8
>
<1
-

-			On.	PM, s	202	NOX	ပ္ပ
_	DATE	LOCATION	UC / M3	µg/M³	µg/M³	ug/M³	ng/M³
+	10001010	33 // 661	47.75	34.43	13	18	1293
-	01.01.20	132 NV 33	10 03	32.65	12	16	1304
	31,01.2025	132 KV 55	20.74	00 10	0.	10	1282
_	01.01.3025	Rest Shelter	46.24	31.22	2		7101
+	7000 10 10	Don't Chalter	47.16	32.51	13	//	0101
-	31.01.5023	Neal Stieller	00 97	21.59	12	155	1304
-	01.01.2025	EDP	40.00	40.00	7.5	17	1339
-	21 01 3025	EDP	45.01	30.38	4		100.
+	01.01.020		47.38	32.21	12	18	1304
	01.01.2025	25-		0000	ď	16	1282
-	BOOK TO TO	76.11	48.0	00.00	2		

## STACK MONITORING REPORT

MONTH: FEB-2025

0.00			Stack	Stack				Volume of			
S. No	Stack	Stack attached to	OIA (In	Height. From G.L. (mfrs.)	Operating conditions	Temp. of Gases °c	Velocity (m/sec)	Gas in Stack (Nm3/ Min)	PM (Mg/ Nm3)	Raw Mill/ Kiln SO2 (mg/Nm³)	Raw Mill/ Kiln NOx (mg/Nm³)
_	4	Crusher	800	31		41	12.4	354.33	15.18		
24	ධය	Screen House	480	31		44	9.8	100.04	17.22		
6	υ	RMSec. Crusher	1050	38		45	9.5	464.46	16.45		
4	۵	Kiln Feed Section	006	39		42	6.7	350.33	15.07		
25	ш	Raw Mill and Kiln Stack (ESP-1)	2100	65	₹	138	14.7	2220.23	17.65		
9	ıL	New ESP (ESP-2)	1400	40	readings		plant un	plant under shutdown			
7	O	Quencher Stack (Kiln outlet)	1650	30	were	158	14.2	1262.86	20.95		
00	I	Petro Coke Mill - I	800	31	taken		plant un	plant under shutdown		43.98	612.64
0	-	Petro Coke Mill - II	800	31	under	99	9.5	253.72	16.64		
9	-	Pefro Coke Mill - III	980	40	normal	63	6.7	387.80	10.49		
=	<u> </u>	Clinker Tunnel	800	30	operating	19	0.6	242.98	14.87	1	
12	-	Cerrent Mill -1 & II	920	30	conditions	29	9.3	163.05	9.54		
5	×	Cerrent Mill -III	920	90		92	8.8	153.86	10.78		
14	z	Presting Plant (50 kg)	450	32		47	8.5	75.08	16.59		
2	0	Parting Plant (Bag Cleaning Sys.)	800	32		49	8.6	240.98	17,55		
2	Δ	Rolls Stack (TPP)	1200	72			plant ur	plant under shutdown		under	under shutdown

			MONTH: FEB-2025	L/A			
-			PM10	PM25	\$0,	XON	00
_	DATE	LOCATION	LIG/M3	mg/M³	µg/M³	Md/M3	hg/M³
+	2002.00	132 VV SS	49,11	32.80	14	17	1270
+	01.02.2025	102 N 33	44.09	31.07	12	81	1293
+	28.02.2025	132 KV 33	75:07 75:07	32.45	13	16	1304
-	01.02.2025	Rest Shelter	O. C.	2 20	11	7.	1327
	28.02.2025	Rest Shelter	45.39	27.00	-	2	1000
-	5000 00 10	EDP	44.96	32.66	13	16	787
+	01.02.2023		44.11	30.93	14	18	1293
-	28.02.2025	הטר	C L	32.03	13	17	1339
-	01.02.2025	CS-11	45.50	92.79	2		1917
+	5000 CO 80	CS-11	45.08	32.29	14	<u> </u>	0151

STACK MONITORING REPORT
MONTH: MAR-2025



S. No	Stack Mark	Stack attached to	Stack DIA (in	Stack Height. From G.L.	Operating	Temp. of Gases °c	Velocity (m/sec)	Volume of Gas In Stack (Nm3/ Min)	PM (Mg/ Nm3)	Raw Mill/ Kiln SO2 (mg/Nm³)	Raw Mill/ Kiln NOX (mg/Nm³)
1	4	Crisher	800	31		42	11.6	331.74	17.12		
T	6	Screen House	480	31		40	10.3	106.78	14.62	-	
	U	RA# Sec. Crusher	1050	38		45	6.6	481.24	15.04		
	0	Kiln Feed Section	900	39		43	10.0	359.50	17.36		
	ш	Raw Mill and Kiln Stack (ESP-1)	2100	65	Ŧ	135	14.3	2162.00	19,03		
	L	New ESP (ESP-2)	1400	40	readings		plant un	plant under shutdown			
1	O	Quencher Stack (Kiln outlet)	1650	30	were	154	13.9	1242.28	19.42		i.
	1	Petro Coke Mill-1	800	31	taken		plant un	plant under shutdown		35.52	4.00
	-	Petro Coke Mill - II	800	31	under	63	8.9	238.05	11.36		
I	-		080	Q\$/	normal	29	8.7	345.47	14.83		
<u> </u>	3	THE CONSTRUCTION	200	3	operating	64	0.6	239.80	13.06		
_	2	CITIZE TO THE	3	8 8	conditions.		6.9	164.01	9.80		
12	_	Cement Mill -1 & II	000	200	Ī		7 8	154 54	10.68	I	
33	٤	Cement Mill -III	920	95		70	à :	5.55	2015	ī	
7	2	Packing Plant (50 kg)	450	32		46	9.3	82.64	15.24		
4	c	Packing Plant (Bag Cleaning Sys.)	800	32		48	9.6	268.36	4.39		a shareholous
2 ;	) 0	Boiler Storte (TPP)	1200	72			Plant u	Plant under shuldown		nugei	under shuldown

			MONTH: MAR-2025	25			
_			PM.	PM <sub>2.5</sub>	502	NOX	3
	DASE	LOCATION	III/W <sub>3</sub>	ug/M³	ug/M³	µg/M³	μg/₩³
				70.00	1,5	17	1259
-	01 03 2025	132 KV SS	46.34	31.24	7		0.00
4	01:00:00:0		46.05	34.29	13	19	1316
_	29.03 2025	132 KV 55			7	16	1282
+	01 02 2025	Roct Shelter	44.57	35.38	77	24	
-	01.03.2023		45 50	37 33	12	17	1316
-	29.03.2025	Rest Shelter	45.33	25:30			1204
+		to the second	45.72	30.82	14	18	TOCT
	01.03.2025	EDP	1		15	17	1327
+	3000 EO OC	EDP	43.17	30.25	CT	11	
	23.02.20.62	5	20 10	32 54	16	19	1316
-	01 05 2025	CS-11	C0.14	10:30			7001
+	07:07:07	2 4 4	50.91	33.93	13	16	1251



Quarterly Monitoring Report from NABL approved Laboratory M/s Vibrant Techno Lab Pvt. Ltd. Jaipur is attached as Annexure-2.

TEST REPORT



VTL/AA/01-04 M/s JK White Cement Works (Unit of JK Cement Ltd.) Vill. & Po. Gotan, Dist.-Nagaur, Rajasthan

Report No.: Format No.:

Party Reference No.:

Report Date: Period of Analysis:

Receipt Date

VTL/A/2503270917-20/A 7.8 F 02

NIL

31/03/2025 27-31/03/2025 27/03/2025

Sample Description :

Name & Address of the Party

Ambient Air Quality Monitoring

General Information:-Sample collected by

Instrument Calibration Status

Meteorological condition during monitoring

Date of Sampling

Amblent Temperature (°C)

Surrounding Activity

Scope of Monitoring

Sampling & Analysis Protocol

Sampling Duration Parameter Required : VTL Team

: Calibrated

: Clear sky

: 21/03/2025 to 22/03/2025

Min. 18°C, Max. 35 °C

: Human, Vehicular & Plant Activities

: Regulatory Requirement

: IS-5182 & CPCB Guidelines

: 24 hrs.

: As Per Work Order

			V	Lucation A	Lat Lone		Shright.	1546
-31	selfater.		132 KV55	Hest Shelter Juoniomite	EDF Club Building	CS-1.1	Unit	NAAQS 2009
1.	Parameter	Protocol	23'44'46'1	3144/32°E 26'38'43'N	73"44"33"E 26"38"30"N	73"44"46"£ 26"38"23"N		
			26'38'50'N		70.15	68.52	ng/m'	100
	Particulate Matter	15:5102 (P-23), 2006,	74.89	77.24	7 1/2 1/21			60
Ţ.	(PM10)	RA 2022	38.62	40.16	36.68	04.01	µg/m²	-00
2.	Particulate Matter (PM2.5)	IS 5182 (P-24) -2019	35.65		Sc Bearing	8.29	hg/m³	80
	Sulphur Diaxide	15: 5182 (P-2):Sec 1	11.74	12.10			. (	80
J.	(502)	2023 15: 5182 (P-6), 2006 RA	19,84	2195	17.59	16.48	hg/m3	90.
4.	Nitrogen Dioxide (NO2)	2022	19.04		0.92	0.68	mg/m²	4
_	Carbon Monoxide	1555182 (P-10) -1999,	0.70	0.05	().O <sub>20</sub>		from 3	5
5.	(as CO)	RA2019 (NDIR) IS: 5182 (P-11)-2006.	*BJ.Q(**LOQ1.0)	*RLQ[**LDQ1.0]	*BLQ(**LOQ1.0)	*erd(rodro)	h@/m2	
6.	Senzene (as Chila)	RA.2022			-BLQ(-LOQ18.0)	*BLQ(**L0Q10.0)	hB/m2	400
7.	Ammonia (as NH3)	IS 5182 (P-25) -2018	*Hrd(**rod10.0)	*Brd(**rodrom)		13.20	µg/m <sup>3</sup>	180
-		IS:5182 (P-9):1974.	16.49	18.87	15.32			
9.	Ozone (as 03)	RA.2019 IS:5182 (P-22):2004,		*BLQ(**LOQ0.02)	*BLQ[~LOQ0.02)	*HLQ(**LOQ0.02)	μg/m <sup>3</sup>	1
٠),	Lead (as Pb)	RA.2019	*BLQ(**L0Q0.02)		*BLQ(**LOQ0,5)	*BLQ(**L0Q0,5)	ng/m³	ú
_	Assemble (se As)	VTL/STP/02/SOP/09	*Brd(**rodo:2)	*BLQ[**L0Q0.5]		*BLQ(**LOQ5.0)	ng/mo	20
10,	Arsenic (as As)	IS 5182 (P-26) -2020	*BEQ(**LUQ5.0}	*BLQ(**LOQ5.0)	*BLQ(**L0Q5.0)		ng/m <sup>1</sup>	1 3
11.	Nickel (as NI)	IS:5182 (P-12):2004.	*8LQ(**L0Q0.2)	*BLQ(**LOQ0.2)	*BLQ(**1,0Q0.2)	*BLQ(**L0Q0.2)	"EJ III	1
12.	Henza (a) Pyrene	RA.2019	Codf padaret	1 2 2 2				





RK Yadav Lab Incharge Authorized Signatory

(Approved & Contified) EPA 1984 Recognised, ISD/9001 and OHSAS:45001 Certified

#### Vibrant Techno Lab Pvt. Ltd.

- 9 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020
- C 9929108691, 9810205356, 8005707098; 9549956601

- ₩ 0141-295463E
- 🖾 bd@vibranttechnolab.com
- Www.vibranttechnolab.com





Sample Number: Name & Address of the Party: VTL/AN/01-0+

M/s JK White Cement Works (Unit of JK Cement Ltd.)Vill. & Po.- Gotan,

Dist.-Nagaur, Rajusthan

Ambient Noise Level Monitoring Sample Description: Regulatory Requirment Scope of Monitoring

IS 9989

Protocol Used: Instrument Used:

SLM

Report No.:

Format No.: Party Reference No.:

Report Date:

Receipt Date: Sampling Duration

Sample Collected by

instrument Calibration Status



VTL/N/2503270017-20/A

7.8 F 04

31/03/2025 27/03/2025

24 Hrs.

VIL Team

Callbrated

#### Ambient Noise Level Monitoring Results

General Information:

Meteorological condition during monitoring

Date of Monitoring

Time of Monitoring

Ambient Temperature (°C)

Surrounding Activity

Parameter Required

Clear sky

21/03/2025 to 22/03/2025

: 06:00 AM to 06:00AM

: Min. 18°C, Max. 36°C

: Human, Vehicular & Plant, Activities

: As per Work Order

		67 A C.	CONTRACT.		Location &	Letteng			elevani.
Test. Parameter	Protocol		EVES	Dest Sto /Deplacement 73°44°	e Pampi 12th	ENP Club 73*44 26*38	33 E	73*4	128°H
		Day	Hight	Day Time	Hight Time	Day	Night Time	Day Time	Night
Noise Level	IS:9989-1981, RA	Time	Time			201154	41.2	54.3	39.0
142 dB(A)	2020	63.7	50.0	59.4	42.3	55.9	41.4	71.100	

		Leg In dB (A)	Might
Category of Zenes	Day 95		70 15
กตับสหาร์สโ	65		45
ommercial	50		40

1. Day Time is from 6.00 AM to 10.00 PM.
2. Night Time is recknowed between 10.00 PM to 6.00 AM.
3. Sidence Zone is defined as an area up to 2.00 m around premises of Hospitals, Edwardsonal and Couris. Use of vohicle horn, Loudspeaker and bursting of crackers is banned in these zones.

Note: Micol categories of great one of the four above mentioned categories by the competent Authority and the corresponding standards shall note:

-----End of the Report-----





RK Yadav Lab Incharge Authorized Signatory

Approved 3 Contilled EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

9 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020

\_ 9929108691, 9810205356, B005707098, 9549956601

**2** 0141-2954638

bd@vibranttechnolab.com.

Www.vlbranttechnolab.com



11 | Page







Name & Address of the Party : M/S JK White Cement Works

(Unit of JK Cement Ltd.) Vill. & Po. Gotan, Dist. -

Nagaur, Rajasthan

: VTL/S/2503270003/A Report No.

7:8 F-03 Format No

Party Reference No : NIL

31/03/2025 Report Date

27/03/2025-31/03/2025 Period of Analysis

Receipt Date

27/03/2025

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Raw Milly Kiln ESP-1

Sample Collected By

: VTL Team

Date of Sampling

21/03/2025 : 20 min (11:00 to 11:20 hrs.)

Sampling duration (Minutes)

Stack attached to

: ESP

Make of stack

: MS

Diameter of stack(m)

2.1 m

Height of stack(m)

: 65 m

Instrument calibration status

: Calibrated

Meteorological Condition

: Clear Sky

Ambient Temperaturo - Ta (°C)

Temperature of Stack Gases - Ts ("C)

: 28°C

: 154

Velocity of Stack Gases (m/sec.)

: 16.50

Flow rate of PM (LPM)

: 49

Flow rate of Gas (LPM)

: 20

Sampling condition

: OK

Protocol used

; IS 11255 & USEPA

	Coordinates			L 11 24	Limits
		Test Mathod	Results	Units	FRIGHTS
3.No.	Parameters	The second secon	23.76.	mg/Nm3	30
1	Particulate Matter (PM)	IS: 11255 (P-1): 1985, RA 2019		mg/Nm3	100
_	5 - W. 1902 \	IS: 11255(P-2): 1985; RA-2019	74.55	HEJERATOV	
	Sulphur Dioxide (SO2 )	USEPA 10: 1995	09	mg/Nm3	84
3	Carbon Monoxide (CO.)	4 Out	451 22	ma/Nm3	800
	rouses of Nilrogen (NOX)	IS 11255 (P-7) 2005; RA 2022	491.2E	N. B.	

\*BLO= Below Limit Of Quantification, \*\*LOQ= Limit Of Quantification

"End of Report"







RK Yaday Lab Incharge Authorized Signatory



Page No. 171

(Approved & Comition) EPA. 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

#### Vibrant Techno Lab Pvt. Ltd.

- 9 SC-40, 3rd Floor, Narayari Vihar S, Ajmer Road, Jaipur Raj. 302020
- © 9929108691, 9810205356, 8005707098, 9549956601

**2** 0141-2954638

bd@vibranttechnolab.com

® www.vibranttechnolab.com



#### TEST REPORT



Name & Address of the Porty : M/S JK White Cement Works

(Unit of JK Cement Ltd.) Vol. & Po. Golan, Dist. -

Nagaur, Rajasthan

Report No. Format No. : VTDS/2503270004/A

Party Reference No

7.8 F-03 NIL

Report Data

: 31/03/2025

Period of Analysis

: 27/03/2025-31/03/2025

Receipt Date

: 27/03/2025

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Clinker Quencher (Steam Exhaust ESP)

Sample Collected By

: VIL Team

Date of Sampling

21/03/2025

Sampling duration (Minutes)

36 min. (13:00 to 13:36 hrs.)

Stack attached to

ESP

Make of stack

MS

Diameter of stack(m)

1.80 m

Height of stack(m)

30 m

Instrument calibration status

: Calibrated

Meteorological Condition

Clear Sky

Ambient Temperature - Ta (°C) Temperature of Stack Gases - Ts (°C) 32°C

Velocity of Stack Gases (m/sec.)

232 11.10

Flow rate of PM (LPM)

28

Flore rate of Gas (LPM)

OK

Campling condition

IS 11255 & USEPA

Protocal used Coordinates

	Coordinates	Test Method
S.No.	Parameters	
4	Designate Matter (PM)	IS: 11255 (P-1) : 1985, P
191.0	Below Limit Of Quantification, "LO	Q= Limit Of Quantification

"End of Report"

1985, RA 2019







RK Yadav Lab Incharge Authorized Signatory



Limits

Units

mg/Nm3

Results

18:08

Page Ha. 1/1

Approvate 5 Certified EPA 1986 Recognised, ISO:9001 and OHSAG:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

♥ SC-40, 3rd Floor, Narayan Vihar S, Almer Road, Jaipur Raj. 302020

C 9929108691, 9810205356, 8005707098, 9549956601

T 0141-2954638

devibranttechnolab.com

www.vibranttechnolab.com

13 | Page







Name & Address of the Party : M/S JK White Coment Works

(Unit of JK Cement Ltd.) Vill. & Po. Gotan, Dist. -

Nagaur, Rajasthan

: VTL/S/2503270005/A Report No.

: 7.8 F-03 Format No Party Reference No : NIL 31/03/2025 Report Date

; 27/03/2025-31/03/2025 Period of Analysis 27/03/2025

Receipt Date

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

Sample Collected By

Date of Sampling

Sampling duration (Minutes)

Stack attached to

Make of stack

Diameter of stack(m)

Halght of stack(m)

Instrument calibration status Meteorological Condition Ambient Temperature - Ta (°C )

Temperature of Stack Gases - Ts (°C) Velocity of Stack Gases (m/sec.)

Flow rate of PM (LPM) Flow rate of Gas (LPM)

Sampling condition

Protocal used

: Pet Coxe/ Coal Mill 02

: VTL Team

22/03/2025 : 28 min. (09:30 to 09:58 hrs.)

Bag House

MS : 0.80 m

: 39 m Calibrated : Clear Sky

: 20°C : 78

10.01 35

: OK

: IS 11255 & USEPA

Coordinates	

Co	ordinates		Denulin	Units	Limits
Leave of	5 to en	Test Method	Results		20
S.No.	Paramoters	IS: 11255 (P-1) , 1985, RA 2019	19.0	mg/Nm3	44
Buck	enlare Malter (PIA)	(2) 1522 (b) (1 (200) 1 (200)			

BLO= Below Limit Of Quantification, "LOQ = Limit Or Quantification

"End of Report""







KK Asqax Lab Incharge Authorized Signatory



Page No. 611

Apple of S.E. airlied EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

#### Vibrant Techno Lab Pvt. Ltd.

9 5C-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020

C 9929108691, 9810205356, 8005707098, 9549956601

**2** 0141-2954638

a pd@vibranttechnolab.com

 **www.vibranttechnolab.com** 



#### TEST REPORT



Sample Number: VIUS/04

Name & Address of the Party : MS JK White Coment Works

(Unit of JK-Cement Etd.) Vill. & Pc. Gptan, Dist. -

Nagaur, Rajasthan

Report No.

: VTL/S/2503270005/A

: 7.8 F-03 Format No Party Reference No : NIL

: 31/03/2025 Report Date : 27/03/2025-31/03/2025

Period of Analysis : 27/03/2025

Receipt Date

Sample Description

Stack Emission Monitoring

General Information:-

Sampling Location

: Pet Coke/ Coul Mill-03

Sample Collected By

VTL Team 22/03/2025

Date of Sampling

: 29 min. (11:00 to 11:29 hrs.)

Sampling duration (Minutes) Stack attached to

: Bag House

Make of stack

MS

Diameter of stack(m)

: 0.98 m

Height of stack(m)

: 41 m

Instrument calibration status

: Calibrated

Moteorological Condition

: Clear Sky

Ambient Temperature - Ta (\*C )

24°C

Temperature of Stack Gases - Ts ("C)

Paramuters

: 71

Valocity of Stack Gases (m/sec.)

9.16

Flow rate of PM (LPM)

34

Flow rate of Gas (LPM)

Sampling condition

: OK

Protocol used

IS 11255 & USEPA

Coordinates

S.No.

			1.4 74
- Vac 16 6 d	Results	Unite	Limits
Test Method		W	30
2013	15.31	mg/Nm3	30

15.31

Paniculate Matter (PM) "BLO = Below Limit Of Quantification, "LOOP Limit Of Quantification

IS: 11255 (P-1): 1985, RA 2019







RK Yadav Lab Incharge Authorized Signatory



Page No. 1/1

Approved & Certifies PPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

9 SC-40, 3rd Floor, Narayan Vihar S, Afmer Road, Jalpur Raj. 302020

C 9929108691, 9810205356, 8005707098, 9549956601

C 0141-2954638

M bd@vibranttechnolab.com

₩ww.vibranttechnolab.com

15 | Page

#### TEST REPORT





(Linit of JK Cament Ltd.) Vill & Ps. Gotan, Dist. -

Nagaur, Rajasthan

VTL/S/2503270007/A Report No.

7.8 F-03 Format No : NIL Party Reference No

: 31/03/2025 Report Date.

Period of Analysis

: 27/03/2025-31/03/2025

Receipt Date

27/03/2025

Sample Description

: Stack Emission Monitoring

General Information: Sampling Location

Sample Collected By

: Cement Mitt -1 & 2 : VTL Team 22/03/2025

Date of Sampling Sampling duration (Minutes)

36 min. (12:30 to 13:06 hrs.)

Stack attached to

Bag House MS

Make of stack

0.93 m

Diameter of stack(m) Height of stack(m)

30 m

instrument colibration status

Calibrated Clear Sky.

Meteorological Condition Ambient Temperature - Ta (°C) Temperature of Stack Gases - Ta (\*C)

28°C 69

Velocity of Stack Gases (m/sec.)

7.44

Flow rate of PM (LPM) Flow rate of Gas (LPM) 28

Sampling condition

ÐΚ

Protocol used

IS 11255 & USEPA

	Coordinates	LOS PROCESSOR	Results	Units	Limits
S.No.	Parameters	Test Method	14.57	Emg/Nm3	30
1	Particulate Matter (PM)	IS: 11255 (P-1): 1985, RA 2019			

BLG= Below Limit Of Quantification, "LOQ= Limit Of Quantification







RK Yadav tab Incharge Authorized Signalory



Page No. 1/1

Approved & Cordified EPA 1986 Recognised, ISQ:9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

© 5C-40, 3rd Floor, Narayan Vihar S, Almer Road, Jaipur Raj. 302020

C 9929108691, 9810205356, 8005707098, 9549956601

**2954638** 

bdevibranttechnolab.com

www.vibranttechnolab.com







Name & Address of the Party : M/S JK White Cement Works

(Unit of JK Cement Ltd.) Vill. & Po. Geran, Dist -

Nagaur, Rajasthan

: VTU5/2503270008/A Report No. 7.8 F-03

Format No Party Reference No : NL

: 31/03/2025

Report Date Period of Analysis : 27/03/2025-31/03/2025

: 27/03/2025 Receipt Date

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

Sample Collected By

Cement MIII -3 VTL Team 21/03/2025

Date of Sampling

26 min. (14:10 to 14:36 hrs.)

Sampling duration (Minutes) Stack attached to

Bag House MS

Make of stack Diameter of stack(m) Height of stack(m)

0.69 m 30 m Calibrated

instrument calibration status Meteorological Condition Ambient Temperature - Ta (\*C )

Clear Sky : 33°C 67

Temperature of Stack Gases - Ts (°C) Velocity of Stack Gases (misec.)

10.35 39

Flow rate of PM (LPM) Flow rate of Gas (LPM)

Sampling condition

QK.

Protocol used

S.No

IS 11755 & USEPA

Co	ordinates		Results	Units	Limits	
. 1	Parameters	Test Method	13.30	mg/Nm3	30	
Me.	TO SECTION OF THE PARTY OF THE	IS: 11255 (P-1): 1985; RA 2019	(5.5,5			

Particulate Matter (PM) \*BLQ= Below Limit Of Quantification, \*TLOQ= Limit Of Quantification

"End of Repor"







RK Yadav Lab Incharge Authorized Signalory



Pago No. 11

Approvable Countried EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

© SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020

\_ 9929108691, 9810205356, 8005707098, 9549956601

0141-2954638

bd@vibranttechnolab.com

www.vibranttechnolab.com



17 | Page





Name & Address of the Party : M/S JK White Cement Works

(Unit of JK Cement Ltd.) VIII. & Po. Gotan, Dist. -

Nagaur, Rajasthan

Report No.

: VTUS/2503270017/A

Format No Party Reference No.

7.8 F-03 : NIL

Report Date

: 31/03/2025

Period of Analysis

: 27/03/2025-31/03/2025

Receipt Date

27/03/2025

: Stack Emission Monitoring

General Information:-

Sampling Location

: DG Set 250 KVA

Sample Collected By

: VTL Team

Date of Sampling

: 24/03/2025

Sampling duration (Minutes)

: 30 min. (10 00 to 10:30 hrs.)

Stack attached to

: Acoustic Encloser

Make of stack

: MS

Diameter of stack(m)

: 0.90 m

Height of stack(m)

: 30 m

Instrument calibration status

: Calibrated

Meteorological Condition

: Clear Sky

Ambient Temperature - Ya ('C) Temperature of Stack Gases - Ts ("C) : 24°C

: 125

Velocity of Stack Gases (m/sec.)

10.44

Flow rate of PM (LPM)

Flow rate of Gas (LPM)

: 33

Sampling condition

COK

Protocol used

: IS 11255 & USEPA

	Coordinates		11	41.11	Limits
	Parameters	Test Method	Results	Units	
No	Parameters	170001 70 1900	1.71	om/kw-hr	3.5
	Carbon Monoxide (CO.)	USEPA 10: 1896			0.02
_	Particulate Matter (PM)	IS: 11255 (P-1): 1985, RA 2010	0.017	gm/kw-hr	0.02
	Saurchiare Marten (Leut)		C 27	am/kw-hr	0.40
	Oxde of Nitrogen (NOX))	IS 11255 (P-7) 2005; RA 2022		-	0.19
_	Total Hydrocarbon (HC)	USEPA 18: 1996	0,13	gmåwht	
	rotal rivarocursum (no)	1005 D. 2015	3,42	om/kw-hr	Not Specified
	Sulphur Dioxide (SO2)	1S: 11255(P-2); 1985, RA 2019	V.12		

\*BLQ= Below Limit Of Quantification, \*\*LOQ= Limit Of Quantification

\*\*\*End of Report\*\*\*







Lab Incharge Authorized Signatory



Page No. 1/1

Approved & Corolled EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

9 SC-40, 3rd Floor, Narayari Vihar S, Ajmer Road, Jalpur Raj. 302020

\_ 9929108694, 9810205366, B005707098, 9549956601

**2** 0141-2954638

23 bd@vibranttechnolab.com

www.vibranttechnolab.com

18 | Page





Name & Address of the Party

Sample Description

Sampling Location

Sample Collected By



M/S JK White Cement Works

(Unit of JK Cement Ltd.) Vill. & Po. Gotan, Dist. -

; STP Outlet (STP Treated Water) 500 KLD STP

Nagaur, Rejasthen

: Waste Water

: VTL Team

Format Ho Party Reference No : NIL

7.8 F-01

: 31/03/2025

Period of Analysis : 27/03/2025-31/03/2025

: TC1122725000000405F

: VTL/WW/2503270002/A

Receipt Date

Report Date

ULR No.

Report No.

: 27/03/2025 : 23/03/2025

Sampling Date Sampling Type

: Grab

Sample Quantity

: 2 Ltr.

Preson	rvation : Suitable F d of sampling : 15:3025	Preservation	Sample Qu Coordinate		ur. 1,748795 N & 26,638279E
S.No.	philadelegal /	Test Method	Result	Unit	Limite
5.NO.		IS: 3025 (P-11): 2027	7.72		5.5 to 0.0
1	pH	IS: 3025 (P-17): 2022	18.45	mg/l	20
3	Total Suspended Solids (145)	star duspended cond (100)		*C	Shall not exceed 5°C above the receiving water temperature
_	Oil & Grease	(S:3025 (P-39): 2021	*BLQ(**LOQ-4.0)	mg/l	10
5	Ammonical Nitrogen (es NH3-N)	IS: 3025 ( P-34) Sec 1 2023 (Clause 5.3)	4,32	mg/i	5.0
6	Total Kjeldahl Nitrogen (as NH3)	(Clause 8.0)	6.84		10
7	Biochemical Oxygen Demand (BOD) (3 days @ 27°C)	i5: 3025 (P-44): 2023	8.25	mg/i	10
3	Chemical oxygen Demand (COD)	(S : 3025 (P-58) : 2023	30.60	mg/T	50
9	Chloride (as Cl)	IS: 3025 (P-32): 1988, RA. 2019	949.71	mgti	* 1
19	Sulphide (as S)	IS: 3025 (P-29) : 2022 (Clause 6.0 )	-BLQ(-'LOG-0 1 )	mg/i	2
11	Residual Free Chlorine	(S; 3025 (P-26): 2021 (Clause 5.0)	0.72	mg/l	1.0
12	Faecal coliform	APHA 24th Edition 9221 C ,2023	49	MPN/100 ml	<100

\*BLQ-Below Limit OF Quantification, \*\*LOQ- Limit Of Quantification

\*\*\*End of Report\*\*\*







RK Yadav C Lab Incharge Authorized Signatory



Puge No. 1/1

Approved & Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.


🕏 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jajpur Raj, 302020

<u> 7929108691, 9610205356, 8005707098, 9549956601</u>

**2** 0141-2954638

bdevibranttechnolab.com

www.vibranttechnolab.com





nta Labs Limited

stered Office IDA Phase II, Cherlapally erabad 500 051, Telangana, India 91 40 2726 4141 91 40 2726 3657



Driven by Quality. Inspired by Science.

ISSUED TO:

M/S. J.K. WHITE CEMENT WORKS Unit: - J.K. CEMENT LTD PO. GOTAN, DISTT. NAGAUR RAJASTHAN-342902

INDIA.

Report Number

VLL/VLS/24/24205/001

Issued Date P.O. Number

2025.04.01 4600003729

P.O. Date

2024.09.20

Page 1 of 3

SAMPLE PARTICULARS

Source Emission Monitoring for Raw Mill Kiln ESP Stack-1

(Co- Processing with TDI TAR, Spent Carbon, Waste Mix Liquid, Waste Mix Solid, Process residue and Distillation Residue with Pet

Sample Registration Date

2025.03.06

Sample Collection Date

: 2025.03.03

Analysis Starting Date

2025.03.06

Analysis Completion Date

2025.04.01

Test Required Sample Collected by Vimla Labs Ltd.

PM, SO, NOx HCL HF, CO, O2 and TOC.

TEST REPORT

)		ST REPC	SHOULD VALUE OF SHOULD IN		Limits as per
r. No.	Parameters	UoM	Method of Testing	Results	MoEF&CC Notification GSR 497(E)
				2.10	**
1	Diameter of stack	m		124	
2	Flue gas temperature	oC	Pel Coke+ TDITAR	NA	
3	Ruel	%	Flue Gas Analyzer	8.6	••
4	Oxygen as O <sub>2</sub>		USEPA Method -3	16.3	
5	Velocity	m/sec	USEPA Method =3	37.71	
6	Volumetric flow rate	Nm³/Sec	USEPA method-5	23.5	<30
7	Particulate Mailer	mg/Nrn³	Flue Gas Analyzer	45.2	<100
8	Sulphur Dioxide	mg/Nm3	Flue Gas Andlyzer	290.0	<800
9	Oxides of Nitragen, NOx as NO2	mg/Nrn3	USEPA method -26	2.0	<10
10	Hydrogen Chloride as HCI	mg/Nm³	USEPA melitiou -20	<0.1	<1.0
11	Hydrogen Fluoride as HF	mg/Nm³	USEPA method -13	74.0	<100
12	Carbon Monoxide as CO	mg/Nm3	Flue Gas Analyzer	14.0	
13	Total Organic Compounds as TOC	mg/Nm³	USEPA method -40 & MM5(10)	3.0	<10

All the Values are represented at 10% O2

Dr. SubbaReddy Mallampati Manager-Environment.

Life Sciences Campus, # 5, Neovantage Science & Technology Park, Genome Valley, Shamirpet, Medchal-Malkaigiri Dy Hyderabad - 500 101, Telangana, India. T : +91 40 6740 4040 E : mdoffics@vimts.com URL : www.vimts.com CIN: L24110TG1990PLC011977

nta Labs Limited

listered Office IDA Phase II, Cherlapally lerabad-500 051, Telangana, India +91 40 2728 4141 +91 40 2726 3657



Driven by Quality, Inspired by Science,

ISSUED TO:

M/S. J.K. WHITE CEMENT WORKS

Unit: - J.K. CEMENT LTD

PO. GOTAN, DISTT. NAGAUR,

RAJASTHAN-342902

INDIA.

Report Number

VLL/VLS/24/24205/001

Issued Date

2025.04.01

P.O. Number

4600003729

P.O. Date

2024.09.20

Page 2 of 3

SAMPLE PARTICULARS

Source Emission Monitoring for Raw Mill Kiln ESP Stack-1

(Co- Processing with TDI TAR, Spent Carbon, Waste Mix Liquid,

Waste Mix Solid, Process residue and Distillation Residue with Pet

Coke)

Sample Registration Date

2025.03.06

Sample Collection Date

: 2025.03.03

Analysis Starting Date

2025.03.06

Analysis Completion Date : 2025.04.01

Test Required

Hg & its compounds, Cd + Ti its compounds, Sb+ As+ Pb+ Co+ Cr+ Cu+

Mn+ NI+ V+ Their compounds

Sample Collected by Vimta Labs Ltd.

TEST REPORT

Sr.No.	Farameters	UoM	Method of Testing	Results	MoE.FaCC Notification GSR 497(E)
1	Marcury as Hg + their Compound			0.006	<0.05
2	Cadmium + Thallium (Cd + Tl) +   Their Compound			<0.001	<0.05
	Chromium as Cr + their Compound			0.020	
	Manganese as Mn + their			0.019	(Sb+ As+ Pb+ Co+ Cr+ Cu+ Mn+ Ni+ V+ Their compounds) < 0.5
	Arsenic as As + their Compound	(3.13	USEPA	0.016	
	Antimony as Sb + their Compound	mg/Nm <sup>3</sup> method -29	method -29	0.020	
3	Lead as Pb + their Compound			0.021	
	Coball as Co + their Compound			0.017	
	Copper as Cu + their Compound			0.008	V 0.5
	Nickel as Ni + their Compound			0.020	
	Vanadium as V + their Compound			0.018	
	Sb+ As+ Pb+ Co+ Cr+ Cu+ Mh+ Ni+ V+ Their compounds			0.159	

All the values are represented at 10% Oz



Dr. SubbaReddy Mallampati Manager-Environment.

Life Sciences Campus. # 5, Neovantage Science & Technology Park, Genome Valley, Shamirpet, Medchal-Malkajgiri District. Hyderabad 500 101, Telangana, India. T: +91 40 6740 4040 E: mdoffice@vimta.com URL: www.vimta.com

CIN: L24110TG1990PLC011977

nta Labs Limited

istered Office , IDA Phase II, Chertapally era bad-500 0\$1,Telangana, India -91 40 2726 4141

91 40 2726 3657



Driven by Quality. Inspired by Science.

ISSUED TO:

M/S. J.K. WHITE CEMENT WORKS

Unit: - J.K. CEMENT LTD

PO. GOTAN, DISTT. NAGAUR,

RAJASTHAN-342902

INDIA.

Report Number

VLL/VLS/24/24205/001

Issued Date

2025.04.01

P.O. Number P.O. Date

4600003729

2024.09.20

Page 3 of 3

SAMPLE PARTICULARS

Source Emission Monitoring for Raw Mill Kiln ESP Stack-1

(Co- Processing with TDI TAR, Spent Carbon, Waste Mix Liquid,

Waste Mix Solid, Process residue and Distillation Residue with Pet

Coke)

Sample Registration Date

2025.03.06 Sample Collection Date 2025.03.06 Analysis Completion Date 2025.03.03 2025.04.01

Analysis Starting Date Test Required

PCDD & PCDF

Sample collected by Vinita Labs Ltd.

TEST REPORT

St.No.	Congeners of Dioxins and Forans	WoM	Results
ACIONAL DE	2,3,7,8-TCDD		0.0095
1	1,2,3,7,8-PeCDD		0.0033
2	1,2,3,4,7,8-HxCDD		0.0002
3	1,2,3,6,7,8-HxCDD		0.0002
4			0.0002
5	1,2,3,7,8,9-HxCDD		0.0015
6	1,7,3,4,6,7,8-HpCDD		0.0000
7	OCDD		0.0015
8	2,3,7,8-TCDF	ng/Nm³, TEQ	0.0002
9	1,2,3, <b>7</b> ,8-PeCDF	11g/11111 / 124	0.0025
10	2,3,4,7,8 PeCDF		0.0002
11	1,2,3,4,7,8-HxCDF		0.0003
12	1,2,3,6,7,8-HxCDF		0.0002
13	1,2,3,7,8,9-H×CDF		0.0002
14	2,3,4,6,7,8-HxCDF		0.0001
15	1,2,3,4,6,7,8-HpCDF	-	0.0000
16	1,2,3,4,7,8,9-HpCDF		0.0000
17	OCDF	W-1 750	0.0227
Total Fu	rans & Dioxins	ng/Nm³, TEQ	V.022.
Total Fu	rans & Dioxins	ng/Nm³, TEQ Corrected to 10% O2 Concentration	0.0202
To the Li	s per MoEf & CC Notification GS	R 497(E)	<0.1

Method of Testing: As per USEPA 23 A & 8290

Instruments used: Auto spec Premier (HRGC/HRMS), Delection Limit; 0,01 ng

Dr. SubbaReddy Mallampati Manager-Environment.

Life Sciences Campus, # 5, Neovantage Science & Technology Park, Genome Valley, Shamirpet, Medichal-Malkajorii Distrib Hyderabad - 500 101, Telangana, India. T : +91 40 6740 4040 E : mdoffice@vimta.com URL : www.vimta.com

CIN: L24110TG1990PLC011977



JK White Cement Works, Gotan A Unit of JK Coment Ltd.

CIN: L17229UP1994PLC017199

🕏 P.O. Gotan - 342 902, Dist - Nagaur (Rajasthan), India ◆ +01591 230201 03 (PBX), 230976 (D), ◆ +01591 230206

Www.jkcement.com

#### JKWC/PLG/ENV/03/

REGD A/D

Date: 18.01.2025



The Member Secretary,

Rajasthan State Pollution Control Board

4, Institutional Area, Jhalana Doongari, Jaipur (Rajasthan) - 302 004

C-024 Cement

Sub:

Compliance Report of Consent to Operate conditions under Air & Water Act of M/s JK White Cement Works, situated at P.O. Cotan. Distr. Nagaur. Rojasthan for the period from Oct 2024 to Dec 31,24 (Quarter 3; of Fr 2024 25.

Reference: F(CPM)/Nagaur(Merta)/5(1)/2022-2023/5454-5456 dated 10/11/2023, and Order No:

Dear Sir.

As above subjected matter, submitting herewith the point - wise compliance report of the conditions of consent to operate us per communicated board vides letter no, mentioned as reference, following is the compliance status of C10 under Air & Water Act for the period from Oct-2024 to Dec-2024 (Quarter-3) of FY 2024-25 is attached.

We hope that you will find all the information in order.

Thanking you,

Yours faithfully

FOR J. K. WHITE CEMENT MORKS



Copy to:

Regional Officer.

Reg. A/d

Encl:

Rajasthan State Pollution Control Board First Floor, Sehkari Bhoomi Vikas Bank Ltd., Nagaur- 34100.

as above

Corporate Office

Prism Tower, Ninaniya Estate. Gwal Pahari, Gurugram, Harvana 122102 India

\$ +0124 6919000

admin prismt@jkcement.com

www.jkcement.com









Nimbahera, Mangrot, Gotan (Rajasthan - Muddapur (Karnataka) | Jharli (Haryana) Katni, Panna, Ujjain, M.P. : Provograj, Augarh, Hamirpur (U.P.) : Balasinor (Gujarat) | Fujairah



### M/S JK WHITE CEMENT WORKS COMPLIANCE REPORT OF CONSENT TO OPERATE FOR THE PERIOD: OCT-2024 to DEC-2024 (OHARTER 3) EV 2024 R

Sr.	Conditio	onditions:			ANCE REPORT OF CO OCT-2024 to DEC-20	24 (QUA	RTER-3) FY 2024-25
31.	That	ns					atom <b></b>
1	THAT THIS	Consent to Or	oera e	e is valid to	r period from 01/02/		Compliance Status
2	31/01/20	29.		5 20/10/88/16/00/D	Delica from 01/02/	2024 to	We are communicating
3	11101 1115	Consent is assess	217 778				Table of the contract of the c
	products,	by product of	or ca	rrying out	the following activ	llowing	the state of the s
1	diver h	vprocesses or	provid	ding fallowi	the following activ ng services with cap	ities or	for the condition of 400 000 Th
- 11	given bel Particulo	OW.			a services with cap	pacities	and 8,80,000 TPA White Cen
- 11	CLINKER	174	pe	Quant	ity with Unit		productions.
- I i	THAKER SA		duci	600 000	2.00 TON PER ANNUN		
-4	WHITE CE	MENT   Pro	duct				
3.   7	hat this co	onsent to de a					
0	Mid separ	ale consent in	e vistani	ur existing	talant process & capite is required to be	pagity !	We are come
11	or any ac	idition/ modifie	e offici	distra apere	the is required to be in process or char	taken	We are communicating our agreem
11 34		It is become to a	A		Process of char	1010 in	for obtaining fresh Consent to Establish Operate for further change / alteratio
1 10 100	HALLING OU	antity of office	wt. 4		ong with mode of dis		modification / expansion if any.
To	or the trea	tea effluent sh	all be	as under	ong with mode of dis	posal	THOTAL IS NO INCLUSTRAL
412	YPE 0	of Max.		1 1 1 1 1 1 1 1 1 1			State of the state
1 5	affluent	effluent	d s		posed Qty. of efflu		The state of the s
11		generatio	esffly		D) and made		
W.		n (RLD)	INIT		escatali		THE RESERVE THE PROPERTY OF THE PARTY OF THE
3 113	Domestic .	13.00	N		Civil Commence		The state of the s
S	ewage	1) 1		570	0 KLD - To be treated	am   t	plantation and harticulture.
1				plan	and to be used		—eruner och min <del>till M</del> X
					ntation and horticult		
The	al the sour	ces of air emiss	Jon of	Oper ith	ollution control meas		
and	d the emi	ssion standard	s for t	he most	ollution control meas sed parameters shall	unes I ti	ne Adequate stack heights has provide
and	Jen		. 156000	in biescho	ed parameters shall	be a	The I have been a fact to the feet
50	ources of	Pollution Co	ontrol	Prescribe		- 8	stacks are provided with the end
CH	r Emission:	Measures		Paramet	E-101		\$250 \$450 \$400 \$400 \$400 \$400 \$400 \$400 \$4
. 03	ersont spill	Adequate	Sec.	raidiner	er Standard		and a second
			-11-41 - P	227 by 4 7 m	25. 39. 11 No. 164 F. 164		THE PARTY OF THE P
12	50 PH	The state of the s	o let	Francis Line	FE 30 mg/fw/3	i A	opicable monthly start monitoring
Ear	5± (50 (±)+ ch)	Height Puis Bog Filter	0 J <u>e</u> t	Matter	25. 39. 11 No. 164 F. 164	A re	parts are being submitted to
Ear Ce	ka (57 (4)) chj ment Mill	Height, Puis Bog Filter Adequate S	e jet Stack	Matter	re 30 mg/rvv3	re of	ppicable monthly stack monitoring parts are being submitted to your good fice.
Ear Ce	5± (50 (±)+ ch)	Height, Puis Bog Filter Adequate S Height, Puise	e jet Stack	Matter	re 30 mg/r.w3	re of w	parts are being submitted to your good fice.
Eoi Se -3 (	La (50 TEN ch) ment Mill (65 TPH)	Height, Puis Bog Filter Adequate S Height, Pulse Bag Filter	e jet Stack	Matter	re 30 mg/rvv3	re of Wi	parts are being submitted to your good fice.  The achieving the standards
Se -3 (	Le (30° ) File ch) ement Mill (65° TPH) e D.G set	Height, Puis Bag Filter Adequate S Height, Pulse Bag Filter Acoustic	e jet Stack	Matter	te 30 mg/NM3	of Williams	policable monthly stack monitoring parts are being submitted to your good lice.  The area achieving the standards escribed by the board w. r. t. emissions and ards in stacks. We have instantially
Se -3 (	La (50 TEN ch) ment Mill (65 TPH)	Height, Puis Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure.	e Jet Stack e Jet	Matter Particula Matter	re 30 mg/rvv3	re of Williams store	policable monthly stack monitoring parts are being submitted to your good lice.  The are achieving the standards escribed by the board w. r. t. emissions and ards in stacks. We have installed of the policy of the policy of the policy.
Se -3 (	Le (30° ) File ch) ement Mill (65° TPH) e D.G set	Height, Puis Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St	e Jet Stack e Jet	Matter Particula Matter	te 30 mg/NM3	re of wind pression on	populable monthly stack monitoring parts are being submitted to your good fice.  The are achieving the standards asscribed by the board w. r. t. emissions indured in stacks. We have installed attitudes online apacity meters & allysers for monitoring of PM 50.
Ce -3	E (50 PP) ch) ment MIII 65 TPH) e D.G set 0KVA]	Height, Puis Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height	e Jet Stack e Jet	Matter Particula Matter	te 30 mg/NM3	Arres of Williams of Co.	populable monthly stack monitoring parts are being submitted to your good fice.  The parts are achieving the standards ascribed by the board w. r. t. emissions indured in stacks. We have installed attitudes online apacity meters & alysers for monitoring of PM, SO2 NOX 1551016.
Ce -3   One (250)	chy chy ment Mill 65 TPH) e D.G set 0KVA1	Height, Puis Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height	e jet Stack e jet tack	Matter Particula Matter	ie 30 mg/NM3	re of war on an am	policable monthly stack monitoring parts are being submitted to your good lice.  For are achieving the standards escribed by the board w. r. t. emissions indured in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOX vers. Stack monitoring could be PCB's
Confession Period	chy chy ment Mill 65 TPH) e D.G set 0KVA1	Height, Puis Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height Adequate St Height, Pulse	e jet Stack e jet tack	Particular Particular	te 30 mg/NM3	Aire of wind part store on em	policable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions indured in stacks. We have installed ntinuous online apacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx ission. & data Connected to PCB's vers. Stack monitoring results are given.
Coo (121	chy ment Mill 65 TPH) e D.G set OKVA) coke / pl Mill - 3 TPHJ	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height Adequate St Height, Pulse Bag Filter	e Jet Stack e Jet tack tack Jet	Matter Particula Matter	ie 30 mg/NM3	Aire of wind part store on em	pplicable monthly stack monitoring parts are being submitted to your good fice.  The area achieving the standards asscribed by the board w.r.t. emissions indured in stacks. We have installed ntinuous online apacity meters & alysers for monitoring of PM 50.
Configuration (12.5) Petc	chy chy ment Mill 65 TPH) e D.G set OKVA) coke / pl Mill - 3 TPH)	Height, Puis Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height Adequate St Height, Pulse Bag Filter	Stack Stack Det tack Jet	Particular Matter	te 30 mg/NM3	Aire of William Series in rep	pplicable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions indured in stacks. We have installed ntinuous online apacity meters & alysers for monitoring of PM, SO <sub>2</sub> NO <sub>2</sub> vers. Stack monitoring results are given Annexure-1 & third-party monitoring ofts are attached as annexure - 2.
Con (121) Petc Con (121)	chy chy chent Mill 65 TPH) e D.G set OKVA1 coke / al Mill - 3 TPH) coke /	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse	Stack Stack Det tack Jet	Particular Matter  Particular Matter  Particular	te 30 mg/NM3	Aire of win pressed con ann erm Ser in rep	ppicable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions indured in stacks. We have installed ntinuous online apacity meters & alysers for monitoring of PM, SO2 NOX ission. & data Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring arts are attached as annexure - 2.  DG sets are used in emargance.
Coo (121) Petc Coo (122)	chy chy ement Mill 65 TPH) e D.G set OKVA1 coke / al Mill - 3 TPH) coke / I Mill - (5 TPH	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height Adequate St Height, Pulse Bag Filter	Stack Stack Det tack Jet	Particular Matter	te 30 mg/NM3	Aire of win prestor on one servin rep	popicable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions indured in stacks. We have installed ntinuous online apacity meters & alysers for monitoring of PM, SO2 NOX ission & adia Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring arts are attached as annexure - 2.  DG sets are used in emergency only.
Peta Coa (121) Peta Coa (121) Peta Coa (182)	coke / I Mill – (5 TPH)	Height, Pulse Bag Filter Adequate St. Height, Pulse Bag Filter	Stack Stack e Jet tack Jet ack Jet	Particular Matter  Particular Matter  Particular	te 30 mg/NM3	Aire of wing prestor on one of the only	ppicable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online apacity meters & alysers for monitoring of PM, SO2 NOX ission. & adia Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only.  250 KVA DG set is used in emergency.
Petc Coo (121) Petc Coo Coo Coo Coo Coo Coo Coo Coo Coo Co	S. (50 PP) ch) ment M(I) 65 TPH)  e D.G set OKVA1  coke / I M(I) - (5 TPH I) ncher	Height, Pulse Bag Filter Adequate Steph Pulse Bag Filter Acoustic Enclosure, Adequate Steph Pulse Bag Filter	Stack e Jet tack lack Jet ack Jet	Particular Matter  Particular Matter  Particular Matter  Particulate Matter	te 30 mg/NM3  = 30 mg/NM3  = 30 mg/NM3	Au re of win pressed on em Ser in rep The Ine only (700	pplicable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online apacity meters & alysers for monitoring of PM, SO2 NOX ission. & adia Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring arts are attached as annexure - 2.  DG sets are used in emergency only.  250 KVA DG set is used in emergency.  Two nos. of D.G sets (3500 KVA x 2)  0 KVA) not in operation which key
Peta Cood (121) Peta Cood (121) Peta Cood (121) Peta Cood (131) Peta Cood (131)	chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / al Mill - 3 TPHJ coke / 1 Mill - (5 TPH a)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse	Stack e Jet tack lack Jet ack Jet	Particular Matter  Particular Matter  Particular Matter  Particulate Matter	te 30 mg/NM3  - 30 mg/NM3  30 mg/NM3	An re of which store on the rep The only (700 dism	policable monthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions indards in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx ssion & adia Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) 0 KVA) not in operation which have antitled. Stack monitoring upper to the content of the cont
Petc Cood (121) Petc Cood (122) Petc Cood (122	chy chy chy chemic Mill 65 TPH) e D.G set 0KVA1 coke / di Mill - 3 TPHI coke / di Mill - (5 TPH di Chev coke /	Height, Pulse Bag Filter Adequate Steph Pulse Bag Filter Acoustic Enclosure, Adequate Steph Pulse Bag Filter	Stack e Jet tack lack Jet ack Jet	Particular Matter  Particular Matter  Particular Matter  Particulate Matter	te 30 mg/NM3  = 30 mg/NM3  = 30 mg/NM3	An re of which store on the rep The only (700 dism	pplicable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online apacity meters & alysers for monitoring of PM, SO2 NOX ission. & adia Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring arts are attached as annexure - 2.  DG sets are used in emergency only.  250 KVA DG set is used in emergency.  Two nos. of D.G sets (3500 KVA x 2)  0 KVA) not in operation which key
Peta Cood (121 Peta C	chy chy ment Mill 65 TPH) e D.G set 0KVA) coke / al Mill - 3 TPH) coke / I Mill - (5 TPH b) noches e (Kirn et)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height Adequate St Height, Pulse Bag Filter Adequate Ste Height, Pulse Bag Filter Adequate Ste Height, Pulse Bag Filter	Stack e Jet tack lack Jet ack Jet	Particular Matter  Particular Matter  Particular Matter  Particulate Matter	te 30 mg/NM3  = 30 mg/NM3  = 30 mg/NM3	An re of which store on the rep The only (700 dism	policable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx sisten & acra Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) O KVA) not in operation which have antitled. Stack monitoring upport of DG antitoring upport
Peta Cood (121) Peta Cood (121	chy chy chy cherit Mill 65 TPH) e D.G set 0KVA) coke / al Mill - (5 TPH b) none; e (Kirn et) Will Kiln	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	fack e Jet tack tack Jet Jet Jet	Particular Matter  Particular Matter  Particular Matter  Particular Matter  Particular Matter  Particular Matter	te 30 mg/NM3  30 mg/NM3  30 mg/NM3	An re of which store on the rep The only (700 dism	policable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx sisten & acra Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring arts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) O KVA) not in operation which have antitled. Stack monitoring upper at the content of the con
Petc Cood (12 1 Petc Cood (12	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height Adequate St Height, Pulse Bag Filter Adequate Ste Height, Pulse Bag Filter Adequate Ste Height, Pulse Bag Filter	fack e Jet tack tack Jet Jet Jet	Particular Matter  Particular Matter  Particular Matter  Particulate Matter	te 30 mg/NM3  30 mg/NM3  30 mg/NM3	An re of which store on the rep The only (700 dism	policable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx sisten & acra Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) O KVA) not in operation which have antitled. Stack monitoring upport of DG antitoring upport
Peta Cood (121) Peta Cood (121	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	fack e Jet tack tack Jet	Particular Matter	te 30 mg/NM3  30 mg/NM3  30 mg/NM3  10 mg/NM3  100 mg/NM3	An re of which store on the rep The only (700 dism	policable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx sisten & acra Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) O KVA) not in operation which have antitled. Stack monitoring upport of DG antitoring upport
Petc Cood (12 1 Petc Cood (12	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	Stack e Jet tack tack Jet	Particular Matter  Particular Ma	te 30 mg/NM3  30 mg/NM3  30 mg/NM3	An re of which store on the rep The only (700 dism	policable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx sisten & acra Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) O KVA) not in operation which have antitled. Stack monitoring upport of DG antitoring upport
Petc Cood (12 1 Petc Cood (12	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	fack e Jet tack tack Jet	Particular Matter  Particular Ma	te 30 mg/NM3  30 mg/NM3  30 mg/NM3  10 mg/NM3  100 mg/NM3	An re of which store on the rep The only (700 dism	policable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx sisten & acra Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) O KVA) not in operation which have antitled. Stack monitoring upport of DG antitoring upport
Petc Cood (12 1 Petc Cood (12	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	Stack a Jet stack Jet stac	Particular Matter  Particular Ma	10 mg/NM3 10 mg/NM3 10 mg/NM3 10 mg/NM3	An re of which store on the rep The only (700 dism	policable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx sisten & acra Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) O KVA) not in operation which have antitled. Stack monitoring upport of DG antitoring upport
Petc Cood (12 1 Petc Cood (12	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	Stack e Jet tack tack Jet Jet Jet Ck	Particulate Matter	10 mg/NM3 10 mg/NM3 10 mg/NM3 10 mg/NM3 10 mg/NM3	An re of which store on the rep The only (700 dism	policable menthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions induced in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx sisten & acra Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring arts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) O KVA) not in operation which have antitled. Stack monitoring upper at the content of the con
Petc Cood (12 1 Petc Cood (12	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	Stack a Jet tack lack Jet ack Jet ck	Particulate Matter  Partic	10 mg/NM3 10 mg/NM3 10 mg/NM3 10 mg/NM3 10 mg/NM3	An re of which store on the rep The only (700 dism	policable monthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions indards in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx ssion & adia Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) 0 KVA) not in operation which have antitled. Stack monitoring upper to the content of the cont
Petc Cood (12 1 Petc Cood (12	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	se Jet Stack e Jet tack tack Jet ack Jet Ck Stack Stack Jet	Particular Matter  Particular Matter  Particulate Matter  Particul	10 mg/NM3	An re of which store on the rep The only (700 dism	policable monthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions indards in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx ssion & adia Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) 0 KVA) not in operation which have antitled. Stack monitoring upper to the content of the cont
Petc Cood (12 1 Petc Cood (12	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	se Jet Stack e Jet tack lack Jet ack Jet Ck Stack Jet	Particulate Matter  Partic	10 mg/NM3 10 mg/NM3 10 mg/NM3 10 mg/NM3 10 mg/NM3	An re of which store on the rep The only (700 dism	policable monthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions indards in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx ssion & adia Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) 0 KVA) not in operation which have antitled. Stack monitoring upper to the content of the cont
Petc Cood (12 1 Petc Cood (12	chy chy chy chent Mill 65 TPH) e D.G set 0KVA1 coke / all Mill - 3 TPH) coke / I Mill - 3 TPH b) nother e (Kiln set) Mill Kiln set)	Height, Puise Bag Filter Adequate S Height, Pulse Bag Filter Acoustic Enclosure, Adequate St Height, Pulse Bag Filter Adequate St Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto Height, Pulse Bag Filter Adequate Sto	stack e Jet tack lack Jet ack Jet ck lack Jet la	Particular Matter  Particular Ma	10 mg/NM3	An re of which store on the rep The only (700 dism	policable monthly stack monitoring parts are being submitted to your good lice.  are achieving the standards escribed by the board w. r. t. emissions indards in stacks. We have installed ntinuous online opacity meters & alysers for monitoring of PM, SO <sub>2</sub> NOx ssion & adia Connected to PCB's vers. Stack monitoring results are given Annexure-1 & third-party monitoring orts are attached as annexure - 2.  DG sets are used in emergency only. 250 KVA DG set is used in emergency. Two nos. of D.G sets (3500 KVA 2) 0 KVA) not in operation which have antitled. Stack monitoring upper to the content of the cont

Cd + Th  + their 0.05 mg/Nn  compounds  Hg and its 0.05 mg/Nn  compounds	
compounds Hg and its 0.05 mg/Nm	
Compounds High and its 0.05 mg/Nm Compounds	13
compounds	1
campounds	3
D D D	361
Sb + As + Pb	11
*Co+ C' +	11
Cu +Mn +	
Ni + V +	
their	
Two nos. of Compounds	
D.G. rote USO ma/NA/3	
13500 PVA Profitculate 75 ma/NM3	11
2) (7000 Maiter	
KVA NOx 710 mg/NM3	
6 That the domestic sewage shall NMHC 100 mg/NM3	
	in the second
conform to the standards prescribed under the Environment (Protection) Act-1986 for disposal into laboration	We are complying with all the parame
(Protection) Act-1986 for disposal into Inland Surface Water. 1	
main parameters for regular monitoring shall be as under.	
CA2	- I The state of t
PAT VOIDE	is attached herewith as Annexure 2,
The second of th	
To the degree Ce and	
Chemical Oxygen Demand Not to except forms in	
NH4 - Ammoniacal Nitropen for NI	
18 10101	•
Total suspended Solids	
Fecal Coliform [MPN per 100 ml] Not to exceed 20 mg/l	
That this consent to operate is valid for the production of clinks 6 00,000 TPA & white cement 8 80,000 TPA	
That the total capital investment as on 19.09.2023 as per the C. a certificate submitted by the unit is Rs 371.66 crores which include the cost of land, building, plant & machinery and miscellaneous assets.  That the industry shall comply with all the capalities to the conditions t	s s
That the industry shall comply with all the conditions imposed by the SEIAA, Jaipur while issue of environment clearance vide letter no F(14)/SEIAA/SEAC Raj/SecIt/Project/ Cat.3(b)81/ (367)/11-12 dated 28/12/2012 and subsequently amended vide letter dated letter dated letter and the project of the second subsequently amended vide letter dated letter dated letter and the second subsequently amended vide letter dated letter	and MoEF&CC timely.
inatina nazaraous waste/ non hazaradus waste, shall be iused/co-	Agreed.
processed in cement kiln without obtaining prior permission from	Marabu.
CPCB & RPCB as per the provisions of Hazardous and Other Waste	
(Management & Transboundary) Rules, 2016 and consent to	
establish/operate from the State Board, if applicable.  That no fuel other than Indian coal/imported coal/petcoke shall be used in kiln without prior consent from the State Board.	
traction tile tile tile till indian coal/imported coal/petcoke chall ha	Yes noted and complying with,
THE WITHOUT DESCRIPTION OF STREET	and and complying willy
used in kiln without prior consent from the State Board.	Adjust We are allerial
that the industry shall use had as a fate Board.	Agreed We are submitting the petcoke
That the industry shall use Indian & imported coal/pelcake as feedstock in the manufacturing productions.	
That the industry shall use Indian & imported coal/petceke as feedstock in the manufacturing process in the kills of cemeral plant only and quantity of perceke use.	detail or monthly basis to your office.
That the industry shall use Indian & imported coal/celcoke as feedstock in the manufacturing process in the kiln of cemeral plant and quantity of percoke use shall not exceed to 82500 lons per annum (7750 lons per month) without	octor of Mortifly basis to your office.
That the industry shall use Indian & imported coal/detceke as feedstock in the manufacturing process in the kills of cemeral plant only and quantity of percoke use shall not exceed to 82500 tons per annum (7750 tons per month) without prior consent from the State Board. The quantity of percoke parallel process.	design of Profilmly basis to your office.
That the industry shall use Indian & imported coal/detacke as feedstock in the manufacturing process in the kills of cemeral plant only and quantity of percake use shall not exceed to 82500 Ions per annum (7750 Ions per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 Ions per percay.	design of Profitnity basis to your office.
That the industry shall use Indian & imported coal/detacke as feedstock in the manufacturing process in the kills of cemeral plant only and quantity of percoke use shall not exceed to 82500 Ions per annum (7750 Ions per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from the state of the control o	
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the kills of cemeral plant only and quantity of petcoke use shall not exceed to 82500 lons per annum (7750 lons per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered (and their Board's registered).	Agreed.
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the kills of cemeral plant only and quantity of percoke use shall not exceed to 82500 lons per annum (7750 ions per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.	Agreed.
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the kills of cemeral plant only and quantity of percoke use shall not exceed to 82500 lons per annum (7750 ions per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.	Agreed.
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the kills of cemeral plant only and quantity of petcoke use shall not exceed to 82500 lons per annum (7750 ions per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.  That the industry shall not store petcoke for more than its three imonths consumption.	Agreed.  We are ensuring compliance within the
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the kilm of cemeral plant only and quantity of percoke use shall not exceed to 82500 tons per annum (7750 tons per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.  That the industry shall not store petcoke for more than its three months consumption.	Agreed.  We are ensuring compliance within the stipulated time.
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the killing cemeral plant only and quantity of percoke use shall not exceed to 82500 tons per annum (7750 tons per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.  That the industry shall not store petcoke for more than its three months consumption.	Agreed.  We are ensuring compliance within the stipulated time.
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the kills of cement plant only and quantity of petcoke use shall not exceed to 82500 lons per annum (7750 lons per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.  That the industry shall not store petcoke for more than its three imports consumption.  That the industry may in portities better the factors of the industry. For import of petcoke the industry shall obtain registerial.	Agreed.  We are ensuring compliance within the
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the kilm of cemeral plant only and quantity of percoke use shall not exceed to 82500 tons per annum (7750 tons per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.  That the industry shall not store petcoke for more than its three months consumption.  That the industry may in partitle petcoke for more than its three consignment shall be in the name of the industry. For import of petcoke the industry shall obtain registration from the State Board.	Agreed.  We are ensuring compliance within the stipulated time.  Agreed, We are complying the same.
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the killing cemeral plant only and quantity of percoke use shall not exceed to 82500 tons per annum (7750 tons per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.  That the industry shall not store petcoke for more than its three months consumption.  That the industry may in partitle petcoke for more than its three consignment shall be in the name of the industry. For import of petcoke the industry shall obtain registration from the State Board.	Agreed.  We are ensuring compliance within the stipulated time.  Agreed, We are complying the same.
That the industry shall use Indian & imported coal/pelcoke as feedstock in the manufacturing process in the kills of cement plant only and quantity of percoke use shall not exceed to 82500 lons per annum (7750 ions per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.  That the industry shall not store petcoke for more than its three months consumption.  That the industry shall not store petcoke for more than its three months consumption.  That the industry shall be in the name of the industry. For import of petcoke the industry shall obtain registration from the State Board, that the industry shall submit details of pet coke purchasege form various sources during the second code perchasege.	Agreed.  We are ensuring compliance within the stipulated time.  Agreed, We are complying the same.
That the industry shall use Indian & imported coal/petcoke as feedstock in the manufacturing process in the kills of cement plant only and quantity of percoke use shall not exceed to 82500 lons per annum (7750 lons per month) without prior consent from the State Board. The quantity of petcoke permitted for import shall not exceed to 82500 tons per annum.  That the unit shall procure petcoke from Board's registered producer or refineries and their Board's registered / authorized dealers only or may import directly.  That the industry shall not store petcoke for more than its three months consumption.  That the industry may in port the petcoke for more than its three months consumption.	Agreed.  We are ensuring compliance within the stipulated time.  Agreed, We are complying the same.

	the month and opening and closing stock to the State Board monthly basis.	on
100		
18	monitoring systems at all the main stacks (attached to kiln, coal cement mill and clinker cooler etc.) to monitor the emission level particulate motter (PM), SO2 and NOx etc. and connectively of same shall be ensured with SMCs. CRCs to and connectively of	mill, stacks & connected with RSPCB servers.
19		
20	That for the control of fugitive emission guidelines/ code of pract as issued by CPCB will be followed.	
2.0	That all the recommendations made in the Charter of Corpora Responsibility for Environment Protection for Cement Plants shall implemented.	
21	that the industry shall comply with revised emission standards notified by the MoEF & CC. Gol New Delhi for certain plants via gazette notification dated 25/08/2014 without co-processing waste) subsequently amended on 9/05/2016 and notified via notification dated 10/05/2016 with co-processing of waste whichever is applicable.	Environment Protection, as applicable, res, we are complying with all revised emission guidelines as prescribed by the MOEF&CC, CPCB/RSPCB.
	That guidelines on co-processing in cement industries issued by the Central Pollution Control Board shall be compiled, if applicable.	
24	That the industry shall maintain stack of adequate height and adequate air pollution control measures at all the sources of emissions so as to achieve the prescribed emission standards that adequate infrastructure facility for stack emission monitoring shall be maintained at all the stacks viz klin, cooler, cement mill an acousting the stacks of the	adequate height & PCM to meet the norms according to the guidelines.  Adequate infrastructure facility for stack emission monitoring has provided at all
25 J	That no additional source of air pollution shall be installed withou prior consent from the State Board.	
26 7	hat closed canveyor belts thall be some for	source of air pollution without prior
27   11 10 10	a minimize the fugitive emissions.  hat the industry shall maintain dust collection and extraction system  o control fugitive dust emissions at all the transfer points and  cading/unloading areas.  hat all the raw materials and products shall be stored in closed	the possibility of fugitive emission or transportation of powder form materials. We have maintained dust collection and extraction system to control fugitive dust emissions at all the transfer points and coading/unloading area at site.
		All the raw material (powder form) and products are stared in closed covered shed and silos.
to	nal cemented roads shall be provided & maintained in good andition inside the premises to minimize the fugilive emissions due vehicular movements.	All roads are cemented (Pucca) in plant premises and maintained in good condition to minimize the funitive
1 22	at water sprinkling and cleaning of roads by vacuum cleaner all be done regularly to control the fugitive emissions generated the lovehicular movement.	emissions due to vehicular movements. Water sprinkling system is installed for controlling fugitive emissions. Sweeping machine and vacuum cleaner has been accloved for regular cleaning to control the fugitive emissions generated due to
Inc hec	at the recommendations of the policy briefs related to human aith risk due to cement dust exposures shall be complied.	yethcular movement.  We are following recommendations of policy related to human health risk due to cement dust exposures. Our plant is ISO 9001, ISO 14001, ISO 45001, ISO 50001 & SA 8000 Certified. We are committed to demonstrate continual improvement in our trivironmental, Occupational Health
of n	rlocked with the pollution control equipment that in the event	Pollution control measures interlocked with production equipment, which on
That mair reco	separate energy meter & hour meter shall be provided and	increase in levels of pollutants, the production process stops automatically.  We are maintaining all records as per condition.

122		
34	India, Notification dated 14th September 1999, amended up date relating to fiv ash management, and shall be a mended up	p to because plant is engaged in wh
200		
35	That industry shall maintain continuous ambient air que monitoring stations in all directions for maniform of gase emissions and particulate matter in the ambient air and record the same shall be submitted on quarterly bass to the State Board	we have maintained four number continuous ampient air quality monitoris of stations and four number manual stations.
		air quality monitoring station is connected to PCB's servers. Quarterly monitoring reports are submitting timely to your good office and report is attached.
36	That the total water consumption shall not exceed to 1077 K	Annexure-1.
	[Bailer/cooling-100.00 KLD industrial use 805 KLD domestic use- KLD and others: 155.00 KLD, and the freshwater equirement shall meet from ground water (2.77 KLD) and recycled water from \$19 (2.76 KLD).	12
	That the industry shall comply with all the conditions of CGWA NO for abstraction of ground water up to 1050 m3/day issued vide NO No. CGWA/NOC/IND/REN/2/2021/ 59674 with validity up 29.11.2022. The industry shall get renewed the NOC for drawl groundwater from CGWA and submit a copy of the same to the office within 03 margins.	received dated 22.08.2024 valid up to 29.11.2024 with 945 KLD (945X360). Again of renewal application was submitted as
	office within 03 months.  That ground water in excess to 1950 KID shall not be abstracted without programmission from COMM.	deemed valid up to 29,11,2026 as pe
	The same of the sa	_ water NOC.
8	hat the water meter shall be installed and maintained at all the porewells to measure the quantity of daily ground water withdraws a fecord of the same shall be maintained on daily basis that the domestic wastewater generated from the cement planting that exceed to 13.00 ktp. The remarks that the comment planting that exceed to 13.00 ktp. The remarks that the comment planting that exceed to 13.00 ktp. The remarks that the comment planting that exceed to 13.00 ktp. The remarks that the comment planting the comment planting that the comment planting that the comment planting that the comment planting that the comment planting the comment planting that the comment planting the comment planting that the comment planting the comment planting that the comment planting	Digital water flow meters along with telemetry system are installed at all bare
l ki	hall not exceed to 13.00 KLD. The domestic wastewater shall be reated through existing sewage treatment plant (STP) of 50 LD located in the colony of per dandaras mentioned a condition no.7 and the same shall be used for in the analytic unposes within the premises.	
or	on land.	wastewater is being discharged inside or outside the factory premises in to a
of ge	at suitable flow measuring devices/ meters on the intet and outlet STP shall be maintained. Daily record of domestic wastewater eneration and its treatment one utilization shall be maintained.	Flow measuring digital meter is installed on the inlet and outlet of STP and daily record is maintained. Treated water is
180	at inaustry shall comply with the provisions of Hazardous & others aste (Management, & Transboundary Movement) Rules, 2016 and cord of daily hazardous waste generation and its disposal shall maintained.	Complied with.
The	at the industry shall carryout effluent completely	
and rec Go	olysis report from the State Board Jaboratory/ Jaboratory tognized by Ministry of Environment & Forests (MoE&F) verament of India.	monitoring/ambient air quality reports is being done on quarterly basis from recognized NABL approved laboratory
1000	of the industry has to mandatorily carry out at least 25% of the signated frequency of sampling/monitoring as paid monitoring the State Board laboratory.	are attached as Annexure-2.  Yes, we are ensuring the 25% paid monitoring yearly by the state board.
ma	t suitable measure for rain water harvesting for artificial charge of ground water shall be taken.	laboratory.  We have taken suitable measures for rain water narvesting for artificial recharge of ground water at plant, colony and mines
logi	t the plantation in alleast 33% of total area of the project in and sund the identification in alleast shall be carried out & maintained.	We covered more than 33% of total area in green bell. Tree sapling of Neem, Desi Ashok, Pendular Ashok, Arjun, Phycus panda, Kaner, Karanj, Duranta etc. has been planted in the plant and colony
	WIR ON	area along with boundary side & nearby.  Photographs of the plantation are attached as annexure – 3.

48	That the industry shall make all efforts to control dust emissions are keep suspended particulate matter (SPM) as well as noise level within the prescribed norms. The industry shall utilize all the available	ls per condition. Different types of plan
	development of greenbeit with species like sids/circus mulbiers on jamun for control of SOV and Neem Transacrae Palas and Church	le l'species have been planted and submi or the compliance accordingly.
	trees for general purpose of Corners Plant and Mausail, Be Ashoxa, Pipal and Tulip trees for the control of noise level	er 1
49	Compilance in this regard shall be submitted within 4 months	
	That no Single Use Plastic (SUP) item, which is banned vide Ministry of Environment, Forest and Climate Change (MOEF & CC Government of India notification dated 12.08.2021 shall be used if the industry/unit premises.	
50	That the industry shall also ensure the compliance of all the other conditions of revised consent order no. 2022-23/CPM/8675 date: 23.12.2022	Yes. We are complying the same,
51	That the industry shall submit the quarterly compliance report of a the above conditions to the State Board.	
52	That this consent is being issued in supersession of earlier consent issued vide letter no.3242-3245 dated 11,12,2019.	17.13
53	Inal notwithstanding anything provided hereinghove the state	1 Marian marian and 1 Marian marian and 1 Marian ma
	section 27(2) of the Water Act and under section 21(6) of the Air Act to review anyone or all the Education (1997).	to comply with all other requirements of Air act & Water act.
	purpose of A1 Act & Water Act.	
54	That the grant of this Consent to Operate is issued from the environmental angle only, and does not absolve the project proponent from the other statutory obligations prescribed under any other law or any other instrument in farce. The sole and	for this condition.
- 1	complete responsibility to comply with the conditions laid down in all other laws for the time-being in force, rests with the industry unit project proponent.	
55	that the grant of this Conson to Operate shall not in any way, adversely affect or paparage the paul processing it are	for this area different
	this integration the past or that could be instituted against you by the State Board for violation of the provisions of the Act or the Rules made thereunder.	or his condition
9	That the Project Proponent shall comply with provisions of the E-waste (Management) Rules, 2016 and ensure that e-waste generated by them is channelized through collection centre or dealer of authorized producer or dismantler or recycler or through designated take back service provider of the producer to authorized dismantler or recycler.	We maintain the generation record of E-waste and submit annual return in form 3 annually. E-waste is disposed off to registered recycler only and ensuring the compliance as per board condition.
5	hat the Project Proponent shall maintain tecord of e-waste generated by them in Form-2 and make such records available for crutiny by the Board.	We maintain the generation record of E- waste in form no. 2 and complying with.
i	hat the Project Proponent shall file annual returns in Form-3, to the loard on or before the 30th day of June following the financial year owhich that return relates.	We submit the annual return of E-waste in form no. 3 annually by the 30th Jun of every year.
् d : d	hat the transportation of e-waste shall be carried out as per the charifest system whereby the transporter shall be required to carry a locument (three copies) precared by the sender giving the details , is per Form-6.	During disposal of E-waste, we fill and maintain all copies of manifest in form -6 and provide the three copies to the
Be Be all all pi He	nat the Project Proponent shall comply with provisions of the afferies (Management and Handling) Rules, 2001 (as amended) and submit half yearly returns (as bulk consumer, importer, uctioneer, recycler as the case may be) to the State Board as rovided under Rule 10 (2) (ii) of the Battery (Management and analing) Rules, 2001 (as amended), in case the Project Proponent and analing of the state of the Project Proponent and analysis and consumer even then the land half rules and land of the land	transporter after details completion. We submit the half yearly return in form VIII of battery waste time to time and also ensuring the disposal of battery waste to the registered recycler or dealers only.
re ar	and made available to the afficers of the Roard	Ensuring the disposal of battery waste to the registered recycler or dealers only. We are also maintaining the battery waste generation record and complying

1282

# MONTHLY ENVIRONMENT MONITORING REPORT STACK MONITORING REPORT

Annexure-1

MONTH: OCT-2024

DIA Height.  (in From G.L.
800 23
L
-
1
Raw Mill and Kiln Stack HSP-11
1400
-
000
000
000
000
920
Forma Plant (Baa Chemony Co.
0001
2005

1	
L	
C	)
FP	
2	
O	
Z	
8	
2	
Z	
0	
2	
>	
Ξ	
A	
2	
~	
-	
1	
Z	
AMBIEN	
V B	
3	
اد	

under shutdown

SR.         DATE         LOCATION         PM:0         FM:2         SO <sub>2</sub> NOx         CO           1         01.10.2024         132 KV SS         44.79         37.51         14         17         1270           2         31.10.2024         132 KV SS         50.95         26.64         12         16         1293           3         01.10.2024         Rest Shelter         46.48         30.25         15         18         1304           5         01.10.2024         EDP         46.48         31.10         13         19         1282           6         31.10.2024         EDP         52.31         30.26         14         16         1283           7         01.10.2024         EDP         52.31         30.26         14         16         1293           8         31.10.2024         C5-11         43.63         32.47         15         15         1316           8         31.10.2024         C5-11         45.67         34.64         13         17         13.00				MONTH: OCT-2024	V			
DATE         LOCATION         PM <sub>10</sub> PM <sub>2</sub> s PM <sub>2</sub> s SO <sub>2</sub> NOx Hg/M³         PM <sub>2</sub> s PG/M³         NOx Hg/M³         N				707 170 1111				
132 KV SS         Hg/M³		DATE	LOCATION	P.M.10	PM25	50,	NO.	
132 KV SS       44.79       37.51       14       17       17         132 KV SS       50.95       26.64       12       16         Rest Shelter       46.48       30.25       15       18         Rest Shelter       44.19       32.50       14       16         EDP       46.48       31.10       13       19         EDP       52.31       30.26       14       16         CS-11       43.63       32.47       15       15         CS-11       45.67       34.64       13       17				µg/M³	UG/M3	1100/1643	<>>	3
132 KV SS       50.95       56.95       26.64       12       17         Rest Shelter       46.48       30.25       15       16         Rest Shelter       44.19       32.50       14       16         EDP       46.48       31.10       13       19         EDP       52.31       30.26       14       16         CS-11       43.63       32.47       15       15         CS-11       45.67       34.64       13       17		01.10.2024	132 KV SS	07 47		hg/w/s	1g/W3	M/Bri
132 KV SS         50.95         26.64         12         16           Rest Shelter         46.48         30.25         15         18           Rest Shelter         44.19         32.50         14         16           EDP         46.48         31.10         13         19           EDP         52.31         30.26         14         16           CS-11         43.63         32.47         15         15           CS-11         45.67         34.64         13         17	T	21 10 2011	\$ \cdot \cdo	£1.44	57.51	14	17	1770
Rest Shelter         46.48         30.25         15         16           Rest Shelter         44.19         32.50         14         16           EDP         46.48         31.10         13         19           EDP         52.31         30.26         14         16           CS-11         43.63         32.47         15         15           CS-11         45.67         34.64         13         17	7	4707 OTTC	132 KV 55	50.95	26.64	E e		2770
Rest Shelter         46.48         30.25         15         18           EDP         46.48         31.10         13         19           EDP         52.31         30.26         14         16           CS-11         43.63         32.47         15         15           CS-11         45.67         34.64         13         17		01.10 2024	Ract Chalton			71	16	1293
Rest Shelter         44.19         32.50         14         16           EDP         46.48         31.10         13         19           CS-11         52.31         30.26         14         16           CS-11         43.63         32.47         15         15           CS-11         45.67         34.64         13         17	1	- 101	incat delice	46.48	30.25	1,	0.4	
EDP         44.19         32.50         14         16           EDP         46.48         31.10         13         19           CS-11         43.63         32.47         15         16           CS-11         45.67         34.64         13         17		31.10.2024	Rest Shelter	0 0 0		CT	20	1339
EDP         46.48         31.10         13         1b           EDP         52.31         30.26         14         16           CS-11         43.63         32.47         15         15           CS-11         45.67         34.64         13         17	T			44.19	32.50	~	0.9	
EDP     52.31     30.26     14     16       CS-11     43.63     32.47     15     15       CS-11     45.67     34.64     13     17		01.10.2024	FDD	6 · · · · · · · · · · · · · · · · · · ·		7.4	OI I	1304
EDP         52.31         30.26         14         16           CS-11         43.63         32.47         15         15           CS-11         45.67         34.64         13         17	1			46.48	31.10	<del>/-</del>	,	
CS-11 30.26 14 16 CS-11 43.63 32.47 15 15 CS-11 45.67 34.64 13 17	_	31.10.2024	EDP	C		2	FT	1282
CS-11 43.63 32.47 15 15 15 CS-11 45.67 34.64 13 17	+			52.31	30.26	12	7.	0000
CS-11 45.67 34.64 13 17		01.10.2024	CS-11	27.00	1 0 0	1	10	1293
CS-11 45.67 34.64 13 17	1			43.03	32.47	15	7.5	1216
34.04		31.10.2024	CS-11	45.67	24.64			OTCT
				70.01	24.04	13	17	1000



## STACK MONITORING REPORT

to DIA Height Operating Temp. of V (in From G.L. conditions Gases 9c (in				Characte		4707-100 HILL	+707-	4000				
Screen House	0	Stack	Stack attached to	DIA (in	Height. From G.L.	Operating	Temp, of Gases <sup>0</sup> c	Velocity (m/sec)	Volume of Gas in Stack	PM (Mg/	Raw Mill/ Kiln SO2	Raw Mill/ Kiln NOx
Screen House   A80   31   45   43   43   43   44   43   44   44		A	Casher	850	31				(Nm3/ Min)	Nms)	(mg/Nm³)	(mB/Nm)
RM Sec. Chusher   1050   38   43   44   44   44   44   44   44		en.	Screen House	780	i		7.0	12.5	356.82	16.45		
Killin Feed Section   900   39   44     Row Mill and Killin Stack (ESP-1)   2100   65   All   137     New Cap (ESP-2)   1400   40   readings   171     Outen river Stack (Kiln outlet)   1650   30   were   171     Petro Lake Mill - II   800   31   under   65     Petro Lake Mill - II   980   40   romal   68     Curbert Jumpel   990   30   operating   55     Cement Mill - II   650   30   cenditions   72     Packing Plant (50 kg)   450   32   45     Packing Plant (50 kg)   450   32     Packing Plant (50 kg)   450     Packing Plant		U	RM Sec. Crusher	1000	2 2	- In	45	6.4	95.63	17.06		
Row Mill and Kilin Stack (ESP-1)   2100   65   All   137     New (SP_IESP-2)   1400   40   readings   137     Guest the Stack (Kilin outlet)   1650   30   were   171     Petrol ake Mill-1    800   31   taken   56     Petrol ake Mill-1    800   31   taken   56     Cement Aviil III   810   650   30   canditions   73     Cement Mill-1    650   30   canditions   73     Packing Plant (50 kg)   450   32   45     Packing Plant (50 kg)   800   32     Packing Plant (50 kg)   800   30     Packing Plant (50 kg)   800     Packing Plant (50 kg)   800   80     Packing Plant (50 kg)   80     Packing Plant (50 kg)   80     Packing Plant (50 kg)   80		۵	Klin Feed Section	200	0 0		14 (2)	7.89	426.60	16,25		
New Circlestropy   1400   40   readings   171		ш	Row And and Kiln Stack (FRP. 1)	2100	25		44	0 6	323.70	3,98		
Quericher Stack (kiln outlet)   1650   30   vere   171	-17	u.	New CSP (ESP-2)	1400	000	9.0	137	: 2	2279.23	19.40	-	
Petrol Oke Mill-1   800 31 taken   171	= 1	O	Quencher Stack (Kin ourlet)	1250	2 0	readings		Want und	er shutdown			
Petro : oke Mill - II		æ	Perrol oke Mil. I	200	2 2	Were		3,4	1153,45	21.53		
Petro: Junger   55   Junger   65		-	Petro : oke Mill - II	000	5	uexp.		Mant unde	ar shuldown		50 BC	u e
Curver tunnel         800         30         Deletating         55           Gement Mill III         650         30         conditions.         73           Cement Mill III         650         30         conditions.         73           Packing Plant (50 kg)         450         32         45           Packing Plant (Bag Cleaning Sys.)         800         32         45		-	Perro Loke Mill-III	000	5	Under	99	9.4	249.34	277	2007	0.000
Cement Mill off         650         30         conditions, 73           Packing Plant (50 kg)         450         32         45           Packing Plant (Bag Cleaning Sys.)         800         32         45		×	Curver connel	200	2 4	School Service	99	0	399.24	11.24		
Cemient Mill all   650   30   72   72   72   72   72   72   72   7	-	_,	Cement Mili 1 & II	250	3 8	Concenting	S)	9.5	261.54	16.94		
450 32 45 800 32 43	-	W	Cement Mill all	250	2 6		33	10.3	176.80	12.17		
800 32 44	-	z	Packing Plant (50 kg)	250	000		72	10.4	179.46	1.08		
2,77		0	Packing Hart (Bag Cleaning Suc.)	000	700		0.24 0.24	- '>	81.46	15.65		
200	-	n.	Boiler Stack (TPP)	1000	200		27.7	6.5	240.64	14.86		

pignt under shuidown	AMBIENT AIR QUALITY MONITORING REPORT

	Total Control		INDIALE: NOV-2024	74			
	DATE	LOCATION	PM10	PM25	SOs	ò	(
1			µg/M³	ug/M3	1101/843	200	3
_	01.11.2024	132 KV SS	20.02	200	E /AL	hg/rm°	hg/M3
L	20 11 202A	77 77 75	7	38.33	13	16	1282
-	47.11.7024	132 NV 33	46.56	37.86	7		3070
	01 11 2024	Bort Cholton		00:53	14	17	1304
1	L707:T+:T0	incorporation (allelie	41.49	31.04	13	100	
	29.11.2024	Rest Shelter	( ) ( ) L		74	ar	1327
1			79.05	32.33	5	10	0.00
	01.11.2024	EDP	03 //	6		07	1293
L			44.03	30.29	14	χ.	0201
	29.11.2024	EDP	43.86	0, 40			1770
	ACAC 11 10	***	000	31.10	15	17	1793
4	01.11.2024	C2-11	45.11	3101	* 7		
_	29 11 2024	CC 11		10:50	17	16	1304
4	-7.77.T.C.	C3-11	49.89	32.17	16	10	

## STACK MONITORING REPORT MONTH: DEC-2024

Mark	Stack affached to	DIA (F)	Height. From G.L.	Operating	Temp, of Gases <sup>9</sup> C	Velocity (m/sec)	Volume of Gas in Stack	PM (Mg/	Raw Mill/ Kiln SO2	Raw Mill/ Kiln NOx
٨	Crusher	ROD	(mirs.)				(Nm3/ Min)	Nm3)	(mg/Nm <sup>3)</sup>	(mg/Nm <sup>3)</sup>
œ	Screen House	COX	20.00	1-	4	12.3	351.26	50.5		
U	RM Sec. Crusher	1050	200		44	40	97.22	16.85		
Ω	Kiln Feed Section	2000	8 8		en.	C (	447.07	17,53		
ш	Raw Mill and Kim Stack (FSP.11)	2000	35		42	0.0	332,60	16.03	7	
щ	New ESP (ESP-2)	1,400	000	All	69	14.5	2220.04	18.82		
O	Ovencher Stack (kiln outlet)	3	000	readings		plant und	plant under mutdown		-	
×	Petro Coke Mill	000	2 2	were	165.	33.8	205.21	20.45		
==	Petro Coke Mill - 1	000	100	taken		plant und	plant under sturdown		3000	0 0000
-	Petro Coke Mill-III	000	20 5	unde	88	10.2	167.91	8965	)	000000
×	Clinker Tunnel	200	(4)	norman	9.0	0.0	294,74	200		
_	Cement Mill 4 & 1	337	200	Conditions	5,5	9,4	250.36	17.73		
٤	Cement Mill-III	440	7 8		7.0	C.O.	76.36	13.27		
z	Packing Plant (50 ca)	200	200		599	10.3	79.3	11.97		
0	Packing Plant (Bag Cleaning Suc.)	200	200		253	6	80,54	-C		
a_	Boiler Stock (TPP)	1 200	202		455	8.8	249,00	15 69		

PEPOPT	
Ω	۱
0	
i iii	
0	,
155	
2	1
2	,
-	
CE	
0	þ
1	
-	
1	
10	
W	
~	
-	
100	
Q,	
QUA	
0	
~	
0	
=	
P	
-	
5	
177	
쁘	
2	
5	
>	
AMBIENT	

44 444	The state of the s	1		
DATE LOCATION	PM10	PM <sub>2.5</sub>	\$02	NOX
01.12.2024 132 KV 66	nd/bri	hg/M³	нд/Мэ	nd/M³
	51.38	32.80	12	7.
30.12.2024 132 KV SS	40 00		77	/1
	45.03	35.46	13	0
U1.12.2024 Rest Shelter	47.72	22.20	7	
30 12 2024 Chaltan		26.20	1.1	16
	46.56	30.40	13	
01 12 2024 Enp			12	X
	47.23	30 93		į
30.12.2024 FDP			7 1	1/
1	46.09	31.21	13	CT
01.12.2024 CS-11	C C C		24	10
I	48.79	32.05	14	7,
30.12.2024   CS-11	47.59	27.40	· (1	O.T.

µg/М³ 1259

SR.

က





Name & Address of the Party

Sample Description :

VTL/AA/01-04

M/s JK White Cement Works (Unit of JK Cement Ltd.)Vill. & Po.- Gatan,

Dist.- Yagaur, Rajasthan

Amblent Air Quality Monitoring

Report No.

Format So.

VTL/A/2412300017-20/A 7.8 F 02

Party Reference No.: NIL

Report Date: Period of Analysis: 04/01/2025

30/12/2024 - 04/01/2025

Receipt Date

30/12/2024

General Information:-Sample collected by

Instrument Calibration Status

Meteorological condition during manitoring

Date of Sampling

Ambient Temperature (\*C)

Surrounding Activity

Scope of Monitoring

Sampling & Analysis Protocol

Sampling Duration Parameter Regulred VTL Team

Calibrated

Clear sky

25/12/2024 to 26/12/2024

: Min. 12°C, Mux. 22 °C

: Human , Vehicular & Plant Activities

: Regulatory Requirement

: IS-5182 & CPCB Guidelines

: 24 hrs.

: As Per Work Order

					& Lat. Long	* ! ! !!! · · · · · · · · · · · · · · · ·	T	
SE	Parameter	Protocol	132 KVSS	/Doolemite Ramp	EDP Club Building	CS-11	Unit	NAAQ
			73°44'46"E 26"38'50"N	73'44'32"E 26'38'43"N	73°44'33"E 26°38'30"N	73°44'46°E 26°38'28"N		2009
1.	Particulate Matter (PM10)	IS: 5102 (P-23), 2006, RA 2022	70.21	72.65	68.78	65.12	pig/ros	100
2.	Particulate Matter (PM2.5)	IS 5187 (P-24) -2019	36.52	38.11	34.55	32.52	pg/m²	50
3.	Sulphur Dioxide (SO2)	IS 5162 (P-2):Sec 1 2023	9:83	11.26	13 25	9.15	pg/m²	80
4.	Nitrugen Bioxide (NO2)	IS \$302 (P-6), 2006 RA	10.11	19.20	20.45	15.27	ME/mas	80
5.	(as CO)	IS:\$182 (P-10)+1999; RA2019 (NDIR)	0.65	0.72	0.68	0.62	mg/m³	4
6.	Benzene (as C6H5)	IS: 5182 (P-11)-2006, RA:2017	"BLQ("*LOQ1.0)	*BLQ[**[.DQ1,0]	*BLQ(**LOQ1.0)	*BLQ(**LDQ1.0)	pg/m <sup>3</sup>	5
7,	Ammonia (as NB3)	IS 5182 (P-25) -2018	*BLQ(**L0Q16.0)	*BlQ(**L0Q10.0)	*BLQ(**L0Q10.0)		10.00	
8.	Ouple (in 63)	IS:5182 (P-9):1974, IAA:2019	12.66	14.23	12.99	*BLQ(**LOQ10.0)	jig/m²	180
9.	Lead (as Pb)	IS 5182 (P-22):2004.	-Bró(*•rnó9'05)	*BLQ(**LOQ0.02)	*BLQ(**LOQ0.02)	*BLQ(**LOQ9.02)	na/m³	1
0	Arvenic (as Av)	VIL/STP/02/SGP/09	'BLQ(**) (20.5)	*BLQ(**LDQ0.5)	*BLQ(**LOQ0.5)			
1	Nickel (as N1)	15 5192 (P-26) 2020	*HLQ(**LUQE 0)	'BLQ(*'LOQ5.01		TILQ("LOQU.5)	ng/m <sub>1</sub>	6
2.	Henza (a) Pyrene	15:5182 (P-12):2004. RA:2019	*Bro(**rudu 3)	*BLQ(**L0Q0.2)	*BLQ(**LOQ5.0)	*BLQ(**LOQ0.2)	ng/m³	20





RK Yadav Lab Incharge Authorized Signatory

(Approved a comment) EPA 1986 Recognised ISO POOT and OHSAS 45001 Certified

Vibrant Techno Lab Pvt. Ltd.

9 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaiper Raj, 362020

<u>\_ 9929108691, 981020\$356, 8005707098, 9549956601</u>

Z J K W C Z

₩ 0141-2954638

🔁 bd@vibranttechnolab.com

@ www.vibranttechnolab.com





Sample Number:

Name & Address of the Party:

VTL/AN/01-04

M/s JK White Cement Works

(Unit of JK Cement Ltd.) Vill. & Po. Gotan,

**Ambient Noise Level Monitoring** 

Scope of Monitoring

Protocol Used:

Instrument Used:

Sample Description:

Dist. Nagaur, Rajasthan

Regulatory Requirment

15 9989

SLM

Report No:

Format No.:

VTL/N/2412300017-20/A

7.8 F 04

Party Reference No.: NIL

Report Date:

Receipt Date:

Sampling Duration

Sample Collected by

Instrument

Calibration Status

04/01/2025

30/12/2024 24 Hrs.

VTL Team

Calibrated

#### Ambient Noise Level Monitoring Results

General Information:

Meteorological condition during manifering

Date of Monitoring

Time of Monitoring

Ambient Temperature (°C)

Surrounding Activity

Parameter Required

: Clear sky

: 25/12/2024 to 26/12/2024

: 06:00 AM to 06:00AM

: Min. 11°C, Max. 22°C

: Human, Vehicular & Plant Activities

: As per Work Order

						Location	& Latlong		-	-
Sr.	Parameter	Protocol	132	KVSS	Rest Sh /Doulom		EDP Club	Building	cs	-11
				1/46 E 3 50 N	73*44* 26*38*	32°E	73°44 26°38	ALCOHOLD TO THE RESERVE OF THE PARTY OF THE		1'46"E 28"N
1.	Log	l5:9989-1981, RA	Day Time	Night Time	Day Time	Night Time	Day Time	Night Time	Day	Night Time
	dB(A)	2020	59.4	462	65.2	41.8	58.9	43.6	57.2	42.7

Category of Zones		Leg in dB (A)
	Day	Night
Industrial	75	70.
Commercial	65	55
lesidential	55	45
Silence Zone	50	10

Day Time is from 6.00 AM to 10.00 PM.

Night Time is reckoned between 10,00 PM to 6,00 AM.

Silence Zone is defined as an area up to 100 m around premises of Hospitals 1 ducational and Courts. Use of vehicle horn, Louispeake and hurstling of crackers is banned in these zones

Note: Mixed categories of areas be declated as one of the four above mentioned categories by the competent Authority and the corresponding standards shall apply

----End of the Report-----





**RK Yaday** Lab Incharge Authorized Signatory

Approved & Conflict. EPA 1986 Perognised 350 9001 and OHSAS.45001 Lethifled

Vibrant Techno Lab Pvt. Ltd.

9 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road (4 pur Raj 30207)

**□ 9929108691, 9810205356, 8005**707098, 9549956601



**©** 0141-2954638

To bow vibranttechnolabicom

www.vibranttechnolab.com





Sample Number: VTUS/03

Name & Address of the Party

MANS JK White Coment Works

(Unit of JK Cement Ltd i Vil. & Po. Getan Dist &

Nagaur Rajasthan

Report No.

VTUS/2412300003/A

Format No

7 8 F-03 Party Reference No ; NII.

Report Date

: 04/01/2025

Period of Analysis : 30/12/2024-04/01/2025

Receipt Date

: 30/12/7024

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Raw Mills Kiln ESP-1

Sample Collected By

: VTL Team

Date of Sampling

: 24/12/2024

Sampling duration (Minutes)

: 21min (12:00 to 12:21 hrs.)

Stack attached to Make of stack

: ESP : MS

Diameter of stack(m)

: 21 m

Height of stack(m)

: 65 m

instrument calibration status

: Calibrated Clear Sky

Meteorological Condition Ambient Temperature - Ta (°C)

: 17°C

Temperature of Stack Gases - Ts (°C)

Velocity of Stack Gases (m/sec.)

: 15 42

Flow rate of PM (LPM)

. 47

Flow rate of Gas (LPM)

: 20

Sampling condition

Protocol used

OK : IS 11255 & USEPA

Condinien

	Coordinares				
S.No.	Parameters	rameters Test Method		Units	Limits
1	Particulate Matter (PM)	IS (1255 (9-1) 1985 RA 2019	21.46	marter 13	30
?	Sulphur Dioxide (SO2 )	IS 1255(P-2) 1985 RA 2019	71.74	mg/Nm3	100
3	Carbon Monoxide (CG )	USEPA 10 1998	15 94	mg/Nm3	(62
4	Oxide of Nitrogen (NOx)	IS 11255 (P- 7) 2005; RA 2022	434,09	mg/Nm3	800

\*BLO= Below Limit Of Quantification, "1.00# Limit Of Quantification

\*\*\*End of Report\*\*\*







RK Yadav Labinonarge Authorized Significati



Page No. 1/1

Approved & Certified | EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

© SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020

\_ 9929108691 9810205356, 8005707098 9549956601



**©** 0141-2954638

a bd@vlbranttechnolab.com

. www.vibranttechnolab.com





Sample Number: VTL/S/04

Name & Address of the Party : M/S JK White Cement Works

(Unit of JK Cement Ltd.) Vill & Po. Gotan Dist.

Nagaur Rajasthan

VTL/S/2412300004/A Report No.

7 d F-93 Format No Party Reference No : NiL

Report Date : 04:01:25:25

Period of Analysis : 30/12/2024-04/01/2025

: 30/12/2024 Receipt Date

Sample Description : Stack Emission Monitoring

General information:-

Clinker Quenche (Steam Exhaust ESP) Sampling Location

: VTL Team Sample Collected By : 24/12/2024 Date of Sampling

Sampling duration (Minutes) : 36 min. (12 50 to 13.26 hrs.)

Stack attached to : ESP Make of stack : MS 1.60 m Diameter of stack(m) Height of stack(m) : 30 m instrument calibration status : Calibrated Meteorological Condition Clear Sky Ambient Temperature - Ta (°C) : 1810 Temperature of Stack Gases - Ts (\*C) Velocity of Stack Gases (m/sec.) 10.57 Flow rate of PM (LPM) 28

Flow rate of Gas (LPM) Sampling condition : OK

: IS 11255 & USEPA Protocol used

Coordinates

S.No.: Parameters	Test Method	Results	Units	Limits
Particulate Matter (PM)	IS 11255 (P-1) 1985 RA 2019	17.50	mg/Nm3	30

"BLO" Below Limit Of Quantification "TLOQ" Limit Of Quantification

\*\*\*End of Report\*\*\*







PK Yaday Lab Incharge Authorized Signatory



Approvid a Cartified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

#### Vibrant Techno Lab Pvt. Ltd.

- 9 SC-40 3rd Floor Marayan Vinar S. Africar Road, Jacour Paj. 302020
- \_ 9929108691, 9810205356\_8005707098, 9549956601

T 0141-2954638

© nd ≥ vibranttechnolab com







Sample Number: VTL/S/05

Name & Address of the Party

! A#S JK White Cement Works

Unit of JK Camer: Ltd i Vil. & Po. Gutar. Tist

Nugaur Rajasman

Report No.

- VTL/S/2412300005/A

Formut No Party Reference No · NII

F8 F 65

04/01-025

Report Date Period of Analysis

: 30/12/2014-04/01/2025

Receipt Date

: 30/12/2024

Units

mg/Nm3

Results

17.73

Sample Description

Stack Emission Monitoring

General Information:-

Sampling Location

Pet Coke/ Coal (ViiII-02

Sample Collected By

: VTL Team

Date of Sampling

25/12/2024

Sampling duration (Minutes)

27 min (09:30 to 09:57 hrs )

Stack attached to

secot pag

Make of stack

MS

Diameter of stack(m)

0.50 m

39 m

Height of stack(m) Instrument calibration status

u Calibrated -

Meteorological Condition

Ambient Temperature - Ta (\*C )

Parameters

3 Clear Sky

Temperature of Stack Gases - Ts (\*C)

# 18°C 69

Velocity of Stack Gases (m/sec.)

9 92

Flow rate of PM (LPM)

37

Flow rate of Gas (LPM)

Sampling condition

Ois

Protocol used

15 11255 & USFPA

**Test Method** 

Coordinates

S.No.

IS: 11255 (P-1): 1985, RA 2019 Particulate Malter (PM)

\*BLQ= Below Limit Of Quantification, "LOQ= Limit Of Quantification \*\*\*Find of Report\*\*\*







AK Yaday Lab Incharge Authorized Signatory



Limits

Paga No. 1/1

EPA 1986 Recognized, ISO:9001 and OHSAS 43001 Certified

Vibrant Techno Lab Pvt. Ltd.

9 SC 40 3rd Floor, Narayan Vésar S. Almer Royal, Japan, Ray 30 Jr.

7, 9929108691, 9810205356, 8003707098, 9549956601

% 0141-2954638

The bury branttechnolab.com

& www.vibranttechnolab.com







Sample Number: VTUS/04

Name & Address of the Party

M 3 JK White Cement Works.

Punit of JK Cement Etd | Vil. & PoliGaton Dist =

Nagaur, Rajosthan

Report No

OVILS 2457703008-4

Format No

DEPTS:

Party Reference No : Nil

Report Date : 04/01/2025

Period of Analysis : 30/12/2024-04/01/2025

Receipt Date

30/12/2024

Bample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Pet Coke/ Coal MH-00

Sample Collected By

: VIL Team

Date of Sampling

Sampling duration (Minutes)

25113 2024

Stack attached to

31 mm 10 10 to 10 41 irs

: Bag House

Make of stack

: MS

Diameter of stack(m)

: 0.98 m

Height of stack(m)

: 41 m

instrument calibration status

: Calibrated

Meteorological Condition Ambient Temperature - Ta (°C ) : Glear Sky

Temperature of Stack Gases - Ts (°C)

Volocity of Stack Gases (misec.)

: 57

Flow rate of PM (LPM)

3.61

Flow rate of Gas (LPM)

Sampling condition

: OK : IS 11255 & USEPA

Protocal used

	COOLDINATES				
S.No.	Parameters	Test Method	Results	Units	Limits
1	Particulate Malter (PM)	(8. 11266 (P-1), 1985 RA-2019	5.78	mg/N=13	30

<sup>&</sup>quot;BLC = Below Limit Of Quantification, "LCC = Limit Of Quantification

mend of Reporting











(Approved & Content of the EPA 1986 Recognised ISO 9001 and OHSAS 45001 Certified

Vibrant Techno Lab Pvt. Ltd.

9 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020

Q 9929108691, 9810205356, 8005707098, 9549956601

**2 0141-2954638** 

💯 tidrevibranttechnolab.com

www.vibranttechnolab.com









Sample Number: VTL/S/07

Name & Address of the Party

; M/S JK White Cement Works

(Unit of JK Cement Ltd.) Vill. & Po. Gotan. Dist. -

Nagaur, Rajasthan

Report No.

VTL/S/7412300007/A

Format No

7 8 F-03 Party Reference No : NIL

Report Date

: 04/01/2025

Period of Analysis

; 30/12/2024-04/01/2025

Receipt Date

: 30/12/2024

Unite

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

Cameru Mill -1 & 2 # V7L Team

Sample Collected By Date of Sampling

25/12/2024

Sampling duration (Minutes)

Stack attached to

42 min (10 58 to 11 40 hrs.)

Bag House

Make of stack

MS

Diameter of stack(m)

0.93 m

5 30 m

Height of stack(m)

E Calibrated

instrument calibration status Meteorological Condition

Clear Sky

Ambient Temperature - Ta ('C)

18°C

Temperature of Stack Gases - Ts ('C)

55

Velocity of Stack Gases (m/sec.) Flow rate of PM (LPM)

Parameters

THE DR BOOM LITTLE OF QUANTIFICATION IN THE PER

6 63

Flow rate of Gas (LPM)

24

Sampling condition

: OK

Test Method

Protocol used Coordinates

S.No.

: IS 11255 & USEPA

IS 11255 (PAT) 1655 HA : Portugilate Maner (PM).

""End of Respon""







Authorized Signatory

Results



Limits

20

Page No. 18

Approved & Certified | EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

9 SC-40, 3rd Floor, Narayan Vibar 5, Ajmer Road, Jainur Ray 302026.

<u> 7929108671 9810205356 8005707098 9549956601</u>

**2** 0141-2954638

Dd@vibranttechnolab.com

www.vibranttechnolab.com









Sample Number: VTUS/08

Name & Address of the Party : M/S JK White Coment Works

(Unit of JK Cement Etd.) Vill & PoliGulan Dist.

Negaur Rajasthan

Report No.

: VTU/S/2412300008/A

Format No.

- 7 8 F-03

Party Reference No

: 04/01/2025

Report Date

: 30/12/2024-04/01/2025 Period of Analysis

Receipt Date

: 30/12/2024

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Cement Mrl -3

Sample Collected By

: VTL Team

Date of Sampling

: 25/12/2024

Sampling duration (Minutes)

: 28 mm (12/00 to 12/28 hrs.)

Stack attached to

: Gag House

Make of stack

: MS

Diameter of stack(m)

: 0 69 m

Height of stack(m)

; 30 m

Instrument calibration status

Meteorological Condition

: Calibrated : Glear Sky

Ambient Temperature - Ta ("C)

Temperature of Stack Gases - Ts (°C)

: 53

Velocity of Stack Gases (m/sec.)

5 9.41

Flow rate of PM (LPM)

36

Flow rate of Gas (LPM)

Sampling condition

OK

Protocol used

: IS 11255 & USEPA

	Coordinales						5 from 14 m
S.No.	Parameters	Test N	lethod	1	Results	Units	Limits
	Particulate Marter (PM)	 \$ 11285 (P.1)	1955 RA2019		20.10	mg/Nin3	30

\*BLQ= Below Limit Of Quantification \*11/1/Q=1 and Of Quantification

""End of Recort""







THE PERSON Authorized Signatury



Approved & Curtified ERA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

9 SC-40, 3rd Floor, Narayan Vilhar S. Aymer Road, Jaiour Rail 202023.

T 9929108691 9810205356 8005707098 9549958657

© 0141-2954638

티오 od v vibranttechnolab com

www.ibranttechnolab.com







Sample Number: VTUS/017

Name & Address of the Party

\* MrS JK White Cement Works

(Unit of alk Carrent Ltd., Vil. & Po. Glina: Dist.

Nagaur Rajasthan

Report No.

VTL-S/2412300017/A

Format No.

T 8 F 03

Party Reference No \_ NiL

Report Date 5 54/01/2025

Receipt Date

Period of Analysis 1 30/12/2024-04/01/2025 1 30/12/2024

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

Sample Collected By

Date of Sampling

Sampling duration (Minutes)

Stack attached to

Make of stack

Diameter of stack(m)

Height of stack(m)

Instrument calibration status

Meteorological Condition Ambient Temperature - Ta (°C)

Temperature of Stack Gases - Ts (\*C) Velocity of Stack Gases (m/sec.)

Flow rate of PM (LPM)

Flow rate of Gas (LPM)

Sampling condition

Protocol used

Coordinates

: DG Set 250 KVA

: VTL Team

: 27/12/2024

34 min (12 10 to 12 44 mis.)

1 Acoustic Encloser

: MS

: 0.90 m : 30 m

: Calibrated

: Clear Sky

: 19°C

: 120 9.23

3 29

- OK : 15 11255 & USERA

No.	Parameters	Test Method	Results	Units	Limits
	Cerbon Monoxidé (CO )	USEPA 10: 1996	1 37	gre/kw-hr	35
	Particulate Matrer (PM)	IS 11255 (P-1) 1985, HA 2019	0 014	grifkve-hr	0.02
	Oxide of Nitrogen (NOX))	IS 11255 (P-7) 2035, RA 2022	0.20	gm/kw-hr	0.40
	Total Hydrocarbon (HC)	USEPA 18, 1996	0 10	gm/kw-hr	0 19
	Sulphur Dioxide (SO2)	IS: 11255(P-2): 1985 RA 2019	2.74	gnvkw-hr	Not Specified

\*\*\*End of Report\*\*\*





RK Yaday Lab Incharge Authorized Signatory



Page No. 1/1

(Approved & Carolleon) EPA 1986 Recognised, ISO:9001 and OHSA5:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

Q SC 40, 3rd Facer Marayan Vibar S. 7, mer Robb., biological and To

[ 9929108691, 9810205356 800070 1098 954604; J

TO 1041-2954638

www.vibranttechnolab.com





Sample Number: VTL/WW/02

M/S JK White Coment Works

(Unit of JK Gement Ltd ) Vill & Po Gotan Dist.

Nagaur, Rajasthan

Name & Address of the Party

Sample Description

Sampling Location Sample Collected By

Preservation

: Waste Water : STP Outlet (STP Treated Water) 500 KLD STP

: VTL-Team : Suitable Preservation ULR No.

: TC:129725000000015F

Report No Format No : V\*L/WW-24125000002/A

, 2 a F-01 Party Reference No : NIL

Report Date

; 04/91/2025

Period of Analysis

: 30/12/2024-04/01/2025

Receipt Date

: 35/12/2024

Sampling Date

: 27/12/2024

Sampling Type Sample Quantity

Grap 2214

_	od of sampling : IS:3025		Coordina	Les : 7	3 748795 N & 26.638279E
S.No	Test Parameters	Test Method	Result	Unit	Limits
ř.	pH	(S 3025 (P-11; 2022	7 46		5 5 to 9 0
2	Total Suspended Solids (TSS)	IS 3925 (P-17) 2022	150	mg/l	20
3	Temperature	is 3025 (P-9): 2023	1,83	*C	Shall not exceed 5°C above the receiving water temperature
4	Oil & Grease	IS:3025 (P-39): 2021	"BLO(""LOQ 4 0)	mgil	10
5)	Arnmonical Nitrogen (as NH3-N)	IS 3025 ( P-34) Sec 1 2023 (Chause 5.3)	4 12	i ngil	\$ \$
5	Total Kyekiahi Nitrogen (as NH3)	(S 3025 ( P-34; Sec 1 2023 (Clause 8.0)	5 65		10
	Biochemical Oxygen Demand (BOO) (3 days & 27°C)	IS: 3025 (P-44): 2023	7.2	mg/l	10
	Chemical oxygen Demand (COD)	IS: 3025 (P-58) : 2023	28 6	rrig/l.	50
	Chloride (as ICI)	15: 3025 (P-32) 1968, RA 2019	891	mgrl	
Ō	Sulphide (as S)	IS 3025 (P 29) Z022 (Clause 6.0)	0.49	mgs	2
1	Residual Free Chlorine	IS: 3025 (P-26) 2021 (Clause 5 0)	0.66	mg/	10
2	Faccal collform	APHA 24th Edition 9221 C 2023	41	MPN/100 ml	<100

\*\*\*End of Report\*\*\*







RK Yadav Lab Inches (g Authorized Signatury



EPA 1986 Recognised, ISO 9001 and OHSAS:45001 Certified

Vibrant Techno Lab Pvt. Ltd.

9 SC 40, 3rd Floor Narayan Vihar S, Almer Road Jainus Rap. 302020


**79929108691, 9810205356, 8005707098** 9549956601



2 0141 2954638

👺 indigivitzrantiechnolaticom

ar www.vibranttechnolab.com





Date: 29.03.2025

Time: 11-00 am

Day/ Night:


N4-63/67

E7-58/60

E4-67 )70

s6- 64/18

N8- PX P8



53-59/62

W3- 60/63

W7- 63 66

CRUSHER

: OPERATING/ NOT OPERATING

RAW MILL

OPERATING NOT OPERATING

KILN

: OPERATING/ NOT OPERATING

CEMENT MILL

: OPERATING/ NOT OPERATING.

PACKING PLANT

: OPERATING NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

COMPRESSOR

OPERATING/ NOT OPERATING

PET- COKE MILL

: OPERATING NOT OPERATING

ly 63.05

FELDSPAR MILL

: OPERATING NOT OPERATING

Pre-Mix Dry Mortar (Putty): OPERATING/ NOT OPERATING

REMARKS IF ANY:

MEASURED BY:

W

Date: 29.03.2025

Time:

Day/ Night:


50/54

E7- 52/57

E4- 61/64

56- 60 63

N8. 57 60



53-

W3- 58/61

W7- 56/59

CRUSHER

: OPERATING/ NOT OPERATING

RAW MILL

OPERATING/ NOT OPERATING

KILN

: OPERATING/ NOT OPERATING

CEMENT MILL

: OPERATING/ NOT OPERATING.

PACKING PLANT

: OPERATING/ NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

: OPERATING/ NOT OPERATING

COMPRESSOR

: OPERATING/ NOT OPERATING

PET- COKE MILL

: OPERATING/ NOT OPERATING

58.84

FELDSPAR MILL

Pre-Mix Dry Mortar (Putty): OPERATING/ NOT OPERATING

REMARKS IF ANY:



Date: 22.02-2025

Time: 10.45 Pm Day/ Night:


N4. 65/68

E7-55 59

E4- 64/69

56- 66 70

N8- 13/66



53-58 61

W3- 61/64

W7- 62/65

CRUSHER

OPERATING/ NOT OPERATING

RAW MILL

OPERATING NOT OPERATING

KILN

: OPERATING/ NOT OPERATING

CEMENT MILL

OPERATING NOT OPERATING.

PACKING PLANT

: OPERATING/ NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

: OPERATING/ NOT OPERATING

COMPRESSOR PET- COKE MILL

: OPERATING/ NOT OPERATING

les 63.41

FELDSPAR MILL

. OPERATING/ NOT OPERATING

Pre-Mix Dry Mortar (Putty): OPERATING/ NOT OPERATING

REMARKS IF ANY:



Date: 22.02.2025

Time: 9.00 pm

Day/ Night:

E4-60/62 E7- 53/51 N4.57/60 CRUSHER RMS YARD D. G. CM N8-57/59 FACTORY GATE

56-57/60

53.55/60

59/62

W7- 58/60

CRUSHER

: OPERATING/ NOT OPERATING

RAW MILL

: OPERATING/ NOT OPERATING

KILN

: OPERATING/ NOT OPERATING

CEMENT MILL

: OPERATING/ NOT OPERATING.

PACKING PLANT

: OPERATING/ NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

COMPRESSOR

: OPERATING/ NOT OPERATING

PET- COKE MILL

: OPERATING/ NOT OPERATING

FELDSPAR MILL

: OPERATING/ NOT OPERATING

REMARKS IF ANY:

Pre-Mix Dry Mortar (Putty): OPERATING NOT OPERATING



Date: 25.01.2025

Time: 10.30 AM

Day/ Night:

NA. 69 64.

E7- 6765

E4- 62 68

CRUSHER RMS YARD D. G. CM FACTORY GATE

N8- 63/68

60/63

56-60/63

W3. 64/66

W7- 62/67

CRUSHER

OPERATING/ NOT OPERATING

RAW MILL

: OPERATING/ NOT OPERATING

KILN

: OPERATING/ NOT OPERATING

CEMENT MILL

: OPERATING/ NOT OPERATING.

PACKING PLANT

OPERATING NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

COMPRESSOR

OPERATING/ NOT OPERATING

PET- COKE MILL

: OPERATING/ NOT OPERATING

FELDSPAR MILL

: OPERATING/ NOT OPERATING

Pre-Mix Dry Mortar (Putty): OPERATING/ NOT OPERATING

REMARKS IF ANY:

MEASURED BY:



Leg = 61-37



Date: 25.07.2025

Time: 8.USCM

Day/ Night:

N4- 62/65

E7- 57/60.

E4-62/67

CRUSHER RMS YARD D. G. CM FACTORY GATE P. P.

53- 59/59

56- 60/64

N8- 61/64

W3. Gol 62

W7- 58 60

CRUSHER

: OPERATING NOT OPERATING

RAW MILL

OPERATING NOT OPERATING

KILN

: OPERATING/ NOT OPERATING

CEMENT MILL

: OPERATING NOT OPERATING.

PACKING PLANT

: OPERATING/ NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

COMPRESSOR

OPERATING NOT OPERATING

PET- COKE MILL

: OPERATING/ NOT OPERATING

FELDSPAR MILL

: OPERATING/ NOT OPERATING

Pre-Mix Dry Mortar (Putty): OPERATING/ NOT OPERATING

REMARKS IF ANY:

MEASURED BY:



Leg- 60.53

Date: 28 · 12 · 2024

Time:

10:00 am

Day/ Night:

E4- 58 62 E7- 58 60 N4-55/59 56- 59 61 CRUSHER RMS YARD D. G. CM N8- PYEZ 53- 62 65 FACTORY GATE P. P. W3- 63/65 W7- 61/64 OPERATING/ NOT OPERATING CRUSHER : OPERATING/ NOT OPERATING RAW MILL : OPERATING NOT OPERATING KILN : OPERATING NOT OPERATING CEMENT MILL : OPERATING/ NOT OPERATING PACKING PLANT OPERATING NOT OPERATING D. G. : OPERATING/ NOT OPERATING COMPRESSOR : OPERATING/ NOT OPERATING PET- COKE MILL 60.37 LOOM FELDSPAR MILL-2 OPERATING NOT OPERATING Pre-Mix Dry Mortar (Putty): OPERATING/ NOT OPERATING REMARKS IF ANY:

She-


Date: 28:12.2024 Time: 9.15 Pm

Day/ Night:

N4. 53/56

E7- 57/59

E4-55 58



56- 56 39

53-58/61

N8- 12/64

W3-60 63

WJ. 66/62

Leg. 59.86

CRUSHER

: OPERATING/ NOT OPERATING

RAW MILL

: OPERATING/ NOT OPERATING

KILN

: OPERATING/ NOT OPERATING

CEMENT MILL

: OPERATING/ NOT OPERATING.

PACKING PLANT

OPERATING NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

: OPERATING/ NOT OPERATING

COMPRESSOR

PET-COKE MILL

: OPERATING/ NOT OPERATING

EELDSPAR MILL - 2

: OPERATING/ NOT OPERATING

Pre-Mix Dry Mortar (Putty) : OPERATING/ NOT OPERATING

REMARKS IF ANY:

Date: 30.11.2024


Time: 10: 15 am

Day/ Night:

N4. 63/45

E7- 65/67

E4- 65/70



64/69

53- 63/65

N8- PE/ Pd

W3- 63/66

W7-64/67

CRUSHER

OPERATING NOT OPERATING

RAW MILL

: OPERATING/ NOT OPERATING

KILN

: OPERATING/ NOT OPERATING

CEMENT MILL

: OPERATING/ NOT OPERATING.

PACKING PLANT

: OPERATING/ NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

COMPRESSOR

: OPERATING/ NOT OPERATING

PET- COKE MILL

: OPERATING/ NOT OPERATING

: OPERATING/ NOT OPERATING

LOSPAR MILL-2

Pre-Mix Dry Mortar (Putty): OPERATING/ NOT OPERATING

REMARKS IF ANY:

Date: 30.11.2024

Time: 6.45 pm

Day/ Night:

NA. 62/65

E7- 60/62

E4- 63 67

56- 62/66

N8- 64/67

CRUSHER RMS YARD D. G. CM FACTORY GATE

53- 61/65

W3- 63/65

W7-62/64

CRUSHER

OPERATING NOT OPERATING

RAW MILL

: OPERATING/ NOT OPERATING

KILN

: OPERATING/ NOT OPERATING

CEMENT MILL

: OPERATING NOT OPERATING.

PACKING PLANT

: OPERATING NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

: OPERATING/ NOT OPERATING

PET- COKE MILL

COMPRESSOR

: OPERATING! NOT OPERATING

OPERATING NOT OPERATING

leg. 61.25

ELDSPAR MILL - 2

Pre-Mix Dry Mortar (Putty) : OPERATING/ NOT OPERATING

REMARKS IF ANY:



Date: 26/10/24

Time: 11:00 Aar

Day/ Night:

E7-60-62 E4- 61/62 59/6/ NA- 59-60 CRUSHER RMS YARD D, G, CM N8-62/64 FACTORY GATE 60/62

W3-63/64

64/RF

: OPERATING/ NOT OPERATING CRUSHER

OPERATING NOT OPERATING RAW MILL

: OPERATING/ NOT OPERATING KILN

: OPERATING NOT OPERATING. CEMENT MILL

OPERATING NOT OPERATING PACKING PLANT

: OPERATING/ NOT OPERATING D. G.

: OPERATING NOT OPERATING COMPRESSOR

: OPERATING/ NOT OPERATING PET- COKE MILL

: OPERATING/ NOT OPERATING

Pre-Mix Dry Mortar (Putty) ; OPERATING/ NOT OPERATING

eq - 59.88.

REMARKS IF ANY:

Date: 26 10 24

Time: 10130PM

Day/ Night:

E4- 60/62 E7-60/61 59/60 N4- 62/60 CRUSHER RMS YARD D. G. CM N8-61/62 FACTORY GATE 60/62 6,1,62 : OPERATING/ NOT OPERATING CRUSHER OPERATING NOT OPERATING RAW MILL

KILN

: OPERATING NOT OPERATING

CEMENT MILL

: OPERATING NOT OPERATING.

PACKING PLANT

: OPERATING NOT OPERATING

D. G.

: OPERATING/ NOT OPERATING

COMPRESSOR

: OPERATING/ NOT OPERATING

PET- COKE MILL

: OPERATING/ NOT OPERATING


LO REPOSPAR MILL - 2

: OPERATING/ NOT OPERATING

Pre-Mix Dry Mortar (Putty); OPERATING/ NOT OPERATING

REMARKS IF ANY:

Leef , 59.14



		Name and Parks and Parks			T WORKS, GOTA		HEIGHT	NEAR VISION	NEAR VISION	SPIROMETRY	WEIGHT
Plant/Site	Employee Name	AUDIOMETR Y	Blood Group	DISTANT VISION LEFT	DISTANT VISION RIGHT	ECG REPORT	HEIGHT	LEFT	RIGHT		
Gotan-White	ABDUL KHAN	NORMAL	A+VE	6/6 GLAS	6/6 GLAS		165	N-6 GLS	N-6 GLS	NORMAL	79
Gotan-White	ABHISHEK JOSHI	MLBE	O+VE	6/6 C GLASS	6/6 C GLASS	NORMAL		N-6 C GLASS	N-6 C GLASS		82
Gotan-White	AJAY KUMAR	NORMAL	B+VE	6/6 C GLS	6/6 C GLS	And in contrast of the party of	181	N-6	N-6	NORMAL	78
Gotan-White	AJIT MISHRA	NORMAL	O+VE	6/6	6/6	NORMAL	182	N-6	N-6	NORMAL	105
Gotan-White	AKASH VERMA	NORMAL	B+VE	6/6	6/6	NORMAL	166	N-6	N-6	NORMAL	57
Gotan-White	AMAN JOSHI	NORMAL	B+VE	6/6	6/6	NORMAL	176	N/6	N/6	NORMAL	76
Gotan-White	AMIT KUMAR SHARMA	NORMAL	A+VE	6/6	6/6	NORMAL	168	N-6	N-6	NORMAL	75.9
Gotan-White	ANIL KUMAR	NORMAL	B+VE	6/6 C GLS	6/6 C GLS	NORMAL	174	N-6 C GLS	N-6 C GLS	MILD REST	81
Gotan-White	ANSHU SHARMA		O+VE	6/6	6/6	NORMAL	166	N-6	N-6	NORMAL	74
	APEKSHA	NORMAL	A+VE	6/6 C GLS	6/6 C GLS	NORMAL	162	N-6	N-6	NORMAL	61
Gotan-White	ARADHYA	NORMAL	O+VE	6/6 GLS	6/6 GLS		166	N-6 GLS	N-6 GLS	NORMAL	76
Gotan-White	ARJUN KUMAR	NORMAL	B+VE	6/6 C GLASS	6/6 C GLASS	NORMAL		N-6 C GLS	N-6 C GLS	NORMAL	85.8
Gotan-White	ARVIND	THE SEASON SOLDEN	A+VE	6/6	6/6	NORMAL		N-6	N-6	NORMAL	75
Gotan-White	ASHUTOSH	NORMAL	B+VE	6/6 C GLASS	6/6 C GLASS	NORMAL		N-6 C GLASS	N-6 C GLASS		95
Gotan-White		NORMAL	Charters College		6/6	NORMAL	169	N-6	N-6	MILD REST	
Gotan-White	ASHUTOSH	NORMAL	AB+VE	6/6			177	N-6 CGLASS	N-6 CGLASS		
Gotan-White	ASLAM KHAN	NORMAL	AB+VE	6/6 CGLASS	6/6 CGLASS	17.00.11111111111	_		N-6 C GLASS		86
Gotan-White	BABU KHAN	NORMAL	O+VE	6/6 C GLASS	6/6 C GLASS	NORMAL		N-6 C GLASS	N-6 C GLASS	MILD REST	
Gotan-White	BABU LAL	NORMAL	A+VE	6/9	6/9		166	N-6			
Gotan-White	BABU LAL	NORMAL	O+VE	6/6GLS	6/6 GLS	NORMAL	167	N-8 GLS	N-8 GLS	MILD REST	
Gotan-White	BHAGWATI	ML BE	B+VE	6/6 GLS	6/6 GLS	NORMAL	168	N-6	N-6	NORMAL	61.8
Gotan-White	BHANWAR	NORMAL	O+VE	6/6	6/6	NORMAL	169	N-6 CGLASS	N-6 CGLASS		82
Gotan-White	BHARAT	NORMAL	B+VE	6/6 C GLS	6/6 C GLS	NORMAL	166	N-6 C GLS	N-6 C GLS	NORMAL	67.6
Gotan-White	BIRA SINGH	NORMAL	B+VE	6/9	6/9	NORMAL	169.5	N-6	N-6	NORMAL	84
Gotan-White	BIRMA RAM	NORMAL	B+VE	6/6	6/6	NORMAL	157	N-6	N-6	NORMAL	50
	BRIJ GOPAL	NORMAL	A+VE	6/6	6/6	NORMAL	179	N-6	N-6	MILD REST	128
Gotan-White	BRIJESH		O+VE	6/6	6/6	NORMAL	172	N-6	N-6	NORMAL	84
Gotan-White	CHAILA RAM	NORMAL		6/9	6/9	NORMAL	160	N-8 C GLS	N-8 C GLS	MILD REST	
Gotan-White		NORMAL	AB+VE			NORMAL	165	N-6	N-6	MILD REST	
Gotan-White	DALPAT RAM	NORMAL	O+VE	6/6	6/6			N-6 GLS	N-6 GLS	MILD REST	
Gotan-White	DANA RAM	NORMAL	B+VE	6/6 CGLASS	6/6 CGLASS	NORMAL	167			NORMAL	91.8
Gotan-White	DEEPAK	NORMAL	B+VE	6/6 C GLS	6/6 C GLS	NORMAL	178	N-6 C GLS	N-6 C GLS		
Gotan-White	DEEPAK	NORMAL	B+VE	6/6	6/6	NORMAL	172.5	N-6	N-6	NORMAL	51
Gotan-White	DHANRAJ	NORMAL	O+VE	6/6	6/6	NORMAL	174	N-6	N-6	MILD REST	78
Gotan-White	DILIP KUMAR	NORMAL	B+VE	6/9 C GLASS	6/6 C GLASS	NORMAL	162	N-6	N-6	NORMAL	71.4
Gotan-White	DILIP SHARMA	NORMAL	AB+VE	6/6 C GLASS	6/6 C GLS	NORMAL	158	N-6 C GLS	N-6 C GLS	NORMAL	66
Gotan-White	FATEH SINGH	NORMAL	O+VE	6/6	6/6	NORMAL	177	N-6	N-6	MILD REST	73
Gotan-White	GAJENDRA	NORMAL	B+VE	6/6	6/6	NORMAL	166	N-6	N-6	NORMAL	63
	GAJENDRA	NORMAL	O+VE	6/6	6/6	NORMAL		N-6	N-6	MILD REST	81.5
Gotan-White	GIRJESH KUMAR		O-VE	6/6	6/6	NORMAL	175	N-6	N-6	NORMAL	86
Gotan-White					6/9 GLS	NORMAL		N-6 GLS	N-6 GLS	NORMAL	74.8
Gotan-White	GODHA RAM	MLBE	A-VF	6/9 GLS	101.0. 0.00		-	N-6	N-6	NORMAL	74
Gotan-White	GYANCHAND	NORMAL	A+VE	6/6	6/6	NORMAL	161		N-6	NORMAL	104
Gotan-White	HARENDRA	-	B+VE	6/6	6/6	NORMAL	165	N-6		MILD REST	
Gotan-White	HEER SINGH	MLBE	A+VE	6/6 C GLS	6/6 C GLS	NORMAL		N-6 C GLS	N-6 C GLS		
Gotan-White	IMRAN NAZIR	NORMAL	O + VE	6/6	6/6	NORMAL		N-6	N-6	NORMAL	67
Gotan-White	IPPILI	NORMAL	o+ve	6/6 C GLS	6/6 c gls	NORMAL		N-6 c gls	N-6 c gls	NORMAL	85
Gotan-White	JAGDISH CHAND	NORMAL	AB+VE	6/6 C GLASS	6/6 C GLASS	NORMAL		N-6 C GLS	N-6 C GLS	NORMAL	76
Gotan-White	JAGDISH		Q+VE	6/6	6/6	NORMAL	175	N-6	N-6	NORMAL	79
Gotan-White	JAGDISH NAI		B+VE	6/6 GLS	6/6 GLS	NORMAL		N-6 GLS	N-6 GLS	NORMAL	74
Gotan-White	JAI PRAKASH	ML RE	A+VE	6/6	6/6	NORMAL	166	N-6	N-6	NORMAL	73
Gotan-White	JAY PRAKASH	NORMAL	A+VE	6/6	6/6	NORMAL		N-6	N-6	MILD REST	
	JITENDRA	NORMAL	O+VE	6/6	6/6	NORMAL		N-6	N-6	MILD REST	64
Gotan-White	KAILASH			6/6	6/6	NORMAL		N-6	N-6	NORMAL	101.8
Gotan-White			A+VE			NORMAL		N-6	N-6	NORMAL	46
Gotan-White	KAILASH NATH	1	B+VE	6/6	6/6				N-6	NORMAL	60
Gotan-White	KALYAN RAM	NORMAL	O+VE	6/6	6/6	NORMAL		N-6			71.5
Gotan-White	KAMAL KISHOR	NORMAL	A+VE	6/6 GLS	6/6 GLS	NORMAL		N-6 GLS	N-6GLS	NORMAL	
Gotan-White	KAMAL	NORMAL	A-VE	6/6	6/6	NORMAL	The second second	N-6	N-6	MILD REST	
Gotan-White	KANHIYA NATH	NORMAL	B+VE	6/6	6/6	NORMAL		N-6	N-6	NORMAL	96
Gotan-White	KESHA RAM	ML BE	O+VE	6/9	6/9	NORMAL	172	N-8 C GLS	N-8 C GLS	MILD REST	
Gotan-White	KHALIL	NORMAL	AB+VE	6/9	6/9	NORMAL	170	N-8 C GLS	N-8 C GLS	NORMAL	63
Gotan-White	Kherajram	NORMAL	O+VE	6/6 GLS	6/6 GLS	NORMAL		N-6 GLS	N-6 GLS	NORMAL	89
Gotan-White	KHOWENDRA DAYARAM	NORMAL	B+VE	6/6 GLS	6/6 GLS	NORMAL		N-6GLS	N-6 GLS	NORMAL	59
Coton Milit	KISHAN LAL	ML BE	O+VE	6/6	6/6	NORMAL	174	N-6	N-6	NORMAL	63
Gotan-White		-			6/6	NORMAL	173	N-6	N-6	NORMAL	87
Gotan-White	KRISHNA KANT	NORMAL	O+VE	6/6			THE PERSON NAMED IN	N-6 GLS	N-6 GLS	NORMAL	67
Gotan-White	Kriti Sheen	NORMAL	AB+VE	6/6 GLS	6/6 GLS	NORMAL				NORMAL	71
Gotan-White	LAL SINGH	NORMAL	A+VE	6/6GLS	6/6GLS	NORMAL		N-6 c gls	N-6 c gls		
Gotan-White	LALIT GARG		B+VE	6/6	6/6	NORMAL		N-6	N-6	NORMAL	79
Gotan-White	Laxman Singh	NORMAL	B+VE	6/6	6/6	NORMAL		N-6	N-6	NORMAL	82
Gotan-White	LAXMAN SINGH	NORMAL	B+VE	6/6 C GLS	6/9 C GLS	NORMAL		N-8C GLS	N-8C GLS	MILD REST	
								INI C	N-6	NORMAL	60
Gotan-White	LIVANJALI	NORMAL	B+VE	6/6 C GLS	6/6 C GLS	NORMAL	1250	N-6	N-6 C GLASS		96

G . 14/1/2	LOKESH VERMA	NORMAL	Δ_1/Γ	6/6 C GLASS	6/6 C GLASS	NORMAL	181	N-6 C GLASS	N-6 C GLASS	NORMAL	79
Gotan-White	MAHESH	NORMAL	A=VE O+VE	6/6 C.GLA33	6/6	11/2	160	N6	N-6	NORMAL	65
Gotan-White	MANGI LAL	NORMAL	AB+VE	6/9	6/9	NORMAL		N-6 CGLASS	N-6 CGLASS	NORMAL	57
Gotan-White	MANISH	NORMAL	AB+VE	6/6	6/6	NORMAL	171	N-6	N-6	NORMAL	76
Gotan-White	MANISH	NORMAL	B+VE	6/6	6/6		164	N-6	N-6	NORMAL	79
Gotan-White	MANMOHAN	NORMAL	A+VE	6/6	6/6	NORMAL		N-6	N-6	MILD REST	64.8
Gotan-White	MANOJ KUMAR	NORMAL	A+VE	6/6	6/6		167	N-6 GLS	N-6 GLS	MILD REST	73
Gotan-White	MATA DEEN	NORMAL	A+VE	6/6 C GLS	6/6 C GLS	NORMAL	153	N-6 C GLS	N-6 C GLS	NORMAL	66.5
Gotan-White	MOINUDDIN	NORMAL	O+VE	6/6	6/6	NORMAL	175	N-6	N-6	MILD REST.	82
Gotan-White Gotan-White	MUKESH	NORMAL	B+VE	6/6	6/6	NORMAL	174	N-6	N-6	MILD REST	90
Gotan-White	MUKESH	NORMAL	B+VE	6/6	6/6	NORMAL	179	N-6	N-6	NORMAL	52
Gotan-White	NAINA RAM	NORMAL	B+VE	6/6	6/6	- Control of the Cont	166	N-6 C GLS	N-6 C GLS	MILD REST	75
	NARAYAN LAL	MLBE	O+VE	6/6 CGLASS	6/6 CGLASS	NORMAL	173	N-6 CGLASS	N-6 CGLASS	NORMAL	68
Gotan-White	NARENDRA	NORMAL	B-VE	6/6	6/6	NORMAL	171	N-6	N-6	MILD REST	53
Gotan-White	NITESH GUPTA	NORMAL	O+VE	6/6 GLS	6/6 GLS	NORMAL	161	N-6 GLS	N-6 GLS	NORMAL	65.5
Gotan-White	OM PRAKASII	MLBE	A+ve	6/6	6/6	NORMAL	-	N-6	N-6	MILD REST	64
Gotan-White	OM PRAKASH	NORMAL	O+VE	6/9 CGLASS	6/9 CGLASS	NORMAL	172	N-6 CGLASS		NORMAL	69.3
Gotan-White	OM PRAKASH	ML BE	O+VE	6/6 C GLS	6/6 C GLS	NORMAL	173	N-6	N-6	MILD REST	74
Gotan-White	ONKAR LAL	NORMAL	B+VE	6/6	6/6	NORMAL	174	N-6	N-6	NORMAL	85
Gotan-White	ONKAR NATH	NORMAL	A+VE	6/6 C GLASS	6/6 C GLASS	NORMAL	168	N-6 C GLASS	N-6 C GLASS	MILD REST	79
Gotan-White	PARMANAND	NORMAL	B+VE	6/6 C GLASS	6/6	NORMAL	178	N-6	N-6	NORMAL	97
Gotan-White	POKAR RAM	ML LE	O+VE	6/9 GLS	6/9 GLS	NORMAL	161	N-6 GLS	N-6 GLS	MILD REST	
Gotan-White	PRAHLAD RAM	NORMAL	B+VE	6/6 C GLASS	6/6 C GLASS	NORMAL	178	N-6 C GLASS	N-6 C GLASS		86
Gotan-White	PRAKASH	NORMAL	O+VE	6/6	6/6	NORMAL	173	N-6	N-6	NORMAL	72
Gotan-White	PRATHVIRAJ	NORMAL	A+VE	6/6 C GLS	6/6 C GLS	NORMAL	172	N-6 C GLS	N-6 C GLS	MILD REST	
Gotan-White	Praveen Pancholi	NORMAL	B+VE	6/6	6/6	NORMAL	161	N-6	N-6	NORMAL	69.8
Gotan-White	Praveen Singh		A+VE	6/6	6/6	NORMAL	172	N-6	N-6	NORMAL	84
Gotan-White	PRAVEEN SINGH	NORMAL	A-VE	6/6	6/6	NORMAL	159	N-8 C GLS	N-8 C GLS	MILD REST	73
Gotan-White	PREM SINGH	NORMAL	A+VE	6/6 CGLASS	6/6 CGLASS	NORMAL	167	N-6 CGLASS	N-6 CGLASS		
Gotan-White	PUSHPENDRA	NORMAL	O+VE	6/6	6/6	NORMAL	170	N-6	N-6	NORMAL	83
Gotan-White	RAHUL	NORMAL	O+VE	6/6	6/6	NORMAL	166	N-6	N-6	MILD REST	55
Gotan-White	Rahul Bhardwaj	NORMAL	AB+VE	6/6	6/6	NORMAL	170	N-6	N-6	NORMAL	81
Gotan-White	RAHUL JAIN	NORMAL	B+VE	6/6	6/6	NORMAL	184	N-6	N-6	NORMAL	98
Gotan-White	RAHUL SAIN	NORMAL	A+VE	6/6	6/6	NORMAL	178	N-6	N-6	NORMAL	104
Gotan-White	RAM CHANDRA	NORMAL	O+VE	6/9 CGLASS	6/9 C GLASS	NORMAL	175	N-8 GLS	N-8 GLS	NORMAL	95
Gotan-White	RAM DEV VYAS	NORMAL	B+VE	6/9 C GLS	6/9 C GLS	NORMAL	165	N-8 C GLS	N-8 C GLS	NORMAL	68
Gotan-White	RAM LAL	NORMAL	O+VE	6/6	6/6	NORMAL	167	N-6C GLASS	N-6C GLASS	NORMAL	73
Gotan-White	RAM NIWAS	NORMAL	B+VE	6/6	6/6	NORMAL	176	N-6 C GLASS	N-6 C GLASS		78
Gotan-White	RAM NIWAS	NORMAL	B+VE	6/6 CGLASS	6/6 CGLASS	NORMAL	177	N-6 GLS	N-6 GLS	NORMAL	86
Gotan-White	RAM PRAKASH	NORMAL	A+VE	6/6	6/6	NORMAL	169	N-6 C GLS	N-6 C GLS	MILD REST	76
Gotan-White	SAHI RAM	ML BE	A -VE	6/9	6/9	NORMAL	169	N-6	N-6	MILD REST.	80
Gotan-White	SARDARA RAM	NORMAL	B+VE	6/6	6/6	NORMAL	174	N-6 GLS	N-6 GLS	NORMAL	90
Gotan-White	SAROJ KUMAR	NORMAL	A+VE	6/6 CGLASS	6/6 CGLASS	NORMAL	164	N-6 CGLASS	N-6 CGLASS	NORMAL	73
Gotan-White	SATYANDRA	NORMAL	B-VE	6/6	6/6	NORMAL	183	N-6	N-6	NORMAL	74
Gotan-White	SATYENDRA	NORMAL	B+VE	6/6	6/6	NORMAL	169	N-6	N-6	NORMAL	61
Gotan-White	SATYENDRA	NORMAL	O+VE	6/6 CGLASS	6/6 CGLASS	NORMAL	171	N-6 CGLASS	N-6 CGLASS	MILD REST	73
Gotan-White	SHAFIK ALI	NORMAL	B+VE	6/6 CGLASS	6/6 CGLASS	NORMAL		N-6 CGLASS	N-6 CGLASS		81
Gotan-White	SHAILENDRA	NORMAL	O+VE	6/6 CGLASS	6/6 CGLASS	NORMAL	162.5	N-6 CGLASS	N-6 CGLASS	NORMAL	68.6
Gotan-White Gotan-White	SHALINI SABU	NORMAL	O+VE	6/6 C GLASS	6/9 C GLASS	NORMAL		N-6 C GLASS	N-8 C GLASS	MILD REST	63
Gotan-White	SHELENDRA	NORMAL	B+VE	6/6	6/6	NORMAL	1	N-8 C GLS	N-8 C GLS	NORMAL	72
Gotan-White	SHISHPAL	NORMAL	A+VE	6/6	6/6	NORMAL		N-6	N-6	NORMAL	77
Gotan-White	SHRI RAM	NORMAL	A+VE	6/6 CGLASS	6/6 CGLASS	NORMAL		N-6 CGLASS	N-6 CGLASS	NORMAL	78.9
Gotan-White	SHYAM LAL	NORMAL	A+VE	6/6 C GLS	6/6 C GLS	NORMAL		N-6 C GLS	N-6 C GLS	NORMAL	100
Gotan-White	SRI RAM	NORMAL	A + VE	6/6	6/6	NORMAL		N-6 C GLASS	N-6 C GLASS		73
Gotan-White	SURENDER	NORMAL	A+VE	6/6 GLS	6/6 GLS	NORMAL	_	N-6 GLS	N-6 GLS	NORMAL	63
Gotan-White	SUSHIL KUMAR	NORMAL	B+VE	6/6	6/9	NORMAL		N-6	N-6	NORMAL	76
Gotan-White	TEJ PAL SINGH	NORMAL	B+VE	6/6 C GLS	6/9 C GLS	NORMAL		N-6 C GLS	N-6 C GLS	MILD REST	79
10.75	VIJAY	NORMAL	B+VE	6/6 C GLS	6/6 C GLS	NORMAL	171	N-6 C GLS	N-6 C GLS	NORMAL	82
Gotan-White	VIJAY SONI	NORMAL	B+VE	6/6	6/6	NORMAL	162	N-6	N-6	MILD REST	
Gotan-White Gotan-White	VIKAS KUMAR	NORMAL	O+VE	6/6	6/6	NORMAL	174	N.6	N.6	NORMAL	74
Gotan-White	VIRENDRA	NORMAL	B+VE	6/9 GLS	6/9 GLS	NORMAL	172	N-6 GLS	N- GLS	NORMAL	77
Gotan-White	VIRENDRA	NORMAL	A+VE	6/6 C GLS	6/6 C GLS	NORMAL	100	N-6 C GLS	N-6 C GLS	MILD REST	
	YOGENDRA	NORMAL	B+VE	6/6 C GLASS	6/6 C GLASS	NORMAL		N-6 C GLASS	N-6 C GLASS		102
Gotan-White	YOGESH NAGAR	NORMAL	B+VE	6/6	6/6	NORMAL	-	N-6	N-6	MILD REST	
Gotan-White	1. OGEOTI WAGAIN	HACKINIAL	IDTAE	IOVO	TUTU	HADRINAL	1214	11.4.50	1.0.7. 70		