



**Consent For Operation
(CFO-Air,Water)**

**Consent No. AWH-301684
Valid upto: 30/06/2021**

Industry Colour: RED Industry Scale: LARGE

**Karnataka State Pollution Control Board
Parisara Bhavana, No.49, Church
Street, Bengaluru-560001
Tele : 080-25589112/3, 25581383
Fax: 080-25586321
email id: ho@kspcb.gov.in**

(This document contains 6 pages including annexure & excluding additional conditions)

COPY TO:

The Environmental Officer, KSPCB, Regional Office Bagalkote for information and necessary action.

2. Master Register.
3. Case file.

1. Consent Fee paid : Rs. 400000

SCHEDULE

TERMS AND CONDITIONS

A. TREATMENT AND DISPOSAL OF EFFLUENTS UNDER THE WATER ACT.

1. The discharge from the premises of the occupier shall pass through the terminal manhole/manholes where from the Board shall be free to collect samples in accordance with the provisions of the Act/Rules made there under.

2(a). The sewage/domestic effluent shall be treated in septic tank and with soak pit. No overflow from the soak pit is allowed. The septic tank and soak pit shall be as per IS 2470 Part-I & Part-II.

2(b). The treated sewage effluent discharged shall conform to the standards specified in Annexure-I.

3(a). The trade effluent generated in the industry shall be treated in the ETP and treated effluent shall confirm to the standards stipulated by the Board in Annexure-1

3(b). The trade effluent shall be handed over to CETP and maintain logbook of effluent generated & sent every day.

4. The applicant shall install flow measuring/recording devices to record the discharge quantity and maintain the record.

5. The applicant shall not change or alter either the quality or the quantity or the place of discharge or temperature or the point of discharge without the previous consent/ permission of the Board.

6. The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises. Storm water shall not be allowed to mix with the effluents on the upstream of the terminal manhole where the flow measuring devices are installed.

7. The daily quantity of domestic effluent and trade effluent from the industry shall not exceed the limits as indicated in this consent order:

8. The applicant shall discharge the effluents only to the place mentioned in the Consent order and discharge of treated/untreated outside the premises is not permitted.

B. EMISSIONS:

1. The discharge of emissions from the premises of the applicant shall pass through the air pollution control equipment and discharged through stacks/chimneys mentioned in **Annexure-II** where from the Board shall be free to collect the samples at any time in accordance with the provisions of the Act and Rules made there under. The tolerance limits of the constituents forming the emissions in each of the stacks shall not exceed the limits laid down in Annexure-II.

2. The applicant shall provide port holes for sampling of emission, access platforms for carrying out stack sampling, electrical points and all other necessary arrangements including ladder as indicated in Annexure-II.

3. The applicant shall upgrade/modify/replace the control equipment with prior permission of the Board.

C. WATER CESS:

1. The applicant shall provide water meter at all the intake points as specified under Section (5) of the Water Cess Act, 1977 and shall file the Water Cess returns regularly before fifth of every month and also pay the Cess assessed with the time stipulated.



**Consent For Operation
(CFO-Air,Water)**

**Consent No. AWH-301684
Valid upto: 30/06/2021**

Industry Colour: RED

Industry Scale: LARGE

**Karnataka State Pollution Control Board
Parisara Bhavana, No.49, Church
Street, Bengaluru-560001
Tele : 080-25589112/3, 25581383
Fax: 080-25586321
email id: ho@kspcb.gov.in**

(This document contains 6 pages including annexure & excluding additional conditions)

D.MONITORING & REPORTING:

1. The applicant shall get the samples of effluents & emissions collected and get them analyzed once a month/either by in house monitoring laboratory or through EP approved laboratories for the parameters as Indicated in Annexure I & II.
2. The applicant shall maintain log books to reflect the working condition of pollution control systems and also self monitoring results and keep it open for inspection.

E. SOLID WASTE (OTHER THAN HAZARDOUS WASTE) DISPOSAL:

1. The applicant shall segregate solid waste from Hazardous Waste, Municipal Solid Waste and store it properly till treatment/disposal without causing pollution to the surrounding Environment.
2. The solid waste generated shall be handled & disposed by scientific method without causing eye sore to the general public and to the surrounding environment.

F. NOISE POLLUTION CONTROL:

1. The industry shall ensure that the ambient noise levels within its premises shall not exceed the limits i.e 75 dB(A) Leq during day time and 70 dB(A) Leq during night time as specified in under the Air (Prevention and Control of Pollution) Act, 1981.

G. HAZARDOUS WASTES (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) 2008:

The applicant shall comply with the provisions of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008.

H. GENERAL CONDITIONS:

1. The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises.
2. The applicant shall promptly comply with all orders and instructions issued by the Board from time to time or any other officers of the Board duly authorized in this behalf.
3. The applicant shall set-up Environmental Cell comprising of qualified and competent personnel for complying with the conditions specified.
4. The Board reserves the right to review, impose additional conditions, revoke, change or alter terms and conditions of this consent.
5. The applicant shall forthwith keep the Board informed of any accidental discharge of emissions/effluents into the atmosphere in excess of the standards laid down by the Board. The applicant shall also take corrective steps to mitigate the impact.
6. The applicant shall provide alternative power supply sufficient to operate all Pollution control equipments.
7. The entire premises shall always be kept clean. The effluent holding area, inspection chambers, outlets, flow measuring points should be made easily approachable.
8. The applicant shall display the consent granted in a prominent place for perusal of the inspecting officers of the Board.
9. The applicant his heirs, legal representatives or assignee shall have no claims what so ever to the continuation or renewal of this consent after expiry of the validity of consent.

(This document contains 6 pages including annexure & excluding additional conditions)

10. The applicant shall make an application for consent for subsequent period at least 45 days before expiry of this consent.
11. The applicant shall develop and maintain adequate green belt all around the periphery.
12. The applicant shall provide rain water harvesting system and shall provide proper storm water management system.
13. This consent is issued without prejudice to any Court Cases pending in any Hon'ble Court
14. The applicant shall furnish the Environmental statement for every financial year ending with 31st March in Form-V as per Environment (Protection) Rules, 1986. The statement shall be furnished before the end of September.
15. The applicant shall display flow diagram of the pollution control system near the pollution control system/s.

NOTE:
The following Conditions A[2(a), 3(b)] & G mentioned in the schedule are not applicable.

Additional Conditions:
Please see additional condition to the consent order. The Annexure-I, II & III is applicable for discharge of effluent and emission regulation.

For and on behalf of the
Karnataka State Pollution Control Board



S NANDA KUMAR

Note: All efforts should be made to remove colour and unpleasant odour as far as practicable.

Chi m.N o.	Chimne y attached to	Capacity/ KVA Rating	Minimum chimney height to be provided above ground level (in Mts)	Constituents to be controlled in the emission	Tolerance limits mg/NM3	Fuel	Air pollution Control equipment to be installed,in addition to chimney height as per col.(3)	Date of which air pollution control equipments shall be provided to achieve the stipulated tolerance limits and chimney heights conforming to stipulated heights.
1	Any Other	Attached Coal mill 50 tph	45	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	COA	FIL	Before commissioning.
2	D.G. Sets	500 KVA	7	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	DIE	N.A	Before commissioning.
3	D.G. Sets	500 KVA	7	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	DIE	N.A	Before commissioning.
4	Boiler	Power plant 2 x 25MW	105	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	COA	ESP	Before commissioning.
5	Any Other	slag grinding	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	BGH	Before commissioning.



**Consent For Operation
(CFO-Air,Water)**

**Consent No. AWH-301684
Valid upto: 30/06/2021**

**Karnataka State Pollution Control Board
Parisara Bhavana, No.49, Church
Street, Bengaluru-560001
Tele : 080-25589112/3, 25581383
Fax:080-25586321
email id: ho@kspcb.gov.in**

Industry Colour: RED Industry Scale: LARGE

(This document contains 6 pages including annexure & excluding additional conditions)

6	Any Other	coal crusher 120 tph	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
7	Any Other	packing plant 120 tph	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
8	Any Other	packing plant 120 tph	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
9	Any Other	packing plant 120 tph	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
10	Any Other	packing plant 120 tph	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
11	Any Other	cement mill separato r	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
12	Any Other	cement mill separato r	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
13	Any Other	cement mill 165 tph	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
14	Any Other	cement mill 165 tph	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
15	Any Other	clinker storage 50000 TON	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
16	Any Other	Clinker transport	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
17	Any Other	clinker cooler, 6500 tpd	40	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	COA	ESP	Before commissioning.
18	Any Other	Raw material transport	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.
19	Any Other	Raw mill 525 tph /Kiln	100	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	COA	BGH	Before commissioning.
20	Any Other	Limeston e crushr 1000 tph	30	PM(mg/NM3),SO2 (PPM),NOx(PPM)	150,100,50	ELE	FIL	Before commissioning.

Note:

FIL : Bag Filter
N.A : Not Applicable
ESP : E.S.P
BGH : Bag House
ESP : E.S.P

Note:

- The Noise levels within the premises shall not exceed 75 dB (A) leq during day time and 70 dB(A) leq during night time respectively.
- The DG set shall be provided with acoustic measures as per SI.No.94 in Schedule-I of Environment (Protection)Rules.
- There shall be no smell or odour nuisance from the industry.



**Consent For Operation
(CFO-Air,Water)**

**Consent No. AWH-301684
Valid upto: 30/06/2021**

Industry Colour: RED

Industry Scale: LARGE

**Karnataka State Pollution Control Board
Parisara Bhavana, No.49, Church
Street, Bengaluru-560001
Tele : 080-25589112/3, 25581383
Fax: 080-25586321
email id: ho@kspcb.gov.in**

(This document contains 6 pages including annexure & excluding additional conditions)

LOCATION OF SAMPLING PORTHOLES, PLATFORMS, ELECTRICAL OUTLET.

1. Location of Portholes and approach platform:

Portholes shall be provided for all chimneys, stacks and other sources of emission. These shall serve as the sampling points. The sampling point should be located at a distance equal to at least eight times the stack or duct diameters downstream and two diameters upstream from source of low disturbance such as a Bend, Expansion, Construction Valve, Fitting or Visible Flame for rectangular stacks, the equivalent diameter can be calculated from the following equation.

$$\text{Equivalent Diameter} = \frac{2 (\text{Length} \times \text{Width})}{(\text{Length} + \text{Width})}$$

- The diameter of the sampling port should not be less than 100 mm dia". Arrangements should be made so that the porthole is closed firmly during the non sampling period
- An easily accessible platform to accommodate 3 to 4 persons to conveniently monitor the stack emission from the portholes shall be provided. Arrangements for an Electric Outlet Point of 230 V 15 A with suitable switch control and 3 Pin Point shall be provided at the Porthole location.
- The ladder shall be provided with adequate safety features so as to approach the monitoring location with ease.

[Click Here to View Uploaded Document1](#)