J.K. CEMENT WORKS, MANGROL (RAJ.)

Compliance report of Mangrol Lime stone mine (For the period from April 2013 to September 2013)

Sub:- Conditions of Environment Clearance from MOEF, New Delhi Letter No. J-11015/427/2008-1A. II(M) dated 06.08.2010

Sr.No	Condition	Status	
	A. SPECIFIC CONDITIONS:		
(i)	The project proponent shall obtain Consent to Establish and Consent to Operate from the Rajasthan State Pollution Control Board and effectively implement all the conditions stipulated therein.	Consent to establish has been obtained vide letter reference no. F(Mines)/Chittorgarh/(Nimbahera) 966(1) 2011-12/14718-4722 dated 29.09.2011 & consent to operate has also been obtained vide letter No. F (Mines)/chittorgarh (Nimbahera)/966(1)/2011-2012/9330-9334 dated 05.02.2013 & valid up to 31.01.2016.	
(ii)	Environmental clearance is granted subject to final outcome of Hon'ble Supreme Court of India in Contempt Petition (C) No.412/2004 in IA No. 833 in Writ Petition (C) No. 202 of 1995, as may be applicable to this project.		
(iii)	The environmental clearance is subject to approval of the State Land use Department, Government of Rajasthan for diversion of agricultural land for non-agricultural use.	Agriculture land will be used after having proper conversion for use of mining from state revenue department.	
(iv)	Necessary prior permission from the Competent Authority as may be applicable for use of grazing land for mining purpose shall be obtained.	f obtained from revenue deptt. Vide letter No. Revenue/2011-	
(v)	The project proponent shall develop fodder plots in the non-mineralized area in lieu of use of grazing land.	Agreed. We will develop fodder plots.	
(vi)	The mining operations shall be restricted to above ground water table and it should not intersect the groundwater table. In case of working below the ground water table, prior	Agreed, we will not work below the ground water table prescribed in the approved Mining plan. Max. Depth of working as per approved mining plan 32 mtr. Ground water	

	approval of the Ministry of Environment and Forests and the Central Ground Water Authority shall be obtained, for which a detailed hydrogeological study shall be carried out.	table as per Ground water deptt. Govt. of Raj. Post monsoon -40 mtr, Premonsoon -60 mtr
(vii)	The project proponent shall ensure that no natural watercourse and/or water resources are obstructed due to any mining operations.	There are practically no large channels or other sources of water in the area. The water drains out of the area following the natural slope. No natural water course will be obstructed during Mining operation & this will be strictly followed as mentioned in Approved Mining Plan.
(viii)	The top soil shall temporarily be stored at earmarked site(s) only and it should not be kept unutilized for long. The topsoil shall be used for land reclamation and plantation.	The top soil generated during the mining operation will be stacked at designated places, leveled and plantation will be carried out as mentioned in approved mining plan.
(ix)	The waste generated during the mining operation shall be stacked at the earmarked site and reclaimed by the plantation. Monitoring and management of rehabilitated areas should continue until the vegetation becomes self-sustaining. Compliance status should be submitted to the Ministry of Environment & Forests and its Regional Office, Lucknow on six monthly basis.	As given in approved Mining Plan, there will be no generation of waste during the mining operation except top soil which will be stacked at designated places, leveled & will be stabilized by carrying out plantation over it. Measures will be taken to get more survival rate & self sustain.
(x)	The void left unfilled in the entire excavated area of 88.55ha shall be converted into water body. The higher benches of excavated void/mining pit shall be terraced and plantation done to stabilize the slopes. The slope of higher benches shall be made gentler for easy accessibility by local people to use the water body. Peripheral fencing shall be carried out all along the excavated area.	Since there is no overburden available which is also mentioned in approved Mining Plan, hence no material is available for back-filling. The whole excavated area will be properly fenced off from all sides and will be used for collection of harvested rain water. At the end of life of the Mine, the higher benches of excavated void/mining pit will be terraced and plantation will be done to stabilize the slopes. The entire excavated area will be properly fenced along the periphery.

(xi)	Catch drains and siltation ponds of appropriate size shall be constructed for the working pit, temporary soil, mineral dumps and waste dump(s) to arrest flow of silt and sediment directly into the agricultural fields, the Gambhiri dam, the Murlia reservoir, the Gambhiri river and other water bodies. The water so collected should be utilized for watering the mine area, roads, green belt development etc. The drains should be regularly desilted particularly after the monsoon and maintained properly.	The catch drain & siltation ponds will be constructed of appropriate size around the mining pit to prevent run off water & flow of sediments going directly into the agriculture fields/outside the mining limit & water bodies. There will be no generation of waste as prescribed in approved mining plan, hence no overburden dump will be formed.
	Garland drains, setting tanks and check dams of appropriate size, gradient and length shall be constructed both around the mine pit and waste dump(s) to prevent run off of water and flow of sediments directly into the agricultural fields, the Gambhiri dam, the Murlia reservoir, the Gambhiri river and other water bodies and sump capacity should be designed keeping 50% safety margin over and above peak sudden rainfall (based on 50 years data) and maximum discharge in the area adjoining the mine site. Sump capacity should also provide adequate retention period to allow proper setting of slit material. Sedimentation pits should be constructed at the corners of the garland drains and desilted at regular intervals.	Garland drain system, setting tanks & check dams of appropriate size, gradient & length will be constructed around the mining pit to prevent runoff water & flow of sediments outside the mining limit. There will be no generation of waste as mentioned in approved mining plan; hence no overburden dump will be formed.
(xii)	Dimension of the retaining wall at the toe of the waste dumps and the waste benches within the mine to check run-off and siltation should be based on the rain fall data.	Since there will be no generation of waste, only top black cotton soil will be generated which will be stacked, leveled at designated places & plantation will be done over it. However, wherever it will be required, a retaining wall will be constructed.
(xiii)	Plantation shall be raised in an area of 14ha including a 7.5m wide green belt in the safety zone around the mining lease, reclaimed area, around water body, around waste dumps along	Plantation done during 2013-14 (up to September 2013)-774 nos. total no's of plants planted, covering 0.34 hectare area.

	the roads etc. by planting the native species in consultation with the local DFO/Agriculture Department. The density of the trees should be around 1000 plants per ha. Greenbelt shall be developed all along the mine lease area in a phased manner and shall be completed within first five years.	
(xiv)	Effective safeguard measures, such as regular water sprinkling shall be carried out in critical areas prone to air pollution and having high levels of particulate matter such as around crushing and screening plant, loading and unloading point and all transfer points. Extensive water sprinkling shall be carried out on haul roads. It should be ensured that the Ambient Air Quality parameters conform to the norms prescribed by the Central Pollution Control Board in this regard.	Regular water sprinkling by deploying water sprinkler is done on the haul roads to prevent the dust becoming air borne during transport of vehicles. Wet drilling system is practiced during drilling of holes. Monitoring & measurement of ambient air quality will be done as mentioned in approved mining plan.
(xv)	The project authority should implement suitable conservation measures to augment ground water resources in the area in consultation with the Regional Director, Central Ground Water Board.	Construction measure to augment ground water resources the area will be implemented in consultation with the Regional Director, Central ground water board.
(xvi)	Regular monitoring of ground water level and quality shall be carried out in and around the mine lease by establishing a network of existing wells and installing new piezometers during the mining operation. The periodic monitoring [(at least four times in a year – pre-monsoon (April-May), monsoon (August), post-monsoon (November) and winter (January); once in each season)] shall be carried out in consultation with the State Ground Water Board/Central Ground Water Authority and the data thus collected may be sent regularly to the Ministry	Regular monitoring of ground water level & quality is being carried out in and around the Mining lease area as per the Environment Management Plan of approved Mining plan by establishing a network of existing wells. We have drilled 4 Nos. of piezometic holes for periodic monitoring which is carried out 4 times in a year for different season in consultation with State Ground water Board/Central Ground Water Authority & data thus collected is submitted regularly to the Ministry of Environment and Forests and its Regional Office, Lucknow, the Central Ground Water

	of Environment and Forests and its Regional Office, Lucknow, the Central Ground Water Authority and the Regional Director, Central Ground Water Board. If at any stage, it is observed that the groundwater table is getting depleted due to the mining activity, necessary corrective measures shall be carried out.	Authority and the Regional Director, Central Ground Water Board. We have submitted water quality report of Monsoon season (August-2013) vide letter no. MGR/PC/14/1392 on dated 03/09/2013.
(xvii)	Appropriate mitigative measures shall be taken to prevent pollution of the Gambhiri River and Murlia dam in consultation with the State Pollution Control Board.	No working will be carried out in submergence area of the dam & upto 15 mtr. from the boundary of the catchment area of the Gambhiri & Murlia Dam. There will be no disturbance & obstruction due to mining activity.
(xviii)	The project proponent shall obtain necessary prior permission of the competent authorities for drawl of requisite quantity of ground water required for the project.	Obtained permission from CGWA vide letter no. 21 – 4 (532)/WR/CGWA/2012 – 4326 dated 17.08.2012
(xix)	Suitable rainwater harvesting measures on long term basis shall be planned and implemented in consultation with the Regional Director, Central Ground Water Board.	Rain water harvesting measures on long term basis will be implemented in consultation with the Regional Director, Central ground board.
(xx)	Vehicular emissions shall be kept under control and regularly monitored. Measures shall be taken for maintenance of vehicles used in mining operations and in transportation of mineral. The mineral transportation shall be carried out through the covered trucks only and the vehicles carrying the mineral shall not be overloaded.	Tippers engaged in the mine will be regularly checked once in six months for vehicle emissions & will be kept under permissible limits as per the guidelines issued by the Authorities. The tippers will not be loaded above the rated capacity.
(xxi)	Controlled blasting shall be practiced. The mitigative measures for control of ground vibrations and to arrest fly rocks and boulders should be implemented.	Controlled blasting is being carried out by use of delay detonator, non-electric detonator. Regular monitoring of ground vibration will be practiced. Rock breaker is used to minimize secondary blasting.
(xxii)	The project proponent shall take all mitigative	Agreed

	measures during the mining operation to ensure that the buildings/structures in the nearby areas shall not be affected due to blasting.	
(xxiii)	Drills shall either be operated with dust extractors or equipped with waster injection system.	Water injection system on wagon drill is provided to suppress dust at its source of generation & only wet drilling is permitted as committed in Environment management plan of approved mining plan.
(xxiv)	Mineral handling area shall be provided with the adequate number of high efficiency dust extraction system. Loading and unloading areas including all the transfer points should also have efficient dust control arrangements. These should be properly maintained and operated.	Adequate air pollution control measures shall be installed accordingly.
(xxv)	Sewage treatment plant shall be installed for the colony. ETP shall also be provided for the workshop and waste water generated during the mining operation.	Sewage treatment Plant is already installed in the colony for Nimbahera plant & mines. No waste water will be generated during mining operation.
(xxvi)	Pre-placement medical examination and periodical medical examination of the workers engaged in the project shall be carried out and records maintained. For the purpose, schedule of health examination of the workers should be drawn and followed accordingly.	Pre placement Initial & periodical medical examination of the workers engaged will be carried out & record will be maintained. Schedule of health examination will be drawn is such a manner that every workmen will be examined once in five years.
(xxvii)	Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.	No construction labour will be engaged.

(xxviii)	The critical parameters such as RSPM (Particulate matter with size less than 10 micron i.e. PM ₁₀) and NO _x in the ambient air within the impact zone, peak particle velocity at 300m distance or within the nearest habitation, whichever is closer shall be monitored periodically. Further, quality of discharged water shall also be monitored [(TDS, DO, PH and Total Suspended Solids (TSS)]. The monitored data shall be uploaded on the website of the company as well as displayed on the display board at the project site at a suitable location near the main gate of the Company in public domain. The Circular No. J-20012/1/2006-IA.II(M) dated 27.05.2009 issued by Ministry of Environment and Forests, which is available on the website of the Ministry www.envfor.nic.in shall also be referred in this regard for its compliance.	Agreed, These critical parameter will be measured periodically during ambient air monitoring. No waste water is generating during mining operation.	
(xxix)	A Final Mine Closure Plan along with details of Corpus Fund should be submitted to the Ministry of Environment and Forests 5 years in advance of final mine closure for approval.	Progressive Mine closure plan is prepared along with approved Mining plan. There is no plan of final Mine closure in First five year of Mining Plan.	
	B. GENERAL CONDITIONS		
(i)	No change in mining technology and scope of working should be made without prior approval of the Ministry of Environment and Forests.	Agreed, Without prior approval of the Ministry of Environment & Forest there will be no change in mining technology & Scope of working.	
(ii)	No change in the calendar plan including excavation, quantum of mineral limestone and waste should be made.	Agreed, There will be no change in the calendar plan including excavation, quantum of mineral lime stone & waste.	

(iii)	Conservation measures for protection of flora and fauna in the core and buffer zone should be drawn up in consultation with the local forest and wildlife department and effectively implemented.	Agreed
(iv)	Four ambient air quality-monitoring stations should be established in the core zone as well as in the buffer zone for RSPM (Particulate matter with size less than 10 micron i.e., PM_{10}) and NO_x monitoring. Location of the stations should be decided based on the meteorological data, topographical features and environmentally and ecologically sensitive targets and frequency of monitoring should be undertaken in consultation with the State Pollution Control Board.	Agreed, We have informed State Pollution control board for finalization of Ambient Air Quality Monitoring stations vide letter no. MGR/PC/28/1600 on dated 4/10/2013.
(v)	Data on ambient air quality RSPM (Particulate matter with size less than 10 micron i.e., PM_{10}) & NO_x should be regularly submitted to the Ministry of Environment and Forests including its Regional Office located at Lucknow and the State Pollution Control Board/Central Pollution Control Board once in six months.	Will be complied
(vi)	Fugitive dust emissions from all the sources should be controlled regularly. Water spraying arrangement on haul roads, loading and unloading and at transfer points should be provided and properly maintained.	Agreed, Water spraying arrangement on haul roads, loading & unloading points is provided to control fugitive dust emission.
(vii)	Measures should be taken for control of noise levels below 85 dBA in the work environment. Workers engaged in operations of HEMM, etc. should be provided with ear plugs / muffs.	Agreed
(viii)	Industrial waste water (workshop and waste water from the mine) should be properly collected, treated so as to conform to the standards prescribed under GSR 422 (E) dated 19th May, 1993 and 31st December, 1993 or as amended from time to time. Oil and grease trap should be installed before discharge of workshop effluents.	Agreed. No industrial waste water is generated in the mine.

(ix)	Personnel working in dusty areas should wear protective respiratory devices and they should also be provided with adequate training and information on safety and health aspects. Occupational health surveillance program of the workers should be undertaken periodically to observe any contractions due to exposure to dust and take corrective measures, if needed.	Agreed, Protective respiratory devices will be provided to every personal working in dusty area. Adequate training & information on safety & health aspects will be imparted. Occupational health surveillance program of the workers will be undertaken periodically.
(x)	A separate environmental management cell with suitable qualified personnel should be set-up under the control of a Senior Executive, who will report directly to the Head of the Organization.	Agreed
(xi)	The funds earmarked for environmental protection measures should be kept in separate account and should not be diverted for other purpose. Year wise expenditure should be reported to the Ministry of Environment and Forests and its Regional Office located at Lucknow.	Will be strictly followed
(xii)	The project authorities should be inform to the Regional Office located at Lucknow regarding data of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.	Agreed
(xiii)	The Regional Office of this Ministry located at Lucknow shall monitor compliance of the stipulated conditions. The project authorities should extend full cooperation to the officer (s) of the Regional Office by furnishing the requisite data/information/monitoring reports.	Agreed
(xiv)	The project proponent shall submit six monthly reports on the status of compliance of the stipulated environmental clearance conditions including results of monitored data (both in hard copies as well as by email) to the Ministry of Environment and Forests, its Regional Office located at Lucknow, the respective Zonal Office of Central Pollution Control Board the State Pollution Control Board. The proponent shall upload the status of compliance of the environmental clearance conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional office of the Ministry of Environment and Forests, Lucknow, the respective Zonal Office of Central Pollution Control Board and the State Pollution Control Board.	We have submitted six monthly report vide letter no. MGR/PC/14/545 on dated 1/06/2013

(xv)	A copy of the clearance letter shall be sent by the proponent to concerned Panchayat, Zila Parisad, Municipal Corporation, Urban Local Body and the Local NGO, if any, from whom suggestions/representations, if any, were received while processing the proposal. The clearance letter shall also be put on the website of the Company by the proponent.	Implemented
(xvi)	The State Pollution Control Board should display a copy of the clearance letter at the Regional Office, District Industry Centre and the Collector's Office/Tehsildar's Office for 30 days.	
(xvii)	The environmental statement for each financial year ending 31 st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of environmental clearance conditions and shall also be sent to the Regional Office of the Ministry of Environment and Forests, Lucknow by e-mail.	Will be complied
(xviii)	The project authorities should advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at website of the Ministry of Environment and Forests at http://envfor.nic.in and a copy of the same should be forwarded to the Regional Office of this Ministry located at Lucknow.	Implemented & the necessary information already sent to the concerned authority.