



JK Cement LTD.

Phone : +91-1477-220098, 220087
Fax : +91-1477-220027, 220049
E-mail : jkc.nbh@jkcement.com
Web : www.jkcement.com

J.K. Cement Works, Mangrol
C/o. Kailash Nagar-312617, Nimbahera
Distt. Chittorgarh (Raj.) INDIA

CIN : L17229UP1994PLC017199

ISO 9001:2008, ISO 14001:2004 & OHSAS 18001 : 2007 CERTIFIED COMPANY

MGR/PC/ESR/21 267

Date: 15.09.2020

o/c

To,
The Member Secretary,
Rajasthan State Pollution Control Board 4,
Industrial Area, Jhalaya Dungri
JAIPUR – 302004 (Raj)

Subject: Environmental Statement Report for the year FY 2019-2020 of Cement Plant Line-3 with additive crusher (02 Nos.) of M/s J. K. Cement Works Mangrol, Tehsil: Nimbahera, Dist.: Chittorgarh (Rajasthan).

Ref.: F(CPM)/Chittorgarh(Nimbahera)/11(1)/2018-2019/2188-2190, Order No: 2019-2020/CPM/5515, Dated 27/09/2019.

F(CPM)/Chittorgarh(Nimbahera)/11(1)/2018-2019/3535-3538, Order No: 2019-2020/CPM/5588, Dated 03/01/2020.

Dear Sir,

With reference to above subject matter, please find enclosed herewith Environment Statement Report of Cement Plant Line-3 with additive crusher (02 Nos.) of J.K. Cement Works, Mangrol for the FY 2019-2020 for your reference and record. We trust you will find the same in order.

Thanking You.

Yours Faithfully
For J.K. Cement Works, Mangrol

Anil Kumar Jain
Sr. General Manager (Environment)

Encl. : as above.

Copy:

The Regional Officer, Rajasthan State Pollution Control Board, Near FCI Godown,
Chandaria, Distt.- CHITTORGARH (RAJ)

Corporate & Registered Office : Kamla Tower, Kanpur-208001, (U. P.) INDIA
Phone : +91-512-2371478 to 81 **Fax :** 2399854 **E-mail :** ho.grey@jkcement.com



J. K. Cement Works, Nimbahera
J. K. Cement Works Mangrol
J. K. Cement Works, Gotan

J. K. Power, Bamania
J. K. Cement Works, Muddapur
J. K. White Cement Works, Gotan



ENVIRONMENTAL STATEMENT

FORM - V

Environmental Statement for the financial year 2019-20, ending the 31st March 2020

PART-A

i. Name an address of the owner/occupier of the industry operation or process	J.K. Cement Works, Mangrol Cement Plant (Unit-III) with additive crusher (02 Nos.) C/o Kailash Nagar, Nimbahera Tehsil: Nimbahera, Chittorgarh (Rajasthan) PIN- 312617
ii. Industry category Primary - (STC Code) Secondary - (STC Code)	Primary
iii. Production capacity	Clinker : 2.75 MMTPA Cement : 3.60 MMTPA
iv. Year of establishment	Plant commissioned on dated 29/09/2019
v. Date of last environmental statement submitted	Not applicable

PART-B

WATER AND RAW MATERIAL CONSUMPTION

i. WATER CONSUMPTION in m3/day

Process:	: -	NIL
Cooling	: -	990 m3/day
Domestic	: -	10 m3/day

Name of products	Process water consumption per unit of products (For cooling & domestic)	
	During the previous financial year (2018-19) (KL/MT)	During the current financial year (2019-20) (KL/MT)
1. CEMENT	Plant was not commissioned	0.052

ii. **RAW MATERIAL CONSUMPTION**

Name of raw material	Name of products	Consumption of raw material per unit of output (in MT)	
		During the previous financial year (2018-19)	During the current financial year (2019-20)
Limestone	Clinker	NA*	1.37
Laterite / Red ocher		NA*	0.159
Coal		NA*	0.0132
Petcock		NA*	0.0941
Alternative Fuel Replacement & Alternative Raw Material		NA*	0.0247
Gypsum	Cement	NA*	0.063
Flyash% of OPC + PPC		NA*	0.152
Flyash% of PPC		NA*	0.281
Alternative Raw Material & Performance improver		NA*	0.0101

* Plant was commissioned on dated 29/09/2019.

PART-C

POLLUTION DISCHARGE TO ENVIRONMENT / UNIT OF OUTPUT

Pollutants	Quantity of pollutants discharged (Ton/Day)	Concentration of pollutants in discharge (mg/Nm3)	Percentage of variation from prescribed standards with reasons		
(a) Water	As the plant is being operated on dry process technology, no liquid effluent is generated from cement plant. The Domestic waste water generated from the office toilet and canteen being treated with STP and treated water used in greenery development in the plant premises.				
(b) Air	Stack Emission (yearly average)				
PM	0.373	12.825	-42.75 %		
SO2	10.02	45.09	-45.09 %		
NOx	82.262	367.86	-61.31 %		
Ambient Air Quality (yearly average) in µg/m³					
Location	Parameters				
	PM10	PM2.5	SO2	NOx	CO(in mg/m³)
Near Time Office	52.7	36.7	18.2	24.6	644.9
Near Thermal Power Plant	57.5	39.7	20.0	23.6	721.5
Near Factory Gate	59.7	39.8	18.0	25.5	746.3
Near Colony Gate	54.2	38.1	16.9	24.9	687.2

STP treated water quality data

STP treated water Quality		
Parameters	Standards	Average results of YTD
pH	Between 5.5 to 9.0	7.08
Total Suspended solids	Not to exceed 100 mg/l	4.95
Biological Oxygen Demand (3 days at 27 Degree C)	Not to exceed 30 mg/l	3.7
Chemical Oxygen Demand	Not to exceed 250 mg/l	12.48
Oil & Grease	Not to exceed 10 mg/l	<2.46
Ammonical Nitrogen (as N)	Not to exceed 50 mg/l	1.05

Noise level monitoring data

Month	Noise Monitoring Report FY 2019-20							
	Near Time office		Near Thermal Power Plant		Near Raw material Gate		Near Packing Plant Gate	
	Day	Night	Day	Night	Day	Night	Day	Night
Apr-19	71.8	61.4	67.8	57.2	71.8	61.4	67.8	57.2
May-19	69.9	60.8	69.2	59.1	69.9	60.8	69.2	59.1
Jun-19	71.6	61.2	70.0	60.4	71.6	61.2	70.0	60.4
Jul-19	70.5	60.5	68.9	58.1	70.5	60.5	68.9	58.1
Aug-19	69.7	59.9	69.9	59.6	69.7	59.9	69.9	59.6
Sep-19	71.0	61.1	68.5	58.2	71.0	61.1	68.5	58.2
Oct-19	67.1	57.5	69.2	59.1	69.4	59.2	71.4	61.3
Nov-19	68.4	58.6	67.7	58.7	68.7	57.4	70.8	61.1
Dec-19	67.9	58.5	68.4	58.9	69.6	58.9	71.6	61.5
Jan-20	68.7	59.2	68.9	59.2	70.2	59.4	70.9	60.8
Feb-20	67.4	58.4	69.2	59.6	70.8	58.5	71.2	61.2
Mar-20	66.2	54.6	66.7	54.8	65.6	52.4	66.9	51.2
YTD	69.2	59.3	68.7	58.6	69.9	59.2	69.8	59.1

PART-D

(As specified under Hazardous & Other Waste Management Rules-2016)

Hazardous waste	Total Quantity	
	During previous financial year (2018-19) (KL)	During current financial year (2019-20) (KL)
(a) From process	Used oil (5.1)- 17.4 * Waste oil (5.2)- NIL	Used oil (5.1)- 9.40* Waste oil (5.2)- NIL
(b) From pollution Control facilities	Not applicable	Not applicable

*including Cement Plant L-1,2, 3, CPP, WHRS, Mines & Colony. Hazardous waste generated are being sold through authorized recycler by CPCB.

PART-E

SOLID WASTE

		Total Quantity	
		During previous financial year (2018-19) (MT/Year)	During current financial year (2019-20) (MT/Year)
(a)	From process	Nil	Nil
(b)	From pollution control facility	Dust collected in ESP, bag house and bag filters are recycled to the system	Dust collected in ESP, bag house and bag filters are recycled to the system
(c)	Quantity reutilized with in the unit	100%	100%

PART-F

PLEASE SPECIFY THE CHARACTERISATIONS (IN TERMS OF COMPOSITION AND QUANTUM) OF HAZARDOUS AS WELL AS WASTES AND INDICATE DISPOSAL PRACTICE ADOPTED FOR BOTH THESE CATEGORIES OF WASTES.

- 1) Hazardous waste generated in the form of used / spent oil, waste / residue containing oil, which is stored in barrels at safe & dedicated area and sold to recycler approved by Central Pollution Control Board.
- 2) Dust collected from pollution control equipment's (i.e. from ESP, Bag house and Bag filter) is totally recycled in the process.

PART-G

IMPACT OF THE POLLUTION ABATEMENT MEASURES TAKEN ON CONSERVATION OF NATURAL RESOURCES AND ON THE COST OF PRODUCTION.

Cement manufacturing is a dry process technology, hence no effluent generated from process. Which is cost effective and environmentally clean technology. The advantage of dry process is also in fuel economy. The stack emissions from the plant are controlled by equipment like ESPs and Bag filters installed at various material transfer points to arrest the fugitive emissions. The particulate matter collected from the pollution control equipment is recycled in process and optimizing the cost of operation of pollution control equipment, conserving natural raw material and hence no impact on the environment.

PART-H

ADDITIONAL MEASURES / INVESTMENT PROPOSALS FOR ENVIRONMENTAL PROTECTION INCLUDING ABATEMENT POLLUTION, PREVENTION OF POLLUTION.

- 1) Conducted 3rd party monitoring of leachate testing for soil contamination in AFR storage yard.
- 2) SNCR system installed to control the NO_x emission.

PART-I

ANY OTHER PARTICULARS FOR IMPROVING THE QUALITY OF ENVIRONMENT

- 1) Monitoring of stack emission and ambient air and water quality is being done regularly as mentioned in consent to operate.
- 2) 4 nos. of Continuous Ambient Air Quality Monitoring Systems (CAAQMS) has been installed at periphery of the plant.
- 3) Continuous Emission Monitoring Systems (CEMS) for PM, SO₂ & NO_x have been installed at stack of Kiln section and for monitoring of PM emission CEMS has installed at stack coal mill, cooler & cement mill and real time data transfer to RSPCB & CPCB.
- 4) Bag filters have been installed at various material transfer points to control fugitive emission.

- 5) Cement being manufacturing in dry process and there is no any effluent generated from the process hence maintaining Zero Effluent Discharge unit.
- 6) Apart from this fly ash purchased from nearby thermal power plant and use for cement production.
- 7) Raw materials are storage in covered shed, product in closed silo with high efficient bag filters for fugitive dust emission control.
- 8) To utilization of waste heat, Waste heat recovery system has been installed to generate green power.
- 9) Proper Housekeeping and cleaning is being done with the help of three road sweeping machines.
- 10) Domestic waste water generated is being treated in sewage treatment plant (STP). Treated water is utilized for plantation / horticulture development.
- 11) Cover shed Constructed to store the raw material, to avoid fugitive emission. Finish product stored in closed silo.
- 12) All Belt Conveyor belt are fully covered & also installed Bag filter at all material transfer points
- 13) 16 Rain water harvesting structures have been constructed in plant and colony area to recharge ground water.
- 14) Cemented road constructed to avoid fugitive dust generation during the movement of vehicle.
- 15) Telemetry system installed for online ground water level monitoring.
- 16) Total 4800 sapling planted in the FY 2019-20.
- 17) More than 33 % area covered with green belt.