

JK Cement Works, Mangrol A unit of JK Cement Ltd.

♠ C/o. Kailash Nagar - 312617, Nimbahera Distt., Chittorgarh (Raj.) INDIA

€ +91-1477-220098, 220087 🛥 jkc.mgrl@jkcement.com

MGR/PC/ESR/21

Date: 19.09.2021

To. The Member Secretary, Rajasthan State Pollution Control Board, 4, Industrial Area, Jhalana Dungri JAIPUR - 302004 (Raj)

Subject: Environmental Statement Report for the FY 2021-2022 of Power Plant (25 MW) of M/s J.K. Cement Works, Mangrol, Tehsil: Nimbahera, Dist: Chittorgarh (Rajasthan).

Ref.: 1. F (Tech)/Chittorgarh (Nimbahera)/1(1)/2008-2009/1521-1523 & Order No 2017-2018/CPM/4862, Dated 30/05/2017.

2. F (Tech)/Chittorgarh (Nimbahera)/11(1)/2018-19/5985-5987 & Order No 2020-21/CPM/5687 Gated 19/03/2021.

Dear Sir,

Kindly refer to above subject matter, please find enclosed herewith Environment Statement Report of Power Plant (25MW) of M/s J.K. Cement Works, Mangrol for the FY 2021-2022 for your reference and record. We trust you will find the same in order.

Thanking you.

Yours Faithfully For J.K. Cement Works, Mangrol

> R. B. M. Tripathi President (Operations)

Encl: as above.

Copy:

The Regional Officer, Rajasthan State Pollution Control Board, Near FCI Godown, Chanderiya, Distt. - CHITTORGARH (RAJ)-312021

Corporate Office

Padam Tower, 19 DDA Community Centre Okhla, Phase - 1, New Delhi - 110020, India

+011-49220000

admin.padamtower@jkcement.com

www.ikcement.com





Manufacturing Units at:


Nimbahera, Mangrol, Gotan (Rajasthan) | Muddapur (Karnataka) Jharli (Haryana) | Katni (M.P.) | Aligarh (U.P.) | Balasinor (Gujarat)



Registered Office : 🍙 Kamla Tower, Kanpur-208001, U.P., India. 📞 +91-512-2371478 to 85 👼 91-512-2399854 🔮 www.jkcement.com







ENVIRONMENTAL STATEMENT FORM - V

Environmental Statement for the financial year 2021-2022, ending the 31st March 2022

PART-A

1	Name an address of the owner/occupier of the industry operation or process	25 MW Captive Power Plant J. K. Cement Works, Mangrol C/o Kailash Nagar, Nimbahera Tehsil: Nimbahera, Chittorgarh (Rajasthan) PIN- 312617
Prir	Industry category mary - (STC Code), Secondary - (STC ede)	Primary
iii. Production capacity		25 MW Power Generation
iv.	Year of establishment-	Year 2014
v.	Date of last environmental statement submitted	17 th September 2021

PART-B

WATER AND RAW MATERIAL CONSUMPTION

i. WATER CONSUMPTION in m³/day

Process

: -

Nil

Cooling

:-

300 m³/day

Domestic

:--

5 m³/day

	Process water consumption per unit of products			
Name of products	During the previous financial year	During the current financial year		
	(2020-21) (KL/MWh)	(2021-22) (KL/MWh)		
1. POWER	0.45	0.40		

ii. RAW MATERIAL CONSUMPTION

Name of raw	Name of products	Consumption of raw material per unit of output			
material		During the previous During the current			
		financial year (2020-21)	financial year (2021-		
		(MT/MWh)	22)(MT/MWh)		
Coal	Power (Electricity)	0.715	0.821		

PART-C POLLUTION DISCHARGE TO ENVIRONMENT / UNIT OF OUTPUT

Pollutants	Quantity of pollutants discharged (Ton/Day)	Concentration of pollutants in discharge (mg/Nm3)	Percentage of variation from prescribed standards with reasons		
(a) Water	Effluent waste water gene	erated from blow down of co	ooling tower and DM plant		
	waste water treated in neutralization pit as prescribed by Rajasthan State				
	Pollution Control Board and treated water is being utilized in cement plant in				
	cooling purpose, hence maintaining Zero Liquid Discharge unit.				
(b) Air	Stack Emission				
PM	- 64.78 %				
SO2	- 77.20 %				
NOX	0.942	102.20	- 77.28 %		

Ambient Air Quality (yearly average) in $\mu g/m^3$

Location			Parameter	'S	
	PM10	PM2.5	SO2	NOx	CO (in mg/m³)
Near Time Office	44.8	30.2	15.8	22.2	669.9
Near Thermal Power Plant	46.2	31.6	18.4	23.9	721.1
Near Factory Gate	48.9	31.8	17.5	21.5	709.5
Near Colony Gate	40.1	28.8	15.3	22.5	683.2

STP treated water quality data

STP treated water Quality					
Parameters	Standards	Average results of YTD			
рН	Between 5.5 to 9.0	7.32			
Total Suspended solids	Not to exceed 100 mg/l	17.58			
Biological Oxygen Demand (3 days at 27 Degree C)	Not to exceed 30 mg/l	9.76			
Chemical Oxygen Demand	Not to exceed 250 mg/l	55.50			
Oil & Grease	Not to exceed 10 mg/l	4			
Ammonical Nitrogen (as N)	Not to exceed 50 mg/l	13.43			
Sulphide (as S)	Not to exceed 2.0 mg/l	<0.13			
Total Residual Chlorine	Not to exceed 1.0 mg/l	<0.11			

<u>Treated water quality of Neutralization pit data</u>

Treated	Treated water quality of Neutralization pit					
Parameters	Standards	Average of YTD				
Total Suspended Solids	Not to exceed 100 mg/L	21.74				
Oil & Grease	Not to exceed 10 mg/L	1.39				
Biochemical Oxygen Demand (3 days at 27°C)	Not to exceed 30 mg/l	10.67				
Free available Chlorine	Not to exceed 0.5 mg/l	0.09				
PH	Between 6.5 to 8.5	7.56				
Temperature	Shall not exceed 5° C above the receiving water temperature	4 oC higher than the intake water temperature				
Copper (as Cu)	Not to exceed 1.0 mg/l	0.02				
Zinc (as Zn)	Not to exceed 1.0 mg/l	0.01				
Total Chromium (as Cr)	Not to exceed 0.2 mg/l	0.04				
Iron (as Fe)	Not to exceed 1.0 mg/l	0.38				
Chemical Oxygen Demand	Not to exceed 250 mg/l	43.34				
Phosphate (as P)	Not to exceed 5.0 mg/l	0.41				

Noise level monitoring data

	Noise Monitoring Report FY 2021-22								
Month	Near time office			Near Thermal Near Raw Power Plant Ga				ear Packing Plant Gate	
	Day	Night	Day	Night	Day	Night	Day	Night	
Apr-21	64.7	48.1	65.2	52.6	68.8	57.1	66.9	51.5	
May-21	62.8	47.3	63.1	49.4	65.7	52	64.4	50.8	
Jun-21	67.3	55.7	68.4	56.3	70.1	59.9	70.6	61.2	
Jul-21	65.1	54.6	66.7	53.3	67.9	55.1	62.1	49.9	
Aug-21	64.2	53.9	67.1	53.1	66.2	52.7	63.9	48.6	
Sep-21	61.8	50.1	62.1	48.3	64.7	51.4	60.6	47.1	
Oct-21	60.3	49.7	61.4	47.4	63.9	51.1	58.3	45.6	
Nov-21	62.2	50.7	63.4	48.7	61.4	50.3	61.7	46.8	
Dec-21	59.8	45.1	61.7	50.6	60.8	49.7	57.6	43.2	
Jan-22	63.8	46.6	64.1	51.3	69.2	53.4	65.7	52.9	
Feb-22	56.8	42.3	58.4	49.1	62.6	49.9	62.8	50.6	
Mar-22	59.7	45.1	56.7	46.8	66.8	53.7	61.3	49.2	
YTD	62.38	49.10	63.19	50.58	65.68	53.03	62.99	49.78	

PART-D

(As specified under Hazardous & Other Waste Management Rules-2016)

Hazardous waste	Total Qu	antity
	During previous financial year (2020-21) (KL)	During current financial year (2021-22) (KL)
(a) From process	Used oil (5.1)- 34.80 *	Used oil (5.1)- 5.0*
	Waste oil (5.2)- NIL	Waste oil (5.2)- 31.6*
(b) From pollution Control facilities	Not applicable	Not applicable

*including Cement Plant Line-1, Line-2, & Line-3, CPP, WHRS, Mines & Colony. Hazardous waste generated are being sold through authorized recycler by CPCB.

PART-E SOLID WASTE

		Total Quantity		
		During previous financial year (2020-21) (MT/Year)	During current financial year (2021-22) (MT/Year)	
(a)	From process (Bed Ash)	6150.34	5505.89	
(b)	From pollution control facility (Fly Ash)	40393.04	49608.52	
(c)	Quantity reutilized with in the unit	97.67%	98.42%	

Fly ash collected in pollution control equipment (ESP) is utilized for PPC grade cement manufacturing in own cement plant within the premises & bed ash generated from process in also utilized for cement manufacturing and coal dust collected from bag filters is recycled into the system.

PART-F

PLEASE SPECIFY THE CHARACTERISATIONS (IN TERMS OF COMPOSITION AND QUANTUM) OF HAZARDOUS AS WELL AS WASTES AND INDICATE DISPOSAL PRACTICE ADOPTED FOR BOTH THESE CATEGORIES OF WASTES.

- 1) Hazardous waste generated in the form of used Oil / spent oil, waste / residue containing oil, which is stored in barrels at safe & dedicated area and sold to recycler approved by Central Pollution Control Board.
- 2) Fly ash collected in pollution control equipment (ESP) is utilized for PPC grade cement manufacturing in own cement plant within the premises & bed ash generated from process in also utilized for cement manufacturing and coal dust collected from bag filters is recycled into the system.

PART-G

IMPACT OF THE POLLUTION ABATEMENT MEASURES TAKEN ON CONSERVATION OF NATURAL RESOURCES AND ON THE COST OF PRODUCTION.

Industry has installed electrostatic precipitator (ESP) at boiler for stack and bag filters at transfer points to control the particulate matter and fugitive emission. The particulate matter collected from ESP in the form of fly ash is completely utilized in PPC cement production.

PART-H

ADDITIONAL MEASURES / INVESTMENT PROPOSALS FOR ENVIRONMENTAL PROTECTION INCLUDING ABATEMENT POLLUTION, PREVENTION OF POLLUTION.

Installed new technology NOx and SO2 analyzer to provide real time emission data and same is being transferred to RSPCB and CPCB web portal.

PART-I

ANY OTHER PARTICULARS FOR IMPROVING THE QUALITY OF ENVIRONMENT

- 1) Monitoring of stack emission and ambient air and water quality is being done regularly as mentioned in consent to operate.
- 2) 4 nos. of Continuous Ambient Air Quality Monitoring Systems (CAAQMS) has been installed at periphery of the plant.
- 3) Continuous Emission Monitoring Systems (CEMS) for PM, SO2 & NOx have been installed at the Boiler ESP stack and real time data transfer to RSPCB & CPCB.
- 4) Bag filters have been installed at various material transfer points to control fugitive emission.
- 5) Effluent generated from the cooling tower blow down and DM plant waste water is being treated through neutralization and used in cement plant for cooling purpose, hence maintaining Zero Liquid Discharge Unit (ZLD). PTZ Camera is installed.
- 6) Air cooled condenser installed.
- 7) Fly ash generated from CPP, convey through pneumatic system and stored in silo, and utilized in own cement plant for PPC cement production.
- 8) Apart from this fly ash purchased from nearby thermal power plant and use for cement production.
- 9) Proper Housekeeping and cleaning is being done with the help of four road sweeping machines.
- 10) Domestic waste water generated is being treated in sewage treatment plant (STP). Treated water is utilized for plantation / horticulture development.
- 11) Cover shed Constructed to store the coal, to avoid fugitive emission.
- 12) 16 Rain water harvesting structures have been constructed in plant and colony area to recharge ground water.
- 13) Cemented road constructed to avoid fugitive dust generation during the movement of vehicle.
- 14) Telemetry system installed for online ground water level monitoring.
- 15) Total 155401 nos. of tree planted till 2020-21 in area of 41.89 Ha. Apart from this we have planted 11425 nos. of tree sapling in FY 2021-22 in Cement.
- 16) Oxygen generation plant installed to catch the requirement of Oxygen during Covid-19.
